

THE HUBBELL ADVANTAGE

HUBBELL PT56 vs HATCO PMG-100 Feature Comparison

For Door-Type and Undercounter Dishmachines





D :		_
Р	เก	h

	F 130		r Ma-100
Application Sizing BTU Input Recovery	Desgined specifically for Door-Type Dishmachines 55,000 75 GPH at 70°F rise, 132 GPH at 40°F rise	~	Oversized for Door-Type Dishmachines 105,000 138 GPH at 70°F rise, 241 GPH at 40°F rise
Internal Operation and Gas Modulation	Full gas modulation (Patented VariFlame™ Technology) increases reliability, maximizes efficiency and temperature control, and reduces cycling	~	Control system is slower than a reacting temperature sensing system which is less reliable and results in temperature fluctuations. There are more components that can fail and failure may result in heat exchanger damage.
Exterior Jacket and Base	All Stainless Steel	/	Stainless Steel front and top, powdercoat sides and back (All Stainless Steel - \$235 Option)
Storage Tank	3 Gallon, Stainless Steel		4.75 Gallon, Stainless Steel
Venting	Ventless	/	4" forced air system
Ignition	Direct Spark Ignition	*	Standing Pilot
Wall Mountable	Yes	~	No
Front Panel Access to All Internal Components	Yes	*	No
Pressure Reducing Valve	Brass (Free Upgrade)	/	Cast Iron (Brass is \$144 Option)
Safety Features	 Pilot-less ignition Flame rectification Gas valve shut-off in .8 second with no flame Redundant gas solenoid ECO high temp shut-off @210 F with auto reset Pressure relief @125 PSI Pressure reducing valve w/ bypass, 	✓	T&P relief valve Pressure reducing valve w/ bypass Low-water cut-off
Dimensions (Width x Depth x Height)	26 1/4" x 17 3/4" x 22 3/4"	/	27" x 20 3/4" x 31"
Dry Weight (Shipping Weight)	96 lbs (134 lbs)	*	160 lbs (180 lbs)
Current List Price (Aug '17)	\$9,850	*	\$11,782

