Ladderback Swivel Barstool


ASSEMBLY INSTRUCTIONS



PARTS LIST A Seat 1/PC C Seat Screws 6/PC E Bolts 4/PC G Wrench 1/PC B Seat Frame 1/PC D Base with Swivel Plate 1/PC F Nuts 4/PC H Allen Key 1/PC NOTES

STEP 1

To Start, place the seat (A) upside down on a table and set the seat frame (B) upside on top of the cushion. Be sure to center the frame on top of the cushion. The front edge of the cushion should be parallel to the front edge of the seat frame.



STEP 2


Using a screwdriver or drill, attach the 6 seat screws (C) and secure the cushion to the frame through the screw holes on the seat frame.

Before starting, make sure you have all the required pieces. A screwdriver is required for assembly (not included).

Use caution when assembling the base as the swivel plate

A drill is optional for easier assembly.

has moving parts.



Ladderback Swivel Barstool

ASSEMBLY INSTRUCTIONS



STEP 3

Next, rotate the swivel plate on top of the base (D) so that all four holes are accessible.



STEP 5

Ensure all bolts and screws are tightened securely. Carefully flip the stool and turn it right side up.



STEP 4

Flip the base upside down and position it on top of the seat frame and seat. Align the holes in the swivel plate with the frame. Next, insert a bolt (E) through a hole in the swivel plate and secure with a nut (F). Use the wrench (G) to hold the nut securely while you tighten the bolt with the allen key (H). Repeat for all four holes in the swivel plate.

