

INTRODUCING THE VH HOOD FOR MOFFAT OVENS

FEATURES

1. Ventless operation provides flexibility to locate ovens in variety of indoor spaces
2. Two-speed fan minimizes energy use
3. Integral heat-exchanger removes moisture from air – improving comfort
4. Two stages of filtration remove contaminants from cooking
5. Charcoal filter reduces odors
6. UL Listed – draws 1.6A @120V



VH Hoods available for Models

- E31 = VH31
- E32 = VH32
- E33 = VH33
- E35 = VH35

HOW IT WORKS

1. When a cooking cycle starts, the exhaust fan automatically operates at low speed
2. Fan switches to high speed when either the door is opened or the cooking cycle ends
3. Air is simultaneously pulled through the front of the hood and from the top of the oven and treated:
 1. First by a baffle grease filter to remove heavy particles
 2. It then flows through a mesh filter to separate out smaller particles
 3. Next comes the heat exchanger to remove moisture from the air
 4. The final step is the carbon filter to reduce odors before discharging the cleaned air back to the space



HOODS AVAILABLE FOR ALL MOFFAT OVENS



E31D4



E32D5



E33T5



E35D6-26

Halton/Moffat Convection Oven Hood
For Moffat Oven E31D4

**MOFFAT
VH31**

EXPLODED VIEW

32.5 in [827mm]
13.5 in [343mm]
15.3 in [389mm]

HALTON/MOFFAT CONVECTION HOOD MAIN HOOD

| | | | | | | |
|-------------------|-----------------------------|------|---------|----------------|-------|---|
| VOLTAGE | 120 | AMPS | LOW 0.4 | HIGH 1.6 | PHASE | 1 |
| MATERIAL | 18 & 16 GA. STAINLESS STEEL | | | | | |
| PLUG | NEMA 5-15 | | LOW | HIGH | | |
| WEIGHT | 130 LBS | CFM | 132 | 248 | | |
| QUANTITY OF ORDER | SOUND #B | 62 | 73 | PREFER PRODUCT | | |

Halton

Halton/Moffat Convection Oven Hood
For Moffat Oven E32D/E32T

**MOFFAT
VH32**

EXPLODED VIEW

29.2 in [742mm]
13.4 in [340mm]
15.3 in [389mm]

HALTON/MOFFAT CONVECTION HOOD MAIN HOOD

| | | | | | | |
|-------------------|-----------------------------|------|---------|----------------|-------|---|
| VOLTAGE | 120 | AMPS | LOW 0.4 | HIGH 1.6 | PHASE | 1 |
| MATERIAL | 18 & 16 GA. STAINLESS STEEL | | | | | |
| PLUG | NEMA 5-15 | | LOW | HIGH | | |
| WEIGHT | 130 LBS | CFM | 132 | 248 | | |
| QUANTITY OF ORDER | SOUND #B | 62 | 73 | PREFER PRODUCT | | |

Halton

Halton/Moffat Convection Oven Hood
For Moffat Oven E33D/E33T

**MOFFAT
VH33**

EXPLODED VIEW

24.3 in [617mm]
13.3 in [338mm]
15.3 in [389mm]

HALTON/MOFFAT CONVECTION HOOD MAIN HOOD

| | | | | | | |
|-------------------|-----------------------------|------|---------|----------------|-------|---|
| VOLTAGE | 120 | AMPS | LOW 0.4 | HIGH 1.6 | PHASE | 1 |
| MATERIAL | 18 & 16 GA. STAINLESS STEEL | | | | | |
| PLUG | NEMA 5-15 | | LOW | HIGH | | |
| WEIGHT | 108 LBS | CFM | 132 | 248 | | |
| QUANTITY OF ORDER | SOUND #B | 62 | 73 | PREFER PRODUCT | | |

Halton

Halton/Moffat Convection Oven Hood
For Moffat Oven E35D-26/E35T-26

**MOFFAT
VH35-26**

EXPLODED VIEW

26.1 in [663mm]
13.5 in [343mm]
15.3 in [389mm]

HALTON/MOFFAT CONVECTION HOOD MAIN HOOD

| | | | | | | |
|-------------------|-----------------------------|------|---------|----------------|-------|---|
| VOLTAGE | 120 | AMPS | LOW 0.9 | HIGH 3.5 | PHASE | 1 |
| MATERIAL | 18 & 16 GA. STAINLESS STEEL | | | | | |
| PLUG | NEMA 5-15 | | LOW | HIGH | | |
| WEIGHT | 170 LBS | CFM | 300 | 673 | | |
| QUANTITY OF ORDER | SOUND #B | 64 | 73 | PREFER PRODUCT | | |

Halton

MAINTENANCE IS SIMPLE

DAILY

- Wipe exterior surfaces of hood with soft cloth and mild cleaning solution

WEEKLY

- Remove, soak, wash and rinse baffle filter and mesh filter in sink
- Remove and clean filter tray
- Reinstall filter tray and filters after allowed to air dry

QUARTERLY

- Replace carbon filter

