



EXTENDED BACKWATER VALVE

## Inground backwater control.



- Prevents the reverse flow of backwater into a structure as a result of a plugged sewer system, excess volume in the system or ground water flooding.

- Installs discretely outside, below grade, between the structure and the standard clean-out.

- Lifts up and out of housing for above ground maintenance and inspection.

Action videos and full details  
@ [rectorseal.com/cleancheck](http://rectorseal.com/cleancheck)







## DWV SOLUTIONS

# Clean Check®

## Extendable Backwater Valve Kit



STATE OF  
WISCONSIN  
APPROVED

Code	Description	Qty
97023	3" PVC	1
97024	4" PVC	1
97026	6" PVC	1
97034	4" PVC w/adaptor & plug	1
97003	3" ABS	1
97004	4" ABS	1
97014	4" ABS w/adaptor & plug	1
96980	3"-4" flapper	1
96983	6" flapper	1
97022	3"-4" PVC rebuild kit	1
97025	6" PVC rebuild kit	1

**Application** • Prevents sewage backup into plumbed structures as a result of a plugged sewer system, excess volume in the system or groundwater flooding

**Recommended for** • PVC • ABS

### FEATURES

- No manhole required
- Installs discretely outside - up to 12' below ground level
- Above ground outdoor maintenance accessibility eliminates hidden access indoor applications, and the sewer odor and mess of indoor maintenance



Lower Collar with Flapper. 3" and 4" collars accept both 2" and 4" standard pipe 6" Clean Check collars accept standard 4" pipe.

Optional  
Clean-out with  
adapter plug ▶

Replaceable  
75 PSI flapper



Snap-in, pull-out flapper

Available in 3", 4" and 6" sizes ▶

◀ Valve Body

◀ Upper Collar