

BENEFITS OF INDUCTION



FASTER Rapid heat delivery with quicker recovery than gas or electric.



COST EFFECTIVE 90% less expensive than canned fuel and helps save on air conditioning costs.



PRECISE Even heating, no hot spots. Adjusts automatically as food is added or subtracted.



SAFER No open flame or hot coils; surface cool to the touch when pan is removed.



MORE EFFICIENT 50% more efficient than gas; heats pans directly without losing energy into the air.



COOLER Low radiant heat keeps room cool. Heat stops when pan is removed.



CLEANER Sealed glass surface wipes easy. No stocking, spilling or disposing of canned fuel.



SPRING USA INDUCTION

COUNTERTOP | RECONFIGURABLE | DROP-IN | HIDDEN

ONE-YEAR OVERNIGHT EXCHANGE WARRANTY on all Spring USA ranges in the continental United States

PROVEN RELIABILITY with a less than 1% failure rating

SMART SCAN® TECHNOLOGY safety features adjusts electrical output for pan size and construction, adjusts instantly to voltage fluctuations and auto shuts off after two minutes of non-use

AUTOMATIC PAN RECOVERY seamlessly adjusts and recognizes pans as you lift or tilt from the surface - similar to a gas range but with no flash point and better cost savings than conventional gas

GLASS TOP IS 25% THICKER THAN COMPETITION.
5mm tempered glass is reinforced for durability

EASY TO USE AND MAINTAIN.
Includes easy to read LED controls, self-leveling, slip-proof legs that prevent scratched surfaces, and dials are heavy duty knurled knobs*





LoPRO™

NEW!

The LoPRO™ slimline induction range is a new series of lightweight, compact induction ranges designed for durability and performance backed by Spring USA's industry-leading induction technology.

- Sleek, low-profile housing less than 2.4" high
- LED touch controls accessible via an easy to clean, tempered glass top
- Exclusive SmartScan® technology and Automatic Pan Recovery
- Available in low watt hold-only, cook/ hold, and double hob models
- FCC, ETL listed to: UL 197, CSA C22.2 #109 (cETL), NSF-4



HOLD-ONLY INDUCTION RANGE

SM-300LP

300 W | 110-120 V | 2.5 amps | 60 Hz
4 Settings | 145-185°F/62-85°C
NEMA 5-15P



COOK/HOLD INDUCTION RANGE

SM-1800LP

1800 W | 110-120 V | 15 amps | 60 Hz
Cook Power Levels 1-20
Temp Mode, Temp 110°F - 400°F
NEMA 5-15P



HOLD ONLY INDUCTION RANGE

SM-1800LP-D

900x2 W | 110-120 V | 7.5x2 amps | 60 Hz
Cook Power Levels 1-20
Temp Mode, Temp 110°F - 400°F
NEMA 5-15P



MAX INDUCTION®

The first induction ranges to debut in the United States - MAX Induction offers optimal durability and performance with greater efficiency, precision, and safety over gas or flame.

- Reaches max temperature in just 60 seconds
- Exclusive SmartScan® technology assures correct temperature for optimal performance and energy-efficiency
- No flash points and better cost savings than conventional gas ranges
- 5mm glass top, the thickest glass surface in its class
- Automatic Pan Recovery seamlessly adjusts and recognizes pans as you lift or tilt from the surface during cooking, sauteing, or flipping
- Available in stainless steel and titanium for countertop models, as well as reconfigurable, drop-in, and hidden models



**PLUG-IN TWO IN ONE
15-AMP CIRCUIT**

HOLD-ONLY 650 WATT RANGE

SM-651C-T

Countertop
650 W | 110-120 V | 5.4 amps | 60 Hz
4 Settings | 145-185°F/62-85°C
NEMA 5-15P
9.8 lbs
12.5"W x 16.0"D x 3.1"H
FCC, ETL, ETL-Sanitation to NSF-4,
CETL, UL 197
7 ft. cord

INDUCTION RANGES



**COOK & HOLD 1800 WATT RANGE
SM-181C**

Countertop
1800 W | 110-120 V | 15 amps | 60 Hz
20 Settings | 110-400°F/43-204°C
NEMA 5-15P
11.8 lbs
12.5"W x 16.0"D x 3.1"H
FCC, ETL, ETL-Sanitation to NSF-4,
CETL, UL 197
7 ft. cord



**COOK & HOLD 1800 WATT RANGE
SM-181C-T**

Countertop
1800 W | 110-120 V | 15 amps | 60 Hz
20 Settings | 110-400°F/43-204°C
NEMA 5-15P
11.8 lbs
12.5"W x 16.0"D x 3.1"H
FCC, ETL, ETL-Sanitation to NSF-4,
CETL, UL 197
7 ft. cord



**COOK & HOLD 2600 WATT RANGE
SM-261C**

Countertop
2600 W | 208-240 V | 10.8 amps | 60 Hz
20 Settings | 110-400°F/43-204°C
NEMA 6-20P
11.8 lbs
12.9"W x 16.5"D x 4.0"H
FCC, ETL, ETL-Sanitation to NSF-4,
CETL, UL 197
7 ft. cord

SM-263C 
2600 W | 220-240 V | 10.8 amp | 50-60 Hz
CEE 7/7 Schuko Plu

SM-263CU UK
2600 W | 220-240 V | 10.8 amps | 50-60 Hz
BS 1363 (13A) U.K. Plug



COUNTERTOP



**COOK & HOLD 3500 WATT RANGE
SM-351C**

Countertop
3500 W | 208-240 V | 14.6 amps | 60 Hz
20 Settings | 110-400°F/43-204°C
NEMA 6-20P
18.0 lbs
15.0"W x 20.2"D x 5.8"H
FCC, ETL, ETL-Sanitation to NSF-4,
CETL, UL 197
7 ft. cord

SM-353C 
3500 W | 220-240 V | 14.6 amps | 50-60 Hz
CEE 7/7 Schuko Plug

SM-353CU UK
3000 W | 220-240 V | 12.5 amp | 50-60 Hz
BS 1363 (13A) U.K. Plug



**COOK & HOLD 3500 WATT RANGE
SM-351C-FT**

Countertop
3500 W | 208-240 V | 14.6 amps | 60 Hz
4 Time Settings | 110-400°F/43-204°C
NEMA 6-20P
18.0 lbs
15.0"W x 20.2"D x 5.8"H
FCC, ETL, ETL-Sanitation to NSF-4,
CETL, UL 197
30, 45, 70 or 80 sec countdown timer
7 ft. cord

SM-353C-FTU UK
3000 W | 220-240 V
12.5 amps | 50-60 Hz
BS 1363 (13A) U.K. Plug



RECONFIGURABLE INDUCTION

REMOVABLE CONTROLS for countertop or drop-in application!



HOLD-ONLY ROUND INDUCTION RANGE

SM-360R
 Countertop, Drop-in, Flushmount
 360 W | 110-120 V | 3 amps | 60 Hz
 4 Settings | 145-185°F/62-85°C
 NEMA 5-15P



WYNWOOD BY SKYRA™ INDUCTION DOT DISPLAY STAND

SK-145360R
 13.5" Diameter
 Food-safe, nonporous, easy to clean

The Spring USA Induction DOT round induction range is the perfect solution for powerful induction in tight spaces. Compact in size with just a 9.1" diameter, these ranges take up minimal countertop space for either drop-in, flush-mount, or countertop induction.

- Low profile design, only 9.1" in diameter
- 3 different configurations: countertop, drop-in, or flush-mount
- Daisy-chain up to 4 units on a single 15-amp circuit
- Removable control box with touch controls & indicator lights
- Sleek, round housing with stainless-steel rim
- NSF-Certified, UL Rated NSF-4

UNLIMITED INDUCTION™

- Edge-to-Edge technology can read one or more vessels, regardless of where they are placed
- Power receptacle in back of unit
- Reads multiple pans regardless of placement
- Removable controls allow for use on countertop or drop-in



INDUCTION RANGES

FEATURES



DAISY CHAIN
 Outlet in back, connect up to five units on one 15-amp circuit

HOLD-ONLY 300 WATT RANGE
SM-300CR
 Countertop or Built-in
 300 W | 110-120 V | 2.5 amps | 60 Hz
 4 Settings | 145-185°F/62-85°C
 NEMA 5-15P
 10.0 lbs
 14.0"W x 14.0"D x 3.6"H
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197
 7 ft. cord
 Minimum vessel size 4.7"/12cm

RECONFIGURABLE





MAX INDUCTION®

PATENTED



COOK & HOLD 2500 X 2 WATT DOUBLE RANGE

SM-251-2CR

Countertop or Built-in
 2500x2 W | 208-240 V | 10.4 x 2 amps | 60 Hz
 20 Settings | 110-400°F/43-204°C
 NEMA 6-30P
 29.1 lbs
 28.0"W x 18.1"D x 4.6"H
 FCC, ETL, ETL-Sanitation to NSF-4,
 CETL, UL 197
 7 ft. cord

SM-253-2CR 
 2500x2 W | 220-240 V | 20.8 x 2 amps | 50-60 Hz
 Plug & receptacle to be supplied by the
 customer, based on country code



REMOVABLE CONTROLS for four possible applications - countertop or drop-in in either horizontal or vertical position

GRIDDLE ATTACHMENT

Effortlessly cook breakfast items, burgers, cheesesteaks, and other grilled favorites by harnessing the power and precision of MAX Induction with this griddle overlay attachment.



MAX INDUCTION COUNTERTOP GRIDDLE OVERLAY

SMG251-6

Product dimensions: 32.25" W x 15.25" D x 6" H
 Cooking Area: 28.25" W x 15.15" D
 Weight: 54 lbs.
 10 mm thick stainless steel cooking surface
 Hard chromium plating
 Designed for use with/ retrofits, SM-251-2CR & SM-253-2CR



COOK & HOLD 3500 WATT WOK RANGE W/CONCAVE TOP

SM-351WCR

Countertop or Built-in
 3500 W | 208-240 V | 14.6 amps | 60 Hz
 20 Settings | 110-400°F/43-204°C
 NEMA 6-20P | 17.6 lbs | 14.6"W x 19.1"D x 5.7"H
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197
 7 ft. cord



COOK & HOLD 3500 WATT WOK RANGE W/CONCAVE TOP

SM-351WCR-8

Includes 8217-60/32 Vulcano Wok Pan
 Countertop or Built-in
 3500 W | 208-240 V | 14.6 amps | 60 Hz
 20 Settings | 110-400°F/43-204°C
 NEMA 6-20P | 17.6 lbs | 14.6"W x 19.1"D x 5.7"H
 FCC, ETL, ETL-Sanitation to NSF-4,
 CETL, UL 197
 7 ft. cord

| | |
|---|-------------------------|
| SM-353WCR-8  | SM-353WCRU-8 UK |
| 3500 W 220-240 V | 3000 W 220-240 V |
| 14.6 amps 50-60 Hz | 12.5 amps 50-60 Hz |
| CEE 7/7 16 A Schuko | BS 1363 (13A) U.K. Plug |
| Plug | |



COOK & HOLD 3500 WATT WOK RANGE W/CONCAVE TOP

SM-351WCR-6

Includes 8216-60/34 Primo Wok Pan
 Countertop or Built-in
 3500 W | 208-240 V | 14.6 amps | 60 Hz
 20 Temp Settings | 110-400°F/43-204°C
 NEMA 6-20P | 17.6 lbs | 14.6"W x 19.1"D x 5.7"H
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197
 7 ft. cord

| | |
|---|-------------------------|
| SM-353WCR-6  | SM-353WCRU-6 UK |
| 3500 W 220-240 V | 3000 W 220-240 V |
| 14.6 amps 50-60 Hz | 12.5 amps 50-60 Hz |
| CEE 7/7 16 A Schuko | BS 1363 (13A) U.K. Plug |
| Plug | |

DROP-IN INDUCTION

REMOVABLE CONTROLS & FLUSHMOUNT GLASS TOP for drop-in application

MAX INDUCTION®

PATENTED



HOLD ONLY 650 WATT RANGE

SM-651R

Built-in
 650 W | 110-120 V | 5.4 amps | 60 Hz
 4 Settings | 145-185°F/62-85°C
 NEMA 5-15P | 10.6 lbs
 12.6"W x 13.4"D x 3.3"H
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197



SM-653R
 650 W | 220-240 V | 2.7 amps | 50-60 Hz
 CEE 7/7 16 A Schuko Plug

SM-653RU UK

650 W | 220-240 V | 2.7 amps | 50-60 Hz
 BS 1363 (13A) U.K. Plug

COOK & HOLD 1800 WATT RANGE

SM-181R

Built-in
 1800 W | 110-120 V | 15 amps | 60 Hz
 20 Settings | 110-400°F/43-204°C
 NEMA 5-15P | 10.8 lbs
 12.6"W x 13.4"D x 3.3"H
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197

COOK & HOLD 2600 WATT RANGE

SM-261R

Built-in
 2600 W | 208-240 V | 10.8 amps | 60 Hz
 20 Settings | 110-400°F/43-204°C
 NEMA 6-20P | 11.7 lbs
 12.6"W x 13.4"D x 3.3"H
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197



SM-263R
 2600 W | 220-240 V | 10.8 amps | 50-60 Hz
 CEE 7/7 16 A Schuko Plug

SM- 263RU UK

2600 W | 220-240 V | 10.8 amps | 50-60 Hz
 BS 1363 (13A) U.K. Plug



HIDDEN MULTISURFACE

REMOVABLE CONTROLS & SPECIALIZED GLASS TOP for countertop undermount application

MAX INDUCTION®

PATENTED

Intentionally designed to work with Spring USA SmartStone® to be mounted under the countertop for a completely hidden operation. Hold-only range can be hidden under approved surfaces for a completely seamless operation.

SEEMLESSLY MOUNTS beneath the countertop to eliminate any cutting

SAFE FOR USE under SmartStone or other approved surfaces up to 2 cm thick

INDUCTION TECHNOLOGY safely senses & heats the serving vessel, not the countertop

HOLD ONLY MULTISURFACE 650 WATT RANGE

SM-651SS

Built-in
 650 W | 110-120 V | 5.4 amps | 60 Hz
 4 Settings | 145-185°F/62-85°C
 NEMA 5-15P | 10.6 lbs
 12.6"W x 13.4"D x 3.3"H
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197



SURFACEGUARD SES651
 8" Dia. x 1"H

| SURFACE BRAND | SURFACE MATERIAL | SURFACE THICKNESS | VESSELS |
|----------------|------------------|--------------------|--|
| SMARTSTONE™ | PORCELAIN | 1.2 cm / 2 cm max. | 1.2 cm Thick: All Spring USA Induction Ready Vessels |
| SILESTONE* | QUARTZ | 1.2 cm / 2 cm max. | |
| FIANDRE* | PORCELAIN | 1.2 cm / 2 cm max. | |
| EIFFELGRES* | PORCELAIN | 1.2 cm / 2 cm max. | 2 cm Thick: Round Sauteuse Server, Square Server, Oatmeal/Soup Server, Servella, Ironlite, Wynwood by Skyra |
| IRIS CERAMICA* | PORCELAIN | 1.2 cm / 2 cm max. | |
| FMG* | PORCELAIN | 1.2 cm / 2 cm max. | |
| ARIOSTEA* | PORCELAIN | 1.2 cm / 2 cm max. | |

*Requires SurfaceGuard. For All Other Surfaces & Vessels, Please Inquire for Testing.

CUSTOM INDUCTION RANGE CASES

Ranges offer front-of-house warming and cooking with back-of-house power and durability.



SINGLE RANGE CUSTOM CASES

HIDDEN HOLD ONLY 650 WATT RANGE W/CUSTOM CASE

SRC-651SS

650 W | 110-120 V | 5.4 amps | 60 Hz
 4 Settings | 145-185°F/62-85°C
 NEMA 5-15P
 14.125"W x 20.125"D x 6.0"H
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197
 7 ft. cord

DOUBLE RANGE CUSTOM CASES

TWO HIDDEN HOLD ONLY 650 WATT DOUBLE RANGES W/CUSTOM CASE

SRC-2-651SS

650x2 W | 110-120 V | 5.4 x 2 amps | 60 Hz
 4 Settings | 145-185°F/62-85°C
 NEMA 5-15P
 33.5"W x 20.125"D x 6.0"H
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197
 7 ft. cord

COOK & HOLD 1800 WATT RANGE W/CUSTOM CASE

SRC-181SS

1800 W | 110-120 V | 15 amps | 60 Hz
 20 Settings | 110-400°F/43-204°C
 NEMA 5-15P
 14.125"W x 20.125"D x 6.0"H
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197
 7 ft. cord

TWO COOK & HOLD 1800 WATT DOUBLE RANGES W/CUSTOM CASE

SRC-2-181SS

1800x2 W | 110-120 V | 15 x amps | 60 Hz
 20 Settings | 110-400°F/43-204°C
 NEMA 5-15P
 33.5"W x 20.125"D x 6.0"H
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197
 7 ft. cord

COOK & HOLD 2600 WATT RANGE W/CUSTOM CASE

SRC-261SS

2600 W | 208-240 V | 10.8 amps | 60 Hz
 20 Settings | 110-400°F/43-204°C
 NEMA 6-20P
 14.125"W x 20.125"D x 6.0"H
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197
 7 ft. cord

TWO COOK & HOLD 2600 WATT DOUBLE RANGES W/ CUSTOM CASE

SRC-2-261SS

2600x2 W | 208-240 V | 10.8 x 2 amps | 60 Hz
 20 Settings | 110-400°F/43-204°C
 NEMA 6-20P
 33.5"W x 20.125"D x 6.0"H
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197
 7 ft. cord

PROFESSIONAL COOKWARE

*Back of the House Durable.
 Front of the House Beautiful.*

“When you buy quality, you buy only once.
 Spring USA cookware can last a lifetime. Spring USA
 offers great quality at reasonable prices.”

RANDY ZWEIBAN | EXECUTIVE CHEF | CHICAGO