



WARMING & COOLING
SYSTEMS

Low Power Solutions.
High-End Quality.



iLUME

NEW!

PATENT - PENDING

In a class of its own, the iLUME heat lamp offers a modern design and superior infrared heat technology for better presentation and performance over traditional heat lamps. Powered by medium heat wave technology, the iLume offers more even heat distribution with greater energy efficiency than your standard heat lamp by penetrating heat energy into the food instead of simply warming the foods surface.

- Dual articulating joints, 170° swivel
- 12" Carbon fiber medium-wave IR heating element
- 2 LED illuminate food at 4000k color temperature
- Energy efficient, only 300 watts provides warming at 60% energy consumption
- Daisy-chain feature can connect 5 iLumes to a single 120V, 15-amp outlet (US only)
- 300W, 110V - 120V, Phase 1, 60Hz power rating
- ETL listed, UL 197, cETL, NSF certified



INFRARED HEAT LAMP
2791-ILT

300 W | 110-120 V
NEMA 5-15P
12.8 lbs



FINGERPRINT RESISTANT



WATCH
THE
VIDEO

ADJUSTABLE ARM HEAT LAMPS

- Weighted base provides stability from tipping
- 18/8 stainless steel with mirror polish or matte black finish
- Included shatterproof bulb
- 360 degree adjustable neck
- Integrated outlet in stem
- Daisy-chain additional heat lamps or connect a warming tray in a single 15 amp outlet



**SINGLE ADJUSTABLE
ARM POLISHED**

2791-6E
250 W | 110-120 V | 2.1 amps | 60 Hz
NEMA 5-15P
12.0 lbs
10.5"W x 7.1"D base, (15.1"D from back of base to farthest edge of shade) x 24.9"H (with shade parallel to base)
ETL. UL
Daisy chain 6 units on a 15-amp circuit
5.5 ft. cord



2791-6E-220 
250 W | 220-240 V | 1.0 amps | 50-60 Hz
CEE-7/7 16A Schuko Plug
(BS 1363 (13A) U.K. Plug also available)
Daisy chain 12 units on a 15-amp circuit



**DOUBLE ADJUSTABLE NECK
2792-6E**

500 W | 110-120 V | 4.2 amps | 60 Hz
NEMA 5-15P
16.4 lbs
10.5"W x 7.1"D base, (15.1"D from back of base to farthest edge of shade) x 24.9"H (with shade parallel to base)
ETL. UL
Daisy chain 3 units on a 15-amp circuit
5.5 ft. cord

2792-5-220 
250 W | 220-240 V | 1.0 amps | 50-60 Hz
CEE-7/7 16A Schuko Plug
(BS 1363 (13A) U.K. Plug also available)



**SINGLE TITANIUM
2791-6EB**

250 W | 110-120 V | 2.1 amps | 60 Hz
NEMA 5-15P
12.0 lbs
10.5"W x 7.1"D base, (15.1"D from back of base to farthest edge of shade) x 24.9"H (with shade parallel to base)
ETL. UL
Daisy chain 6 units on a 15-amp circuit
5.5 ft. cord



FINGERPRINT RESISTANT



**DOUBLE TITANIUM
2792-6EB**

500 W | 110-120 V | 4.2 amps | 60 Hz
NEMA 5-15P
16.4 lbs
10.5"W x 7.1"D base, (15.1"D from back of base to farthest edge of shade) x 24.9"H (with shade parallel to base)
ETL. UL
Daisy chain 3 units on a 15-amp circuit

2792-6EB-220 
500 W | 220-240 V | 1.0 amps | 50-60 Hz
CEE-7/7 16A Schuko Plug
(BS 1363 (13A) U.K. Plug also available)

PIVOT HEAD HEAT LAMPS

- Premium 18/10 brushed stainless steel
- Easy to use on/off toggle switch
- Solid positioning, pivoting head design
- Included shatterproof bulbs



**SINGLE
2791-5**

250 W | 110-120 V | 2.1 amps | 60 Hz
NEMA 5-15P
14.6 lbs
8.0"W x 10.5"D base, (16.7"D from back of base to farthest edge of shade) x 25.6"H (with shade parallel to base)
ETL. UL | 5.5 ft. cord

2791-5-220 
250 W | 220-240 V | 1.0 amps | 50-60 Hz
CEE-7/7 16A Schuko Plug
(BS 1363 (13A) U.K. Plug also available)



**DOUBLE
2792-5**

500 W | 110-120 V | 4.2 amps
60 Hz
NEMA 5-15P
22.8 lbs
8.0"W x 10.5"D base, (15.7"D from back of base to farthest edge of shade) x 25.6"H (with shade parallel to base)
ETL. UL | 5.5 ft. cord

2792-5-220 
500 W | 220-240 V | 2.1 amps | 50-60 Hz
CEE-7/7 16A Schuko Plug
(BS 1363 (13A) U.K. Plug also available)

ADJUSTABLE HEIGHT PIVOT HEAD

- Knurled knob smoothly, but firmly adjusts height (22-26")
- Outlet located in base



**COPPER (SPECIAL ORDER)
2791-6C**

250 W | 110-120 V | 2.1 amps | 60 Hz
NEMA 5-15P
14.6 lbs
8.0"W x 17.0"D x 22- 26.0"H
ETL. UL | 5.5 ft. cord
Daisy Chain 6 units on a 15-amp circuit



**ONYX (SPECIAL ORDER)
2791-6B**

250 W | 110-120 V | 2.1 amps | 60 Hz
NEMA 5-15P
14.6 lbs
8.0"W x 17.0"D x 22- 26.0"H
ETL. UL | 5.5 ft. cord
Daisy Chain 6 units on a 15-amp circuit



WARMING TRAYS

- Economical buffet solution
- Low profile pairs well with lamps
- Energy saving - only 1.91 amps*
- Plug up to 6 trays into one 15-amp circuit
- Surface temp range: 80-200°F / 27-93°C
- Tempered glass top is easy to clean



STEALTH WARMING TRAY
ST-1220-T
230 W | 110-120 V | 1.9 amps | 60 Hz
NEMA 5-15P | 11.4 lbs
23.8"W x 13.0"D x 2.0"H



STAINLESS STEEL WARMING TRAY
ST-1220
230 W | 110-120 V | 1.9 amps | 60 Hz
NEMA 5-15P | 11.4 lbs
24.2"W x 13.8"D x 1.9"H



LARGE STEALTH WARMING TRAY
ST-3915-T
450 W | 110-120 V | 3.8 amps | 60 Hz
NEMA 5-15P | 21.2 lbs
38.5"W x 13.8"D x 2.0"H



RISER FOR WARMING TRAYS
Stainless Steel Riser for ST-1220: **STS-1220**
Stainless Steel Riser for ST-1220-T: **STS-1220-SS**
Titanium Riser for ST-1220: **STS-1220-ST**
Titanium Riser for ST-1220-T: **STS-1220-T**



CARVING STATION WITH UNHEATED ONYX BOARD
2793-50

CARVING STATION WITH UNHEATED MOCHA BOARD
2793-5M
500 W | 110-120 V
4.2 amps | 60 Hz
NEMA 5-15P | 58.2 lbs
Lamp (8.0"W x 10.5"D base, 15.7"D (from back of base to farthest edge of shade) x 25.6" H (with shade parallel to base)+ board (24.5"W x 18.3"D x 2.9"H)
ETL. UL | 5.5 ft. cord

MOCHA BOARD UNHEATED
2793-5-220
500 W | 220-240 V | 2.1 amps | 50-60 Hz
CEE 7/7 Schuko Plug, (BS 1363 (13A) U.K. Plug also available)



Integra DUAL WARMING SYSTEM

- Overhead ceramic heating element with warming tray
- Power receptacle in back; Daisy chain 3 units on a 20-amp circuit
- LED lighted canopy highlights food
- Add an optional etched logo or design to canopy
- Ships assembled and ready to use
- 1-year warranty on parts & labor



INTEGRA DUAL WARMING SYSTEM
ISS-600
600 W | 120 V | 5 amps | 60 Hz
105-250°F / 41-121 °C
NEMA 5-20P
20.6 lbs.
26.8"W x 13.5"D x 18.75"H
ETL certified to UL 197 and CSA C22.2 #109
Daisy chain 3 units on a 20-amp circuit
5.5 ft. cord
NSF 4 certified and patented

Solstice COOLING & WARMING SYSTEM

ELECTRICAL HEATING ELEMENTS

- Temperatures range from 23-50°F and 120-185°F
- Goes from warm to cold in 45 minutes
- Only 1.91 amps
- Does not use water or freon
- Non-stick titanium coated body is fingerprint and scratch resistant
- Includes one full size 8-quart insert pan



**SOLSTICE
HC380-CT**
230 W | 110-120 V | 1.9 amps | 60 Hz
23-50°F/-5-10°C &
120-185°F/49-85°C
NEMA 5-15P
61.8 lbs
24.0"W x 18.9"D x 11.4"H
With open cover: 27.0"H
ETL. UL

HC383-CT
230 W | 220-240 V | 1.9 amps | 50-60 Hz
CEE-7/7 Schuko Plug, (BS 1363 (13A) U.K. Plug also available)

**SOLSTICE FULL SIZE INSERT
580-8/11**
20.9"W x 13.0"D x 2.6"H

**SOLSTICE DIVIDED INSERT
580-8/12**
20.9"W x 13.0"D x 2.6"H
Solstice non-stick coated inserts are made from die-cast aluminum for maximum temperature distribution

- Integrated safety thermostat prevents overheating
- One year warranty
- Choose self-regulating or adjustable controls options



**COFFEE URN & SOUP STATION
9503**
170 W | 110-120 V | 1.4 amps | 50-60 Hz
185°F/85°C
PVC cable
UL, CE
8 ft. cord w/NEMA 5-15P Plug
Holds coffee at perfect temperature without burning



**RECTANGLE OR FULL-SIZE
CHAFERS & SERVERS
9517**
450 W | 110-120 V
3.8 amps | 50-60 Hz
410°F/210°C
PVC cable
UL, CE
8 ft. cord w/NEMA 5-15P Plug

**ROUND CHAFER & SERVERS
9520**
240 W | 110-120 V
2.0 amps | 50-60 Hz
210°F/99°C
PVC cable
UL, CE
8 ft. cord w/NEMA 5-15P Plug

9509
600 W | 110-120 V | 5.0 amps | 50-60 Hz
410°F/210°C
PVC cable
UL, CE | 8 ft. cord w/NEMA 5-15P Plug

9508
600 W 220-240 V | 5.8 amps | 50-60 Hz
410°F/210°C
PVC cable
UL, CE
8 ft. cord | w/Schuko Plug

9524
500 W | 110-120 V
4.2 amps | 50-60 Hz
410°F/210°C
PVC cable
UL, CE
8 ft. cord and NEMA 5-15P Plug



9524/1
500 W | 110-120 V
4.2 amps | 50-60 Hz
410°F/210°C
PVC cable
UL, CE
8 ft. cord with energy regulator and NEMA 5-15P Plug



9506/1
700 W | 110-120 V
5.8 amps | 50-60 Hz
410°F/210°C
PVC cable
UL, CE | 8 ft. cord with energy regulator and NEMA 5-15P Plug

9505/1
800 W | 220-240 V | 3.3 amps | 50-60 Hz
240°F/99°C
PVC cable
UL, VDE | 8 ft. cord with energy regulator and Schuko Plug