

Specifications

SURFACE

Material: Solution-dyed polypropylene

Weight: 12 ounces per square yard

BACKING

Material: Releasable adhesive; moisture barrier is a polyester film

Overall Thickness: 3/32" inch (0.0938")

STANDARDS & TESTING

- Passes Flammability Standard CPSC-FFI-70
- Certified high-traction by the National Floor Safety Institute (NFSI)

Cleaning Instructions

Do not pick up your CleanShield Roll Goods to clean the floor underneath until you are ready to replace the mat.

CleanShield Roll Goods can be left in place during regular cleaning. Floor scrubbers, vacuums, brooms, and mops will pass right over without damaging the surface of the mat. Please use low settings for water and pressure. Tougher stains may be pre-treated with standard carpet cleaning products and agitated with a brush to loosen the soil.

Sure Stride mats are designed to dry quickly, however, standard fans or floor blowers can be used to speed the drying time. For extremely wet conditions, use a wet vac or extractor to remove water.

CleanShield Roll Goods are designed to last up to 4 months under normal use. Mats should be replaced if they show signs of wear, damage, or a weakened bond to the floor, and they should always be changed out within 4 months regardless of wear.

Installation Instructions

To Install CleanShield Roll Goods:

1. The floor must be clean and dry.
2. Measure to your desired length and place the cutting board beneath the mat at the location of the cut. Use the safety knife to cut the mat.
3. Position the mat in the desired location, then use the cutting board to press and smooth the mat into place.
4. Cut the corners at a 45 degree angle using the cutting guides on the cutting board.

Watch the Sure Stride Installation Video