

TD3T-N CLEANING INSTRUCTIONS




STEP 1

Once a week, fill the dispenser with a chlorine solution (75°F warm chlorine solution of 50-100 ppm).




STEP 2

Draw a small amount (2 oz.) of presoak through the faucet making contact with the faucet components. Allow the dispenser to soak over night.




STEP 3

The next morning, drain reservoir. Lift reservoir up, then tilt forward to clear faucet.



STEP 4

Turn the faucet wing nut in a clockwise direction and remove the faucet from the reservoir.



STEP 5

Clean reservoir in large sink with soft brush.




STEP 6

Unscrew the faucet bonnet from the faucet body and disassemble all faucet parts.



STEP 7

Transfer these parts to a three compartment sink for cleaning. Fill the first sink with a soap solution using a mild detergent, the second sink is used for clean rinse, and the third sink with a sanitizer solution (75°F warm chlorine solution of 50-100 ppm).



STEP 8

Use a brush to thoroughly scrub the faucet body.



STEP 9


Allow the parts to soak in a sanitizer solution for a minimum of ten minutes.



STEP 10

Remove the faucet parts from the sanitizer solution and rinse thoroughly. Allow parts to air dry over night. Reassemble faucet assembly prior to brewing into dispenser. Wash the entire outside surface of the dispenser with a clean damp cloth.

USE ONLY NON-ABRASHIVE CLEANERS



STEP 11

Once a month, replace the faucet seat cup. Discard the old seat cup.



STEP 12

The faucet assembly can be ordered for replacement.

DO NOT KEEP BREWED BEVERAGES OVERNIGHT