

## **CONVEYOR CONFIGURATOR**

This completed form is vital to help ensure you receive the conveyor you need and should mirror your purchase order. Your purchase order will only be processed when accompanied by this completed form. Please sign, date, and return to Jackson Customer Service at customer.service@jacksonwws.com or fax to 606.523.1799.

BASIC ELEMEN	TS OF CONFIC	GURATION	LEFT TO RIGHT DIRECTION OF OPERATION
Model	<b>44</b> "	<b>66</b> "	Dirty dishes are loaded into the left side of the machine side of the machine side of the side of the machine side of the mach
Sanitizing method	High temp	Low temp	
Direction of operation please refer to chart	Left to right	Right to left	
Voltage*	Phas		DIGUIT TO LEFT DIDECTION OF OPENATION
208, 230 or 460 ( <sup>1</sup>	*upcharge for 460)	single or three phase	RIGHT TO LEFT DIRECTION OF OPERATION
Connection(s)	☐ Single point	Dual point**  **upcharge for dual point connection	Clear dishes are unloaded from the left side of the machine.
OPTIONS & ACCESSORIES (these items carry an upcharge)			
Check all that apply			Ú Ú
☐ Booster heater	Booster heater type	e size 🔲 40 °F Rise 🔲 70	°F Rise
Side loader	Side loader type &	size  23" or 30" - hooded or unhooded	<del></del>
Blower dryer			
☐ Vent cowl collars			
Pressure regulato regulates the water pressure	<b>r</b> ure for optimal machine perfori	mance	
Water hammer arr			
Drain water temper tempers the water before	ering kit it goes down the drain - PVC p	pipe can melt!	
Flanged feet (set of	of 4)		
Scaltrol system prevents the buildup of sc.	ale		
_		VEYOR RETURNS MUST BE AI HARGES BOTH WAYS AND A	UTHORIZED IN WRITING BY JACKSOI 50% RESTOCKING FEE.