NOBLE

SAFETY DATA SHEET

Section 1: PRODUCT IDENTIFICATION

MANUFACTURER'S NAME:	ADDRESS:
Clark Core Services, LLC	2205 Old Philadelphia Pike, Lancaster, PA 17602
COMMON NAME:	**APPLICATION:**
Blue Vinyl Gloves, Powder-Free, Non-Sterile	Hand Protection Barrier

USAGE CONDITIONS:

This glove is to be worn on the hand of healthcare and similar personnel to prevent contamination between healthcare personnel and the patient's body, fluids, waste, and environments.

PRECAUTION TO BE TAKEN IN HANDLING AND STORAGE:

Components used in making these gloves may cause adverse allergy in some users and patients.
Immediately discontinue use if reactions are suspected.
Store in a dry, cool, and ventilated area. Do not store above 100˚F (37˚C). Keep away from heat. Shield open box from direct sunlight, fluorescent lighting, and x-ray. Improper storage will decrease usable life.

CHEMICAL COMPOSITION:

Polyvinyl Chloride (PVC)
Calcium-Zinc Stabilizer
Pigment – Blue
Bis (2-ethylhexyl) terephthalate (DOTP)
Poly Urethane

Section 2: PERFORMANCE REQUIREMENT

Sampling Plan: ISO 2859-1

Specification Standard: ASTM

CHARACTERISTIC	RELATED DEFECTS	INSPECTION LEVEL	ACCEPTABLE LEVELS
Freedom from holes	Holes	G-I	4.0
Major Visual Defect	Appearance	G-I	2.5
Minor Visual Defect	Appearance	G-I	4.0
Dimensions	Width, length, and thickness	S-2	4.0
Physical Requirements	Before aging, after accelerated aging	S-2	4.0
Powder Content	Exceeds Maximum Limit	N=5	<=2mg/piece
Gloves Counting	Gloves per Dispenser	S-2	In-House Standard

Section 3: DIMENSIONS AND TOLERANCES

DIMENSION	EXTRA-SMALL	SMALL	MEDIUM	LARGE	EXTRA-LARGE
LENGTH(mm)	230 (Min. and all for same)				
WIDTH(mm)	75+/-5	85+/-5	95+/-5	105+/-5	115+/-5
WEIGHT(gram)	N/A	3.5+/-0.3	4.0+/-0.3	4.5+/-0.3	5.0+/-0.3
THICKNESS FOR ALL SIZES (mm) SING LAYER					
Fingertip	0.05+/-0.02	Palm	0.05+/-0.02	Cuff	0.04+/-0.02

TENSILE PROPERTIES	UNAGED	AGED
Tensile Strength (MPA)	13	13
Ultimate Elongation (%)	350	300