

MATERIAL SAFETY DATA SHEET**1. Chemical Product and Company Identification**

Product Name: Nickel Metal Hydride Battery

Manufacturer: DONGGUAN TIANQIU ENTERPRISE CO., LTD.

Address: TianQiu Industrial Park, Xinji Industrial Zone, Machong Town, Dongguan, GuangDong, P.R.China

Telephone: 0769-81210202

**2. Composition/Information on Ingredients**

Hazardous Components	Approx wt%	CAS #	EC #
Nickel II Hydroxide (Ni(OH) ₂)	23-27	12054-48-7	235-008-5
Metal Hydride (MH)	25-35	-----	-----
Potassium Hydroxide (KOH)	1.8-2.5	1310-58-3	215-181-3
Cobalt (Co)	0.4-1.0	7440-48-4	231-158-0
Mercury (Hg)	< 0.0005	7439-97-6	231-106-7
Cadmium (Cd)	< 0.002	7440-43-9	231-152-8
Lead (Pb)	< 0.004	7439-92-1	231-100-4

3. Hazards Identification

Routes of Entry: Not applicable under normal conditions

Health Hazards: In case of leakage, will be cause itchy and/or chemical burns when direct contact with electrolyte

Hazards to Environment: Not applicable

Fire and Explosion Hazards: Not applicable

4. First-aid Measures

Skin Contact: If exposed to a leaking battery, remove contaminated clothing. Wash exposed areas with plenty of water and soap. If irritation occurs, consult a physician.

Eyes Contact: If a battery is leakage and materials contact eyes, flush immediately with running water for at least 15 minutes. Consult an ophthalmologist at once.

Inhalation: If vapor from vented or leaked batteries are inhalation, move to fresh air and get medical attention.

Ingestion: Get immediately medical attention, do not induce vomiting or give a liquid to unconscious person.

5. Fire Fighting Measures

Hazard Characteristic: Not available

Hazards Exposed to Combustion Products: In case of fire, carbon dioxide, carbon monoxide and other toxic organic substances will be generated. Do not inhale fumes and smoke.

Extinguishing Media: In case of fire, use a smothering agent such as dry sand, dry ground dolomite or soda ash. If you use water, use enough to smother the fire. Using an insufficient amount of water could possibly make the fire worse. Cooling the exterior of the batteries will help prevent rupturing.

Special Fire Fighting Procedures: Fire fighters should wear self-contained breathing apparatus.

6. Accidental Release Measures

Precautions: Avoid direct contact with the leaking or ruptured batteries. Avoid short circuit.

Methods for Clean Up: Care for well-ventilated conditions. Recycle or dispose of the materials in an appropriate way.

7. Handling and Storage

Precaution: Handling and transfer the products carefully, make sure the packing always in good condition. Damaged packing may cause batteries contact together, in this case batteries may short circuit or improperly connected, it cause batteries venting, leaking or exploding.

Storage: Store in a dry, cool and well-ventilated area.

8. Exposure Control/Personal Protection

Exposition/Technical Measures: Atmospheric vapor concentrations must be minimized by adequate ventilation.

Protection of Hands, Eyes, and Skin: No required under normal use conditions. When handling leaking batteries, use gloves and wear safety glasses to protect hands, eyes and skin.

General Safety and Hygiene Measures: Use only as directed.

9. Physical and Chemical Properties

Physical State and Appearance: Cylindrical

Odor: Odorless

pH: N/A

Melting Point (°C): N/A

Specific Gravity (H₂O=1): N/A

Boiling Point (°C): N/A

Vapor Density (Air=1): N/A

Vapor Pressure (kPa): N/A

Heat of Combustion (kJ/mol): N/A

Critical Temperature (°C): N/A

Critical Pressure (MPa): N/A

Partition Coefficient: N/A

Flash Point (°C): N/A

Ignition Temperature (°C): N/A

Explosion Limit % (V/V): N/A

Solubility in Water: N/A

Solubility in Other Solvents: N/A

10. Stability and Reactivity

Stability: Stable

Incompatibility: None

Condition to Avoid: Avoid shorting, mechanical & thermal abuse

Hazardous Polymerization: Will not occur

Hazardous Decomposition: None

11. Toxicological Information

Note: Since the materials in this battery are sealed in the can, the potential for exposure to the components of the battery is negligible, when the battery is used as directed. However technical or electrical abuse of the battery may result in the release of battery contents.

Toxicity to Animals: Not applicable

Chronic Effects on Human: Not applicable

12. Ecological Information

This product has not been tested for environmental effects.

13. Disposal Consideration

Dispose in accordance with Federal, States and local regulations

14. Transport Information

In general, all batteries in all forms of transportation (ground, air, or ocean) must be packaged in a safe and responsible manner. Regulatory concerns from all agencies for safe packaging require that batteries be packaged in a manner that prevents short circuits and be contained in "strong outer packaging" that prevents spillage of contents. All original packaging for Energizer nickel metal hydride batteries has been designed to be compliant with these regulatory concerns.

TIANQIU nickel metal hydride batteries (sometimes referred to as "Dry cell" batteries) are not defined as dangerous goods under the IATA Dangerous Goods Regulations **62nd2021**. ICAO Technical Instructions and the U.S. hazardous materials regulations (49 CFR). Nickel metal hydride batteries are defined as dangerous goods under the IMDG code. For air and ground transportation, these batteries are not subject to the dangerous goods regulations as they are compliant with the requirements contained in the following special provisions.

Regulatory Body	Special Provisions
ADR	295 - 304, 598
IMDG	UN3496 SP 963
UN	UN 3028 Provisions 295 - 304
US DOT	49 CFR 172.102 Provision 130
IATA	A123

ICAO	UN 3028 Provisions 295 - 304
------	------------------------------

In addition, the IATA Dangerous Goods Regulations and ICAO Technical Instructions require the words “not restricted” and the Special Provision number A123 be provided on the air waybill, when an air waybill is issued.

15. Regulatory Information

Special requirement be according to the local regulators.

16. Other information

Do not heat or dispose of in fire. Do not recharge or disassemble the battery.

Notice to reader:

The information contained in this MSDS was obtained from current and reliable sources, however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of TianQiu, TianQiu will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this MSDS shall be created or inferred by any statement in this MSDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this MSDS. The user is responsible for full compliance.