

Motion Technology	SAFETY DATA SHEET	Date Issued	12 September 2017
		Document Nbr	
		Revision	1
		Date Revised	12 September 2017
CGR-L			

Prepared to U.S. OSHA, CMA, ANSI, Canadian WHMIS Standards

SECTION 1 - IDENTIFICATION

1.1 TRADE NAME:	CGR-L
SYNONYMS:	None
CAS#:	Mixture
1.2 PRODUCT USE:	Oven and grill cleaner
1.3 SUPPLIER/MANUFACTURER'S NAME:	Motion Technology
ADDRESS:	10 Forbes Rd. Northborough MA 01532
BUSINESS PHONE:	(508) 460-9800
EMAIL:	
WEB SITE INFORMATION:	
1.4 EMERGENCY PHONE NUMBERS:	1 (800) 424-9300 (CHEMTREC U.S. - 24 HRS.)

SECTION 2 - HAZARD IDENTIFICATION

EMERGENCY OVERVIEW:

Product Description: This product is a clear, amber, foamy liquid with a mild odor.

Health Hazards: Exposure to this product can cause serious eye damage and skin irritation. Inhalation of mist can cause severe irritation to mucous membranes and respiratory tract.

Flammability Hazards: This product has a flash point greater than 200°F (93.3°C). Non flammable.

Reactivity Hazards: This product is not reactive.

Environmental Hazards: The environmental effects of this product have not been fully investigated.

Emergency Considerations: Emergency responders must wear the proper personal protective equipment (and have appropriate fire-suppression equipment) suitable for the situation to which they are responding.

US DOT SYMBOLS

CANADA (WHMIS) SYMBOLS

GHS Hazard Symbols



Complies with WHMIS 2015



Signal Word:
DANGER!

2.1 GHS LABELING AND HAZARD CLASSIFICATION:

This product does meet the definition of a hazardous substance or preparation as defined by the OSHA and described in 29 CFR 1910.1200(d).

Component(s) Contributing to Classification(s):

All Ingredients

2.2 LABEL ELEMENTS

GHS Hazard Classification(s):

- Acute Toxicity - Oral Category 4
- Acute Toxicity - Dermal Category 4
- Eye Damage/Irritation Category 1
- Skin Corrosion/Irritant Category 2

Hazard Statement(s):

May be harmful if swallowed
 Harmful in contact with skin
 Causes serious eye damage
 Causes skin irritation

Precautionary Statement(s):

Avoid exposure.
 Use only with adequate ventilation.
 Wash thoroughly after handling.
 In case of an accident or if you feel unwell – seek medical advice and show label.

Response Statement(s):

IF SWALLOWED: Call a Poison Control Center/Doctor.
IF SWALLOWED: Rinse mouth. Do **NOT** induce vomiting.
IF ON SKIN: Wash with plenty of water.
 If skin irritation or rash occurs: Get medical advice/attention.
 Take off contaminated clothing and wash it before reuse.
 Call a Poison Center/Doctor if you feel unwell.
IF INHALED: Inhalation of vapors or mist may cause respiratory irritation. May cause dizziness, nausea and/or breathing difficulties.
IF IN EYES: Direct eye contact can cause serious irritation with redness, tearing and blurred vision. Possible eye damage.

Storage Statement(s):

Store in a well-ventilated place. Keep cool.
 Store locked up.

Disposal Statement(s):

Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 HEALTH HAZARDS OR RISKS FROM EXPOSURE:

SYMPTOMS OF OVEREXPOSURE BY ROUTE OF EXPOSURE: The most significant routes of overexposure for this product are by contact with skin or eyes, and inhalation of mists or spray. The symptoms of overexposure are described in the following paragraphs.

ACUTE:

INHALATION: Inhalation of mist from this product causes severe irritation to mucous membranes and respiratory tract.
SKIN CONTACT: Exposure to this product can cause skin irritation. Prolonged exposure can cause severe irritation.
EYE CONTACT: Contact with eyes can cause serious irritation with redness, tearing, and pain. Possible corneal damage.
INGESTION: Ingestion may cause severe burns to the mucous membranes of the digestive tract.

CHRONIC: The effects of long term, low level exposures to this product have not been determined.

TARGET ORGANS: **ACUTE:** Eye, Respiratory System, Skin **CHRONIC:** No data available for this product.

SECTION 3 - COMPOSITION and INFORMATION ON INGREDIENTS

COMPOSITION	WT. PERCENTAGE	CAS #	HAZARD CLASSIFICATION
Water	70-80%	7732-18-5	Not Classified
Potassium Hydroxide	5-15%	1310-58-3	Corrosive to metals – Cat 1, Acute toxicity, Oral - Cat 4, Eye damage/irritation - Cat 1, Skin corrosion/irritation – Cat 1A, Acute aquatic toxicity - Cat 3
Diethylene Glycol Butyl Ether	1-10%	112-34-5	Eye Damage/Irritation Cat 2A
Ethylene Glycol	1-5%	107-21-1	Acute Toxicity - Oral Cat 4, STOT-RE (Oral) Cat 2
Alkyl Glucoside	<1%	68515-73-1	Eye damage/Irritation Cat 1
Balance of other ingredients are less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers)			

NOTE: ALL WHMIS required information is included in appropriate sections based on the ANSI Z400.1-2010 format.

SECTION 4 - FIRST-AID MEASURES**4.1 DESCRIPTION OF FIRST AID MEASURES:**

EYE CONTACT: If product enters the eyes, open eyes while under gentle running water for at least 15 minutes. Seek medical attention if irritation persists.

SKIN CONTACT: Wash skin thoroughly after handling. Seek medical attention if irritation develops and persists. Remove contaminated clothing. Launder before re-use.

INHALATION: If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention if breathing difficulty continues.

INGESTION: If product is swallowed, call physician or poison control center for most current information. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and SDS with the victim to the health professional.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None known.

4.2 SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

Contact with eyes may cause severe irritation with redness and tearing with possible tissue damage. Prolonged skin exposure may cause moderate to severe skin irritation.

4.3 RECOMMENDATIONS TO PHYSICIANS:

Treat symptoms and eliminate overexposure.

SECTION 5 - FIRE-FIGHTING MEASURES

5.1 FIRE EXTINGUISHING MATERIALS:

Use fire extinguishing methods below:

- Water Spray: Yes
- Foam: Yes
- Halon: Yes

- Carbon Dioxide: Yes
- Dry Chemical: Yes
- Other: Any "C" Class

5.2 UNUSUAL FIRE AND EXPLOSION HAZARDS:

None known

Explosion Sensitivity to Mechanical Impact: No

Explosion Sensitivity to Static Discharge: No

FLASH POINT: >200°F (>93°C)


AUTOIGNITION TEMPERATURE: Not applicable.

FLAMMABLE LIMITS (in air by volume, %): Lower: NA, Upper: NA

5.3 SPECIAL FIRE-FIGHTING PROCEDURES:

Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

NFPA RATING SYSTEM



HMIS RATING SYSTEM

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM			
HEALTH HAZARD (BLUE)		2	
FLAMMABILITY HAZARD (RED)		1	
PHYSICAL HAZARD (YELLOW)		0	
PROTECTIVE EQUIPMENT			
EYES	RESPIRATORY	HANDS	BODY
	See Sect 8		See Sect 8
For Routine Industrial Use and Handling Applications			

Hazard Scale: 0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe, *=Chronic Hazard

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES:

See Section 8.2 for Exposure Controls.

6.2 ENVIRONMENTAL PRECAUTIONS:

Keep spilled material out of all sewers and open bodies of water.

6.3 SPILL AND LEAK RESPONSE:

Contain spill if safe to do so. Cover or absorb spilled liquid with sand, earth, or other inert material. Clean up spill immediately and place in appropriate containers. Keep spill out of sewers and open bodies of water.

Dispose of in accordance with applicable Federal, State, and local procedures (see Section 13 Disposal Considerations).

SECTION 7 – HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING:

As with all chemicals, avoid getting this product **ON YOU** or **IN YOU**. Wash thoroughly after handling this product. Do not eat, drink, smoke, or apply cosmetics while handling this product. Avoid breathing vapors/mists generated by this product. Use in a well-ventilated location. Remove contaminated clothing immediately.

7.2 STORAGE AND HANDLING PRACTICES:

Containers of this product must be properly labeled. Store containers in a cool, dry location. Keep container tightly closed when not in use. Keep away from acids and reactive materials.

7.3 SPECIFIC USES:

Developed specifically for oven and grill cleaning.

SECTION 8 – EXPOSURE CONTROLS – PERSONAL PROTECTION

8.1 EXPOSURE PARAMETERS:

CHEMICAL NAME	CAS#	ACGIH TLV	OSHA TWA
Water	7732-18-5	Not Listed	Not Listed
Potassium Hydroxide	1310-58-3	2mg/m3	Not Listed
Diethylene Glycol Butyl Ether	112-34-5	10ppm	Not Listed
Ethylene Glycol	107-21-1	100mg/m3	100mg/m3
Alkyl Glucoside	68515-73-1	Not Listed	Not Listed

8.2 EXPOSURE CONTROLS:

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada.

RESPIRATORY PROTECTION: Not required when using this product. Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93.

EYE PROTECTION: Safety glasses or goggles are recommended. If necessary, refer to U.S. OSHA 29 CFR 1910.133 or appropriate Standards of Canada.

HAND PROTECTION: Chemical resistant gloves are recommended to prevent skin contact. If necessary, refer to U.S. OSHA 29 CFR 1910.138 or appropriate Standard of Canada.

BODY PROTECTION: Use body protection appropriate to prevent skin contact (e.g. lab coat, overalls).

If necessary, refer to U.S. OSHA 29 CFR 1910.132 (also OSHA Technical Manual), or appropriate Standard of Canada.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE (PHYSICAL STATE) AND COLOR: Clear, amber, foamy liquid

ODOR: Mild

ODOR THRESHOLD: Not available.

PH: 13 -14

MELTING/FREEZING POINT: Approx. 32°F (0°C)

BOILING POINT: Approx. 200°F (93.3°C)

FLASH POINT: >200°F (>93.3°C)

EVAPORATION RATE (n-BuAc=1): Not available.

FLAMMABILITY (SOLID, GAS): Not applicable.

UPPER/LOWER FLAMMABILITY OR EXPLOSION LIMITS: Not available.

VOC: 0

VAPOR PRESSURE (mm Hg @ 68°F (20°C)): Not available.

VAPOR DENSITY: Not available.

RELATIVE DENSITY: Not available.

SPECIFIC GRAVITY: 1.07 @ 25°C

SOLUBILITY IN WATER: Complete soluble.

WEIGHT PER GALLON: 8.9 Lb/gal @ 25°C

PARTITION COEFFICIENT (n-octanol/water): Not applicable.

AUTO-IGNITION TEMPERATURE: Not applicable.

DECOMPOSITION TEMPERATURE: Not available.

VISCOSITY: Not available

9.2 OTHER INFORMATION:

No additional information available.

SECTION 10 – STABILITY AND REACTIVITY

10.1 REACTIVITY:

Not reactive.

10.2 STABILITY:

Stable under conditions of normal storage and use.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS:

Will not occur

10.4 CONDITIONS TO AVOID:

Incompatible materials.

10.5 MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE:

Aluminum

10.6 HAZARDOUS DECOMPOSITIONS PRODUCTS:

None known.

SECTION 11 – TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:

Toxicity data is not available for this mixture. See below for individual ingredient acute toxicity data.

Potassium Hydroxide (CAS #1310-58-3)

LD50 (Oral, rat) - 284 mg/kg

Diethylene Glycol Butyl Ether (CAS #112-34-5)

LD50 (Oral, rat) - 7,292 mg/kg

LD50 (Oral, mouse) - 2,406 mg/kg

LD50 (Dermal, rabbit) - 2,764 mg/kg

Ethylene Glycol (CAS #107-21-1)

Lethal Dose (Oral, human-adult) – 3 oz

LD50 (Oral, rat) – 6,000 – 13,000 mg/kg

LD50 (Dermal, rabbit) - >22,270 mg/kg

LC50 (7 hr) (Inhalation, aerosol, rat) - >3.95 mg/L

Alkyl Glucoside (CAS #68515-73-1)

LD50 (Oral, rat) - >5,000 mg/kg

LD50 (Dermal) - >5,000 mg/kg

SUSPECTED CANCER AGENT: The following ingredients are not found on one or more of the following lists: **FEDERAL OSHA Z LIST, NTP, CAL/OSHA, IARC** and therefore are not considered to be, or suspected to be, a cancer-causing agent by these agencies.

None.

IRRITANCY OF THE PRODUCT: Contact with this product can be irritating to exposed skin and eyes.

SENSITIZATION TO THE PRODUCT: This product is not considered a skin and respiratory sensitizer.

REPRODUCTIVE TOXICITY INFORMATION: This product does contain an ingredient that may cause reproductive and fetal effects.

SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE: Not classified as a specific target organ toxicity – single exposure.

SPECIFIC TARGET ORGAN TOXICITY – REPEATED EXPOSURE: Not classified as a specific target organ toxicity – repeated exposure.

CHRONIC EFFECTS: The effects of long term, low level exposures to this product have not been determined.

SECTION 12 – ECOLOGICAL INFORMATION

12.1 TOXICITY:

No toxicity data available for this mixture. See below for individual ingredient ecotoxicity data.

Potassium Hydroxide (CAS #1310-58-3)

LC50/96h (Mosquito fish) - 80 mg/L

LC50/96h (Flathead minnow) - 176 mg/L

EC50/48h (Daphnia magna) – 60 mg/L

EC50/96h (Selenastrum capricornutum) – 61 mg/L

Diethylene Glycol Butyl Ether (CAS #112-34-5)

LC50/96h (Bluegill sunfish) – 1,300 mg/L

LC50/24h (Goldfish) – 46,300 - 51,100 mg/L

Ethylene Glycol (CAS #107-21-1)

LC50/96h (Rainbow trout) – 2,700 mg/L

LC50/48h (Daphnia magna) – 46,300 - 51,100 mg/L

EC50/96h (Selenastrum capricornutum) – 9,500 – 13,000 mg/L

Alkyl Glucoside (CAS #68515-73-1)

LC50/96h (Brachydanio rerio) - >100 mg/L

LC50/48h (Daphnia magna) - >100 mg/L

EC50/72h (Desmodesmus subspicatus) - >10 - <100 mg/L (growth rate)

12.2 PERSISTENCE AND DEGRADABILITY:

No specific data available for this mixture.

12.3 BIOACCUMULATIVE POTENTIAL:

No specific data available for this mixture.

12.4 MOBILITY IN SOIL:

No specific data available for this mixture.

12.5 OTHER ADVERSE EFFECTS:

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

SECTION 13 – DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS:

This product, if disposed of as shipped, is considered a hazardous waste as specified in 40 CFR 261.

Waste disposal must be in accordance with appropriate U.S. Federal, State, and local regulations, and those of Canada.

SECTION 14 – TRANSPORTATION INFORMATION

14.1 U.S. DEPARTMENT OF TRANSPORTATION (DOT) SHIPPING REGULATIONS:

This product is defined as hazardous (per 49 CFR 172.101) by the U.S. Department of Transportation. NOTE: Limited quantities of corrosive material (Class 8) in Packing Group III are exempted from labeling requirements, unless the material is offered for transportation or transported by aircraft, and are exempted from the specification packaging requirements of this subchapter when packaged in combination packagings according to this paragraph. For transportation by aircraft, the package must also conform to the applicable requirements of sec. 173.27 of this part. A limited quantity package that conforms to the provisions of this section is not subject to the shipping paper requirements of subpart C of part 172 of this subchapter, unless the material meets the definition of a hazardous substance, hazardous waste, marine pollutant, or is offered for transportation and transported by aircraft or vessel, and is eligible for the exceptions provided in sec. 173.156 of this part. In addition, shipments of limited

quantities are not subject to subpart F (Placarding) of part 172 of this subchapter. Each package must conform to the packaging requirements of subpart B of this part and may not exceed 30 kg (66 lb) gross weight.

14.2 UN IDENTIFICATION NUMBER:	UN 1760
14.3 PROPER SHIPPING NAME:	Corrosive liquids, n.o.s. (Contains Potassium Hydroxide)
14.4 HAZARD CLASS NUMBER AND DESCRIPTION:	Corrosive, Class 8
14.5 PACKING GROUP:	PG III
DOT LABELS REQUIRED:	Corrosive
NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER:	154
14.6 ENVIRONMENTAL HAZARDS (RQ QUANTITY):	Not applicable.
MARINE POLLUTANT: The components of this product are not designated by the Department of Transportation to be Marine Pollutants (49 CFR 172.101, Appendix B).	
14.7 SPECIAL PRECAUTION FOR USER:	
Use caution and avoid exposure.	
14.8 INTERNATIONAL TRANSPORTATION:	
INTERNATIONAL AIR TRANSPORT ASSOCIATION SHIPPING INFORMATION (IATA): This product is classified as dangerous goods.	
Note: Packaging does not comply with IATA regulations and cannot be shipped by aircraft.	
INTERNATIONAL MARITIME ORGANIZATION SHIPPING INFORMATION (IMO): This product is classified as dangerous goods.	

SECTION 15 – REGULATORY INFORMATION

15.1 SAFETY, HEALTH, AND ENVIRONMENTAL REGULATIONS SPECIFIC FOR THE SUBSTANCE OR MIXTURE:

See below

15.2 UNITED STATES REGULATIONS:

SARA REPORTING REQUIREMENTS: This product is subject to the reporting requirements of Sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act., as follows:

SARA 313 Reporting: Diethylene Glycol Butyl Ether (CAS #112-34-5)(As Glycol Ethers); Ethylene Glycol (CAS #107-21-1).

TSCA: All components in this product are listed on the US Toxic Substances Control Act (TSCA) inventory of chemicals.

SARA 311/312:

ACUTE HEALTH: YES **CHRONIC HEALTH:** NO **FIRE:** NO **REACTIVITY:** NO

U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for this product. The default Federal SDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) may apply, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ): Potassium Hydroxide - CAS# 1310-58-3 - RQ 1,000 Lb, Ethylene Glycol – CAS #107-21-1 – RQ 5000 lb.

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): This product does contain ingredients that are on the California Proposition 65 lists. Ethylene Glycol - CAS#107-21-1

15.3 CANADIAN REGULATIONS:

CANADIAN DSL/NDSL INVENTORY STATUS: All components are DSL listed, NDSL listed, and/or are exempt from listing.

OTHER CANADIAN REGULATIONS: Not applicable.

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LIST: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by those regulations.

CANADIAN WHMIS CLASSIFICATION AND SYMBOLS: This product is categorized as a Controlled Product, not classified as per the Controlled Product Regulations.

SECTION 16 – OTHER INFORMATION

16.1 ABBREVIATIONS AND ACRONYMS:

EPA: United State Environmental Protection Agency

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)