



SAFETY DATA SHEET

1. Product and Company Identification

Product identifier	Aerosol Nu-Brite (4291-18)
Other means of identification	Not available
Recommended use	Cleaner
Recommended restrictions	None known.
Manufacturer information	Nu-Calgon 2611 Schuetz Road St. Louis, MO 63043 US Phone: 314-469-7000 / 800-554-5499 Emergency Phone: 1-800-424-9300 (CHEMTREC)
Supplier	See above.

2. Hazards Identification

Physical hazards	Gases under pressure	Liquefied gas
	Corrosive to metals	Category 1
Health hazards	Skin corrosion/irritation	Category 1A
	Serious eye damage/eye irritation	Category 1
Environmental hazards	Not classified.	
WHMIS 2015 defined hazards	Not classified	
Label elements		



Signal word Danger

Hazard statement
Contains gas under pressure; may explode if heated.
May be corrosive to metals.
Causes severe skin burns and eye damage.

Precautionary statement

Prevention Keep only in original packaging. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe mist or vapor.

Response Absorb spillage to prevent material-damage.
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. Specific treatment (see information on this label). IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage Store locked up. Protect from sunlight. Store in a well-ventilated place. Store in a corrosion resistant container with a resistant inner liner.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC) None known

WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC) None known

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information Not applicable.

3. Composition/Information on Ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	1-5*

Chemical name	Common name and synonyms	CAS number	%
Monoethanolamine		141-43-5	1-5*
Propane		74-98-6	1-5*
Sodium hydroxide		1310-73-2	5-10*

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.
*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First Aid Measures

Inhalation	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
Skin contact	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
Ingestion	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.
Most important symptoms/effects, acute and delayed	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Avoid contact with eyes and skin. Wear rubber gloves and chemical splash goggles. Keep out of reach of children. Do not store at temperatures above 49°C. Do not puncture or incinerate container.

5. Fire Fighting Measures

Suitable extinguishing media	Dry chemical. Carbon dioxide. Fog.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Pressurized container may explode when exposed to heat or flame.
Hazardous combustion products	May include and are not limited to: Oxides of nitrogen. Oxides of carbon.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Dike far ahead of spill for later disposal. Absorb spillage to prevent material damage. Scoop up used absorbent into drums or other appropriate container. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and Storage

Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid contact with eyes, skin and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Keep away from heat, sparks and open flame. Avoid exposure to long periods of sunlight. Store in a corrosion resistant container with a resistant inner liner. Store away from incompatible materials (see Section 10 of the SDS). Keep out of the reach of children.

8. Exposure Controls/Personal Protection

Occupational exposure limits

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value
Butane (CAS 106-97-8)	TWA	1000 ppm
Monoethanolamine (CAS 141-43-5)	STEL	15 mg/m3
		6 ppm
	TWA	7.5 mg/m3
		3 ppm
Propane (CAS 74-98-6)	TWA	1000 ppm
Sodium hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
Butane (CAS 106-97-8)	STEL	750 ppm
	TWA	600 ppm
Monoethanolamine (CAS 141-43-5)	STEL	6 ppm
	TWA	3 ppm
Propane (CAS 74-98-6)	TWA	1000 ppm
Sodium hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
Butane (CAS 106-97-8)	STEL	1000 ppm
Monoethanolamine (CAS 141-43-5)	STEL	6 ppm
	TWA	3 ppm
Sodium hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
Butane (CAS 106-97-8)	TWA	800 ppm
Monoethanolamine (CAS 141-43-5)	STEL	6 ppm
	TWA	3 ppm
Propane (CAS 74-98-6)	TWA	1000 ppm
Sodium hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm
Monoethanolamine (CAS 141-43-5)	STEL	15 mg/m3 6 ppm
	TWA	7.5 mg/m3 3 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm
Sodium hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Type	Value
Sodium hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Monoethanolamine (CAS 141-43-5)	PEL	6 mg/m3 3 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm
Sodium hydroxide (CAS 1310-73-2)	PEL	2 mg/m3

US. ACGIH Threshold Limit Values

Components	Type	Value
Butane (CAS 106-97-8)	STEL	1000 ppm
Monoethanolamine (CAS 141-43-5)	STEL	6 ppm
	TWA	3 ppm
Sodium hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm
Monoethanolamine (CAS 141-43-5)	STEL	15 mg/m3 6 ppm
	TWA	8 mg/m3 3 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm
Sodium hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear safety glasses with side shields (or goggles).

Skin protection**Hand protection**

Impervious gloves. Confirm with reputable supplier first.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).
Thermal hazards	Not applicable.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and Chemical Properties

Appearance	Compressed liquefied gas.
Physical state	Gas.
Form	Aerosol. Spray
Color	Clear Green
Odor	Caustic
Odor threshold	Not available.
pH	13.0 ± 0.5
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Pour point	Not available.
Specific gravity	Not available
Partition coefficient (n-octanol/water)	Not available.
Flash point	Not available
Evaporation rate	< 1 (Ether = 1)
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available
Flammability limit - upper (%)	Not available
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	481 kPa
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	Not available.
Auto-ignition temperature	Not available
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Heat of combustion	3.23 kJ/g

10. Stability and Reactivity

Reactivity	Strong acids.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Chemical stability	Material is stable under normal conditions.
Conditions to avoid	Do not mix with other chemicals.
Incompatible materials	Strong oxidizing agents. Acids. Reducing agents. Soft metals.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon. Oxides of nitrogen.

11. Toxicological Information

Routes of exposure	Inhalation. Ingestion. Skin contact. Eye contact.
---------------------------	---

Information on likely routes of exposure

Ingestion	Causes digestive tract burns.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	Causes severe skin burns.
Eye contact	Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics Burning pain and severe corrosive skin damage. Causes serious eye damage. Permanent eye damage including blindness could result. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects**Acute toxicity**

Components	Species	Test Results
Butane (CAS 106-97-8)		
Acute		
<i>Dermal</i>		
LD50	Not available	
<i>Inhalation</i>		
LC50	Mouse	539600 ppm, 120 Minutes, ECHA 520400 ppm, 120 Minutes, ECHA 1237 mg/L, 120 Minutes 680 mg/L, 2 Hours, HSDB 57 %, 120 Minutes, ECHA 52 %, 120 Minutes
	Rat	> 800000 ppm, 10 Minutes, ECHA 1442738 mg/m3, 10 Minutes, ECHA 1354944 mg/m3, 10 Minutes, ECHA 570000 ppm, 10 Minutes, ECHA 276000 ppm, 4 Hours, CCOHS 1443 mg/L, 10 Minutes, ECHA 1355 mg/L, 10 Minutes
<i>Oral</i>		
LD50	Not available	
Monoethanolamine (CAS 141-43-5)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	2881 mg/kg, 24 Hours, ECHA 2504 mg/kg, 24 Hours 1018 mg/kg, HMIRA 1000 mg/kg, CCOHS 2.5 - 2.8 ml/kg, 24 Hours
<i>Inhalation</i>		
LC50	Mouse	1210 mg/m3, 4 Hours, CCOHS 484 ppm, 4 Hours, CCOHS 1.2 mg/L, 4 Hours, CCOHS
	Rat	> 1.3 mg/L, 6 Hours, ECHA
<i>Oral</i>		
LD50	Guinea pig	620 mg/kg, HSDB, CCOHS
	Mouse	1475 mg/kg, CCOHS 700 mg/kg, SAX, CCOHS
	Rat	1970 mg/kg, CCOHS 1720 mg/kg, CCOHS, SIGMA 1515 mg/kg, ECHA

Components	Species	Test Results
		1089 mg/kg, ECHA
		1.2 ml/kg, ECHA
		1.1 ml/kg, ECHA
Propane (CAS 74-98-6)		
Acute		
<i>Dermal</i>		
LD50	Not available	
<i>Inhalation</i>		
LC50	Mouse	539600 ppm, 120 Minutes, ECHA
		520400 ppm, 120 Minutes, ECHA
		1237 mg/L, 120 Minutes
		57 %, 120 Minutes, ECHA
		52 %, 120 Minutes
	Rat	> 12000000 ppm, 4 hours
		> 800000 ppm, 10 Minutes, ECHA
		> 1464 mg/L, 15 Minutes, HSDB
		1442738 mg/m3, 10 Minutes, ECHA
		1354944 mg/m3, 10 Minutes, ECHA
		570000 ppm, 10 Minutes, ECHA
		1355 mg/L, 10 Minutes
<i>Oral</i>		
LD50	Not available	
Sodium hydroxide (CAS 1310-73-2)		
Acute		
<i>Dermal</i>		
LD50	Not available	
<i>Inhalation</i>		
LC50	Not available	
<i>Oral</i>		
LD50	Rabbit	325 mg/kg, ECHA
Skin corrosion/irritation	Causes severe skin burns and eye damage.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Causes serious eye damage.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitization		
Canada - Alberta OELs: Irritant		
Monoethanolamine (CAS 141-43-5)	Irritant	
Sodium hydroxide (CAS 1310-73-2)	Irritant	
Respiratory sensitization	Not available.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, NTP, or OSHA.	

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Teratogenicity	Not available.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not likely, due to the form of the product.
Chronic effects	Prolonged inhalation may be harmful. May be harmful if absorbed through skin.

12. Ecological Information

Ecotoxicity	See below		
Ecotoxicological data			
Components		Species	Test Results
Monoethanolamine (CAS 141-43-5)			
Algae	IC50	Algae	15 mg/L, 72 Hours
Crustacea	EC50	Daphnia	65 mg/L, 48 Hours
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	114 - 196 mg/L, 96 hours
Sodium hydroxide (CAS 1310-73-2)			
Aquatic			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	34.59 - 47.13 mg/L, 48 hours
Fish	LC50	Western mosquitofish (Gambusia affinis)	125 mg/L, 96 hours
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential	No data available.		
Mobility in soil	No data available.		
Mobility in general	Not available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

13. Disposal Considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	D002: Waste Corrosive material [pH <=2 or >=12.5, or corrosive to steel] The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport Information

Transport of Dangerous Goods (TDG) Proof of Classification	Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.
General	IATA: Limited Quantity, Forbidden
U.S. Department of Transportation (DOT)	
Basic shipping requirements:	
Proper shipping name	LTD QTY
Hazard class	Limited Quantity - US

Transportation of Dangerous Goods (TDG - Canada)

Basic shipping requirements:

UN number	UN1950
Proper shipping name	AEROSOLS, non-flammable, containing substances in Class 8, packing group II
Hazard class	Limited Quantity - Canada
Special provisions	80
Packaging exceptions	<1L - Limited Quantity

IATA/ICAO (Air)

Basic shipping requirements:

UN number	UN1950
Proper shipping name	Aerosols, non-flammable, containing substances in Class 8, Packing Group II
Hazard class	2.2
Subsidiary class	8
ERG code	2C

IMDG (Marine Transport)

Basic shipping requirements:

UN number	UN1950
Proper shipping name	AEROSOLS
Hazard class	Limited Quantity - IMDG
	<1000 mL - Limited Quantity

DOT; IMDG; TDG



IATA



15. Regulatory Information

Canadian federal regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada DSL Challenge Substances: Listed substance

Butane (CAS 106-97-8) Listed.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Butane (CAS 106-97-8) 1 TONNES

Propane (CAS 74-98-6) 1 TONNES

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions

Not applicable

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

The chemicals listed in Section 3 are on the TSCA Chemical Substances Inventory.

CERCLA Hazardous Substance List (40 CFR 302.4)

Butane (CAS 106-97-8) Listed.

Propane (CAS 74-98-6) Listed.
Sodium hydroxide (CAS 1310-73-2) Listed.
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - Yes
Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)
Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)
Propane (CAS 74-98-6)

Clean Water Act (CWA) Section 112(r) (40 CFR 68.130) Hazardous substance

US state regulations California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US - California Hazardous Substances (Director's): Listed substance

Butane (CAS 106-97-8) Listed.
Monoethanolamine (CAS 141-43-5) Listed.
Sodium hydroxide (CAS 1310-73-2) Listed.

US - Illinois Chemical Safety Act: Listed substance

Butane (CAS 106-97-8)
Propane (CAS 74-98-6)
Sodium hydroxide (CAS 1310-73-2)

US - Louisiana Spill Reporting: Listed substance

Butane (CAS 106-97-8) Listed.
Propane (CAS 74-98-6) Listed.
Sodium hydroxide (CAS 1310-73-2) Listed.

US - Minnesota Haz Subs: Listed substance

Butane (CAS 106-97-8) Listed.
Monoethanolamine (CAS 141-43-5) Listed.
Propane (CAS 74-98-6) Listed.
Sodium hydroxide (CAS 1310-73-2) Listed.

US - New Jersey RTK - Substances: Listed substance

Butane (CAS 106-97-8)
Monoethanolamine (CAS 141-43-5)
Propane (CAS 74-98-6)
Sodium hydroxide (CAS 1310-73-2)

US - Texas Effects Screening Levels Hazard Data: Simple asphyxiant

Propane (CAS 74-98-6)

US - Texas Effects Screening Levels: Listed substance

Butane (CAS 106-97-8) Listed.
Monoethanolamine (CAS 141-43-5) Listed.
Propane (CAS 74-98-6) Listed.
Sodium hydroxide (CAS 1310-73-2) Listed.

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8)
Monoethanolamine (CAS 141-43-5)
Propane (CAS 74-98-6)
Sodium hydroxide (CAS 1310-73-2)

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8)
Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8)
Monoethanolamine (CAS 141-43-5)
Propane (CAS 74-98-6)
Sodium hydroxide (CAS 1310-73-2)

US. Rhode Island RTK

Butane (CAS 106-97-8)
Monoethanolamine (CAS 141-43-5)
Propane (CAS 74-98-6)
Sodium hydroxide (CAS 1310-73-2)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	/ 3
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X

**Disclaimer**

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

17-August-2018

Version #

01

Effective date

17-August-2018

Prepared by

Nu-Calgon Technical Service Phone: (314) 469-7000

Other information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.