



SAFETY DATA SHEET

	JAI	ETT DATA SHEET						
SECTION 1: PRODUCT	AND CO	MPANY IDENTIFICA	ATION					
PRODUCT IDENTIFIER	CelaPerl®, Celatom® Perlite expanded (all grades) DFP-80, 8030002, 8030342							
CHEMICAL NAME	Sodium Potassium Aluminum Silicate							
CHEMICAL FAMILY	Silicate							
MATERIAL USE	Functional additive, filter aid							
RESTRICTION ON USE	None Known							
MANUFACTURER	Disco 1895 Brannon Road McDonough, GA 30253							
TELEPHONE NO.	(770) 474-7575 (Monday – Friday 8:00 am PST – 5:00 pm PST)							
EMERGENCY TELEPHONE NO.	(215) 324-0213 (Monday – Friday 8:00 am PST – 5:00 pm PST)							
SDS DATE OF PREPARATION	June 10, 2015							
SECTION 2: HAZARDS	AZARDS IDENTIFICATION							
OSHA GHS HAZARD CLASSIFICATION	Not classified as hazardous							
HAZARDS NOT OTHERWISE CLASSIFIED	None							
LABEL ELEMENTS	No GHS labeling required							
SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS INGREDIENT IDENTIFICATION APPROXIMATE CONCENTRATION (%) C.A.S. NUMBERS EINECS								
Perlite, expanded		100%	93763-70-3	Not Assigned				
SECTION 4: FIRST AID		RES with generous quantities of wate	r or eye rinse solution. Consu	ult physician if irritation persists.				
SKIN	Use moistur	Use moisture renewing lotions if dryness occurs.						
NGESTION	Drink generous amounts of water to reduce bulk and drying effects.							
NHALATION	Remove to fresh air. Blow nose to evacuate dust.							
Most important symptoms/effects, acute and delayed	Dust may cause abrasive irritation to eyes. Prolonged skin contact may cause dryness. Dust may cause nose, throat and upper respiratory tract irritation. Prolonged inhalation of high concentration of dust may cause lung effects.							
Indication of immediate medical attention and special treatment, if necessary	Immediate medical attention is not normally required. If dust irritates the eyes, seek medical attention.							
SECTION 5: FIRE FIGHT	ING MEA	ASURES						
EXTINGUISHING MEDIA	Not applicab	ole, the material is not combustib	le.					
SPECIFIC HAZARDS ARISING FROM THE CHEMICAL	Not applicable, the material is not combustible.							
SPECIAL PROTECTIVE	Not applicable, the material is not combustible.							

MATERIAL NAME	CelaPerl®, Celatom® Perlite ex	Page 2 of 4							
SECTION 6: ACCIDENT	TAL RELEASE MEASU	RES							
PERSONAL PRECAUTIONS	If dust is present, use respirator f	itted with particulate fil	ter as specified in Sect	tion 8. Protect eyes with goggles.					
ENVIRONMENTAL PRECAUTIONS	This material is not a significant environmental concern.								
METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP	Vacuum clean spillage, wet sweep or wash away. Avoid creating dust. Place in a container for use or disposal.								
SECTION 7: HANDLING	S AND STORAGE								
PRECAUTIONS FOR SAFE HANDLING	Minimize dust generation. Avoid contact with eyes. Avoid breathing dust. Repair or dispose of broken bags. Observe all label precautions and warnings.								
CONDITIONS FOR SAFE STORAGE	Store in a dry place to maintain packaging integrity and product quality. Do not store near hydrofluoric acid or strongly basic solutions.								
SECTION 8: EXPOSUR	E CONTROLS / PERSO	NAL PROTEC	TION						
EXPOSURE GUIDELINES:									
Component	OSHA PEL	ACGIH TLV	MSHA PEL	NIOSH REL					
Perlite, expanded	5 mg/m³ (respirable dust) 15 mg/m³ (total dust)	None Established	30 mppcf	5 mg/m³ (respirable dust) 10 mg/m³ (total dust)					
ENGINEERING CONTROLS	Use general or local exhaust ventilation to control dust within recommended exposure limits. Refer to ACGIH publication "Industrial Ventilation" or similar publications for design of ventilation systems.								
PERSONAL PROTECTIVE EQUIPMENT:	, , , , , , , , , , , , , , , , , , ,								
EYE / FACE PROTECTION	Goggles to protect from dust								
SKIN PROTECTION	No special equipment is needed.								
RESPIRATORY PROTECTION	Respirators fitted with filters certified to standard 42CFR84 under series N95 should be worn when dust is present. If the dust concentration is less than ten (10) times the Permissible Exposure Limit (PEL) use a quarter or half-mask respirator with a N95 dust filter or a single use dust mask rated N95. If dust concentration is greater than ten (10) times and less than fifty (50) times the PEL, a full-face piece respirator fitted with replaceable N95 filters is recommended. If dust concentration is greater than fifty (50) and less than two hundred (200) times the PEL use a power air-purifying (positive pressure) respirator with a replaceable N95 filter. If dust concentration is greater than two hundred (200) times the PEL use a type C, supplied air respirator (continuous flow, positive pressure), with full face piece, hood or helmet.								
GENERAL HYGIENE	Avoid breathing dust. Avoid cont	act with eyes. Wash	hands after handling a	nd before eating or drinking.					
SECTION 9: PHYSICAL	AND CHEMICAL PRO	PERTIES							
APPEARANCE, COLOR	White to off white powder	ODOR		Odorless					
PHYSICAL STATE	Solid	ODOR THRESHO	LD	Not applicable					
/APOR PRESSURE	Not applicable	VAPOR DENSITY		Not applicable					
OILING POINT	Not applicable	MELTING POINT		> 800° C					
LASH POINT	Not applicable	pH (10% SUSPENSION)		7					
LAMMABILITY LIMITS	Not applicable	EVAPORATION RATE		Not applicable					
DECOMPOSITION TEMPERATURE	> 800° C	SPEC. GRAVITY DENSITY	RELATIVE	2.3					
AUTOIGNITION TEMPERATURE	Not applicable	PARTITION COEFFICIENT – n- OCTANOL/WATER		Not applicable					
FLAMMABILITY (solid/gas)	1	SOLUBILITY - WATER							
EAMINABILITY (Solidargus)	Not applicable	SOLUBILITY - W.	ATER	< 1%					

MATERIAL NAME	CelaPerl®, Celatom® Perlite expanded (all grades)	Page 3 of 4					
SECTION 10: STAB	ILITY AND REACTIVITY	1					
REACTIVITY	Material is not reactive.						
CHEMICAL STABILITY	Material is stable.	Material is stable.					
POSSIBILITY OF HAZARDOU REACTIONS	Material is not reactive.						
CONDITIONS TO AVOID	Not applicable						
INCOMPATIBLE MATERIALS	Products containing silica may react violently with hydrofluoric acid and strongly basic solutions	•					
HAZARDOUS DECOMPOSITI PRODUCTS	Not applicable	Not applicable					
SECTION 11: TOXIC	COLOGICAL INFORMATION						
POTENTIAL HEALTH EFFEC	See below and Section 11 for additional information						
Likely Routes of Exposur	See below						
EYE	May cause irritation (tear formation and redness) if dust gets in eyes.	May cause irritation (tear formation and redness) if dust gets in eyes.					
SKIN	Not absorbed by the skin, but may cause dryness if prolonged exposure.						
INGESTION	Ingestion of small to moderate quantities is not considered harmful, but may cause irritation of and stomach.	Ingestion of small to moderate quantities is not considered harmful, but may cause irritation of the mouth, throa and stomach.					
INHALATION	Acute inhalation can cause dryness of the nasal passage and lung congestion, coughing and general throat irritation. Chronic inhalation of dust should be avoided.						
CHRONIC EFFECTS	Chronic inhalation of dust in excess of the Permissible Exposure Limit (PEL) established by OSI prolonged number of years may cause lung changes.	HA over a					
CARCINOGENICITY Analyses of these products by X-ray diffraction have not identified any phases of crystalline silica to above the detection limit (0.05%).		a to be present					
NTP Perlite is not classified as a carcinogen.							
IARC	Perlite is not classified as a carcinogen.	Perlite is not classified as a carcinogen.					
NUMERICAL MEASURES OF TOXICITY	LD50 oral mouse 12,960 mg/kg						
CORROSIVENESS, SENSITIZATION, IRRITANCY	Not applicable						
REPRODUCTIVE TOXICITY	Not available						
TERATOGENICITY, MUTAGENICITY	Not available						
SECTION 12: ECOL	OGICAL INFORMATION						
ECOTOXICITY:	These products have no demonstrated toxicity in regards to aquatic or terrestrial life.	These products have no demonstrated toxicity in regards to aquatic or terrestrial life.					
PERSISTENCE AND DEGRADABILITY	Non-biodegradable, inert.						
BIOACCUMULATIVE POTENT	Little potential for bioaccumulation						
MOBILITY IN SOIL	No mobility						
OTHER ADVERSE EFFECTS	None known						
SECTION 13: DISPO	SAL CONSIDERATIONS						
VASTE DISPOSAL	If this material as supplied becomes a waste, use solid waste disposal common to landfill type operation sumps. Not considered a hazardous waste under RCRA (40CFR Part 261).	ons or in slurry to					
PACKAGING DISPOSAL	Dispose of in accordance with applicable laws and regulations, typically solid waste disposal common operations.	spose of in accordance with applicable laws and regulations, typically solid waste disposal common to landfill type erations.					

MATERIAL NAME	CelaPerl®, Celatom® Perlite expanded (all grad	CelaPerl®, Celatom® Perlite expanded (all grades)					
SECTION 14: TRANSPORT INFORMATION							
BASIC SHIPPING INFORMATI	DOT shipping classification 55 (no restrictions). Technical name is "Perlite".						
ADDITIONAL INFORMATION	No special requirements or placarding necessary.						
SECTION 15: REGULATORY INFORMATION							
U.S. FEDERAL:							
TSCA	Perlite is not on the EPA TSCA inventory list by name but as a natural material, it is automatically included.						
CERCLA	Perlite is not classified as a hazardous substance under regulations of the Comprehensive Environmental Response Compensation and Liability Act (CERCLA), 40 CFR 302.						
SARA TITLE III	Not listed.						
INTERNATIONAL:							
WHMIS Classification	These products are not regulated by WHMIS						
WHMIS Ingredient Disclosure List	No reportable ingredients are present.						
SECTION 16: OTHER INFORMATION							
		HMIS	0 Health				
	4-Extreme 3-High 1 0 2-High 2-Slight		0 Flammability				
	Z-Moderate 1-Slight 0-Insignificant		0 Reactivity				
			E Protective Equipment				
ORIGINAL ISSUE DATE	May 26, 1993						
REVISION DATE	June 10, 2015						
REVISION NO.	8						

Disclaimer: As of the date of the preparation of this document, the foregoing information is believed to be accurate and is provided in good faith to comply with applicable federal and state laws. No warranty, representation or guaranty of any kind, express or implied, is hereby provided or intended with respect to the completeness of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by the purchase, resale, use or exposure to our product. Customer users of silica must comply with all applicable health and safety laws, regulations and orders, including OSHA Hazardous Communication Standard.

4626 N. 15th Street Philadelphia, PA 19140 800-523-3814 ~ 215-324-0213 ~ fax 215-324-1290 www.cellucap.com www.discoinc.com