



MATERIAL SAFETY DATA SHEET

MSDS NUMBER: MSDS-1605 ISSUE DATE: 04/16/09

PAGE 1 OF 5

1. PRODUCT AND COMPANY IDENTIFICATION

Product Names

OxiClean Versatile Stain Remover

<u>Product Use</u>: Cleaning product used as Laundry Booster, Carpet Spot Remover and Hard Surface Cleaner Church & Dwight Co., Inc. 469 N. Harrison Street Princeton, NJ 08540

Emergency Phone: 1-800-424-9300 Medical Emergency Phone: 1-888-234-1828 <u>Customer Service</u> 1-800-781-7529

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW White powder with blue specks. Eye irritant. May cause burning and redness. May cause skin irritation. Can react with alkaline materials or metals. Can emit toxic fumes if mixed with products containing chlorine or other sanitizing ingredients. Not a fire hazard. This product is labeled in accordance with regulations administered by the Consumer Product Safety Commission (CPSC). However, the use pattern and exposure in the workplace are generally not consistent with those experienced by consumers. Protective measures, with the exception of those indicated on the label, are not normally necessary. Therefore, the requirements of the Occupational Safety and Health Administration applicable to this MSDS differ from the labeling requirements of the CPSC, and this MSDS may contain additional health hazard information not pertinent to consumer use and not found on the product label; such as appropriate protective measures to prevent eye and prolonged skin contact (glasses, goggles, rubber gloves, protective clothing) and minimize inhalation exposure (engineering controls, NIOSH-approved respiratory protection appropriate for the hazard presented) are recommended. **HMIS Rating** Health 1 Fire 0

CORPORATE HEADQUARTERS: 469 North Harrison Street • Princeton, New Jersey 08543-5297 • Phone (609) 683-5900

Reactivity

0





MATERIAL SAFETY DATA SHEET

MSDS NUMBER: MSDS-1605

ISSUE DATE: 04/16/09

PAGE 2 OF 5

Potential Health Effects

Primary Route(s) of Entry: Eyes, skin contact, inhalation, ingestion

EYE: Potential for severe irritation if not treated immediately. Corneal damage on extended exposure. SKIN CONTACT: Varying severities of irritation are possible from prolonged, repeated, or occluded exposure to skin. Contact on a burn or other wound likely to cause stinging pain or irritation. INGESTION: Ingested amounts may cause burning and pain in the mouth and throat with redness and swelling of mucous membranes. May cause pain, vomiting, dizziness. Harmful if swallowed. INHALATION: Dust may cause irritation to the upper respiratory tract.

SUBCHRONIC EFFECTS/CARCINOGENICITY: None known. Not classified as carcinogenic by IARC, NTP, OSHA, OR ACGIH or NIOSH.

3.	COMPOSITION/INFORMATION ON INGREDIENTS			
	CAS Number	Chemical Ingredients	<u>% By Wt.</u>	
	0497-19-8	Sodium carbonate	50-75%	
	15630-89-4	Sodium percarbonate	30-45%	
	68002-97-1	Ethoxylated Alcohol C12-C16	1-3%	
	68479-09-4	Sodium polycarboxylate	1%	
	06834-92-0	Sodium metasilicate	1%	

4. FIRST AID MEASURES

EYES: Immediately flush eyes with a directed stream of water for at least 15 minutes, forcibly holding eyelids apart to insure complete irrigation of all eye and lid tissues. IF IRRITATION PERSISTS GET MEDICAL ATTENTION.

SKIN: Remove contaminated clothing, including footwear. Wash contaminated areas thoroughly with soap and water. Wash clothing before reuse. Do not reuse footwear that is contaminated on the inner surfaces. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS.

INHALATION: Immediately move from area of exposure to fresh air. If breathing is difficult have a trained person administer oxygen. If breathing has stopped, have a trained person administer artificial respiration. GET MEDICAL ATTENTION IMMEDIATELY.

INGESTION: NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. If ingested, do not induce vomiting. If the patient is conscious and can swallow, first rinse out mouth and then give one or two glasses of water to drink. GET MEDICAL ATTENTION IMMEDIATELY.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES FLASHPOINT: Not flammable METHOD USED: Not applicable FLAMMABLE LIMITS LFL: Not applicable UFL: Not applicable

CORPORATE HEADQUARTERS: 469 North Harrison Street • Princeton, New Jersey 08543-5297 • Phone (609) 683-5900





MATERIAL SAFETY DATA SHEET

MSDS NUMBER: MSDS-1605

ISSUE DATE: 04/16/09

PAGE 3 OF 5

EXTINGUISHING MEDIA: CO2, powder, water spray.

FIRE-FIGHTING INSTRUCTIONS: Use a self-contained breathing apparatus (SCBA) and full protective equipment (Bunker Gear).

UNUSUAL FIRE AND EXPLOSION HAZARDS: Material decomposes exothermically when damp. Rapid evolution of oxygen may increase intensity of fire.

6. ACCIDENTAL RELEASE MEASURES

Wear personal protective equipment (See Section 8). Close off area to traffic. Large spills should be contained, swept up and placed into containers for disposal.

7. HANDLING AND STORAGE

Wear protective equipment when handling material to prevent skin and eye contact. Avoid breathing dust. Store in a cool, dry area away from incompatible substances. Keep containers closed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS: None

ENGINEERING CONTROLS: General ventilation should be adequate. Use local exhaust if necessary. RESPIRATORY PROTECTION: Not normally required. Wear a NIOSH approved respirator with an organic vapor/mist cartridge where spray or mist exposure occurs, or where vapors are generated from mixes with incompatible materials.

PROTECTIVE GLOVES: Impervious (rubber or neoprene) gloves where contact is likely. EYE PROTECTION: None under normal use. Use safety glasses with side shields or full face shields for industrial use.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None. Eyewash facility is recommended in work area or in close proximity.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: White to off white powder with blue specks. ODOR: None PHYSICAL STATE: Solid pH AS IS: 10.5 (1% in H₂O) VAPOR PRESSURE: Not applicable VAPOR DENSITY: Not applicable BOILING POINT @ 760mm Hg: 215 ° F MELTING POINT: Not applicable SOLUBILITY IN WATER % by WT: 140g/l @75°F SURFACE TENSION: Not determined

CORPORATE HEADQUARTERS: 469 North Harrison Street • Princeton, New Jersey 08543-5297 • Phone (609) 683-5900





MATERIAL SAFETY DATA SHEET

MSDS NUMBER: MSDS-1605

ISSUE DATE: 04/16/09

PAGE 4 OF 5

SPECIFIC GRAVITY (Water = 1): 1.06 g/cc @ 20°C VOLATILE ORGANIC COMPOUNDS: None

10. STABILITY AND REACTIVITY

CONDITIONS TO AVOID: High temperatures (55°C, 130°F), High humidity levels, contaminants. CHEMICAL STABILITY: Stable under normal conditions. Product will evolve oxygen upon contact with water.

INCOMPATIBILITY WITH OTHER MATERIALS: Oxidizers, reducing agents, flammable substances.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxygen evolves from contaminated material. Evolved oxygen can support combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity: Not determined Reproductive toxicity/Teratogenicity: No components listed. Mutagenicity: Not determined Toxicologically synergistic products: None known.

12. ECOTOXICOLOGICAL INFORMATION

TOXICITY: This product is expected to be moderately toxic to aquatic animals. PERSISTENCE: This product is not expected to persist in the environment. BIOACCUMULATION: This product is not expected to bioaccumulate.

13. DISPOSAL CONSIDERATIONS

Dispose of waste product in accordance with all government regulations. State and local regulations may differ from federal. Be sure to consult with state and local agencies for specific rules.

14. TRANSPORTATION INFORMATION

DOT proper shipping name: Not regulated (Data indicates that Sodium percarbonate <60% is not an oxidizer)

15. REGULATORY INFORMATION

TSCA: The components of this product are reported in the EPA TSCA Inventory List. OSHA: Hazardous under 29 CFR 1910.1200 CERCLA REPORTABLE QUANTITY: CERCLA requires that releases of hazardous substances to land, air or water, which are equal to or exceed the reportable quantity (RQ) be reported to the National Response Center (800-424-8802

CORPORATE HEADQUARTERS: 469 North Harrison Street • Princeton, New Jersey 08543-5297 • Phone (609) 683-5900





MATERIAL SAFETY DATA SHEET

MSDS NUMBER: MSDS-1605 ISSUE DATE: 04/16/09

PAGE 5 OF 5

RCRA: If this material becomes waste, it would not be a hazardous waste. SARA TITLE III: Section 302, Extremely Hazardous Substances: None Section 311/312, Hazardous Categories: Sodium Percarbonate- reaction hazard. Section 313, Toxic Chemicals: None DSL: All components listed. WHMIS Classification: Sodium percarbonate Class C, D2B

16. OTHER INFORMATION

SUPERSEDES DATE: 10/12/07

REASON FOR REVISION: formula update

For additional non-emergency health, safety and environmental information telephone 609.279.7705 or write to:

Church & Dwight Co. Inc. Product Stewardship 469 North Harrison Street Princeton, New Jersey 08543

This Product Safety Data Sheet is offered solely for your information, consideration and investigation. Church & Dwight Co., Inc. provides no warranties; either expressed or implied, and assumes no responsibility for the accuracy or completeness of data contained herein. Church & Dwight Co., Inc. urges persons receiving this information to make their own determination as to the information suitability for their particular application.