

SAFETY DATA SHEET

Page 1 of 4

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION		
PRODUCT IDENTIFIER	DE125	
CHEMICAL NAME	Diatomaceous Earth, Flux-Calcined	
CHEMICAL FAMILY	Silica	
MATERIAL USE	Filter Aid	
RESTRICTION ON USE	None Known	
DISTRIBUTER	Disco Inc., 1895 Brannan Road, McDonough, GA 30253	
TELEPHONE NO.	(770) 474 7575	
EMERGENCY TELEPHONE NO.	(800) 255 3924 - ChemTel, Inc.	
SDS DATE OF PREPARATION	January 31, 2014	
SECTION 2: HAZARDS IDENTIFICATION		
OSHA GHS HAZARD CLASSIFICATION	Carcinogen Category 1A Specific Target Organ Toxicity, Repeated Exposure Category 1	
HAZARDS NOT OTHERWISE CLASSIFIED	None	
LABEL ELEMENTS	DANGER May cause cancer by inhalation. Causes damage to lungs through prolonged or repeated exposure. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wear eye protection. If exposed or concerned: Get medical advice. Dispose of contents in accordance with local, state and federal regulations. 	
SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS		
INGREDIENT IDENTIFICATION	APPROXIMATE CONCENTRATION (%)	C.A.S. NUMBERS
Diatomaceous Earth, Flux-Calcined (kieselguhr) (contains 35-50% Crystalline Silica - Cristobalite)	100%	68855-54-9 14464-46-1
SECTION 4: FIRST AID MEASURES		
EYE	Flush eyes with generous quantities of water or eye rinse solution. Consult physician if irritation persists.	
SKIN	Use moisture renewing lotions if dryness occurs.	
INGESTION	Drink generous amounts of water to reduce bulk and drying effects.	
INHALATION	Remove to fresh air. Blow nose to evacuate dust.	
Most important symptoms/effects, acute and delayed	Dust may cause abrasive irritation to eyes. Prolonged skin contact may cause dryness. Dust may cause nose, throat and upper respiratory tract irritation. Prolonged inhalation of respirable dust containing silica may cause a progressive lung disease, silicosis and lung cancer. See Section 11 for additional information.	
Indication of immediate medical attention and special treatment, if necessary	Immediate medical attention is not normally required. If dust irritates the eyes, seek medical attention.	

MATERIAL NAME	Diatomaceous Earth, DE125, DE125SYS, 11022951, 415403-1	Page 2 of 4
---------------	---	-------------

SECTION 5: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA	Not applicable, the material is not combustible.
SPECIFIC HAZARDS ARISING FROM THE CHEMICAL	Not applicable, the material is not combustible.
SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS	Not applicable, the material is not combustible.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS	If dust is present, use respirator fitted with particulate filter as specified in Section 8. Protect eyes with goggles. Do not breathe dust.
ENVIRONMENTAL PRECAUTIONS	This material is not a significant environmental concern.
METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP	Vacuum clean spillage or wet sweep. Avoid creating airborne dust. Place in a container for use or disposal.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING	Minimize dust generation. Avoid contact with eyes. Do not breathe dust. Repair or dispose of broken bags. Observe all label precautions and warnings.
CONDITIONS FOR SAFE STORAGE	Store in a dry place to maintain packaging integrity and product quality. Do not store near hydrofluoric acid or concentrated caustic solutions.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES:				
Component	OSHA PEL	ACGIH TLV	MSHA PEL	NIOSH REL
Diatomaceous Earth, Flux-Calcined (kieselguhr)	5 mg/m ³ respirable dust 15 mg/m ³ total dust	None Established	5 mg/m ³ respirable dust 15 mg/m ³ total dust	None Established
Crystalline Silica (Cristobalite)	$\frac{1}{2} \times \frac{30 \text{ mg/m}^3}{\% \text{ SiO}_2 + 2}$ total dust $\frac{1}{2} \times \frac{10 \text{ mg/m}^3}{\% \text{ SiO}_2 + 2}$ Respirable dust	0.025 mg/ m ³ Respirable dust	$\frac{1}{2} \times \frac{30 \text{ mg/m}^3}{\% \text{ SiO}_2 + 2}$ total dust $\frac{1}{2} \times \frac{10 \text{ mg/m}^3}{\% \text{ SiO}_2 + 2}$ Respirable dust	0.05 mg/ m ³ Respirable dust
ENGINEERING CONTROLS	Use general or local exhaust ventilation to control dust within recommended exposure limits. Refer to ACGIH publication "Industrial Ventilation" or similar publications for design of ventilation systems.			
PERSONAL PROTECTIVE EQUIPMENT:				
EYE / FACE PROTECTION	Goggles to protect from dust			
SKIN PROTECTION	No special equipment is needed.			
RESPIRATORY PROTECTION	Respirators fitted with filters certified to standard 42CFR84 under series N95 should be worn when dust is present. If the dust concentration is less than ten (10) times the Permissible Exposure Limit (PEL) use a quarter or half-mask respirator with a N95 dust filter or a single use dust mask rated N95. If dust concentration is greater than ten (10) times and less than fifty (50) times the PEL, a full-face piece respirator fitted with replaceable N95 filters is recommended. If dust concentration is greater than fifty (50) and less than two hundred (200) times the PEL use a power air-purifying (positive pressure) respirator with a replaceable N95 filter. If dust concentration is greater than two hundred (200) times the PEL use a type C, supplied air respirator (continuous flow, positive pressure), with full face piece, hood or helmet.			
GENERAL HYGIENE	Avoid breathing dust. Avoid contact with eyes. Wash hands after handling and before eating or drinking.			

MATERIAL NAME	Diatomaceous Earth, DE125, DE125SYS, 11022951, 415403-1	Page 3 of 4
---------------	---	-------------

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES


APPEARANCE, COLOR	Light pink to white powder	ODOR	Odorless
PHYSICAL STATE	Solid	ODOR THRESHOLD	Not applicable
VAPOR PRESSURE	Not applicable	VAPOR DENSITY	Not applicable
BOILING POINT	Not applicable	MELTING POINT	> 1300° C
FLASH POINT	Not applicable	pH (10% SUSPENSION)	10
FLAMMABILITY LIMITS	Not applicable	EVAPORATION RATE	Not applicable
DECOMPOSITION TEMPERATURE	> 1300° C	SPEC. GRAVITY / RELATIVE DENSITY	2.3
AUTOIGNITION TEMPERATURE	Not applicable	PARTITION COEFFICIENT – n-OCTANOL/WATER	Not applicable
FLAMMABILITY (solid/gas)	Not applicable	SOLUBILITY – WATER	< 1%
		VISCOSITY	Not applicable

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY	Material is not reactive.
CHEMICAL STABILITY	Material is stable.
POSSIBILITY OF HAZARDOUS REACTIONS	Material is not reactive under normal conditions of handling unless mixed with incompatible substances below.
CONDITIONS TO AVOID	Not applicable
INCOMPATIBLE MATERIALS	Hydrofluoric acid and concentrated caustic solutions may react violently with the product.
HAZARDOUS DECOMPOSITION PRODUCTS	Not applicable

SECTION 11: TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS	
Likely Routes of Exposure	See below
EYE	May cause irritation (tear formation and redness) if dust gets in eyes.
SKIN	Not absorbed by the skin, but may cause dryness if prolonged exposure.
INGESTION	Ingestion of small quantities is not considered harmful, but may cause irritation of the mouth, throat and stomach.
INHALATION	Acute inhalation can cause dryness of the nasal passage and lung congestion, coughing and general throat irritation. Acute inhalation of high concentrations of respirable crystalline silica may cause acute silicosis.
CHRONIC EFFECTS	This product contains crystalline silica. Respirable crystalline silica may cause lung cancer and lung disease (silicosis) if inhaled for prolonged periods. Symptoms of silicosis include wheezing, cough and shortness of breath.
CARCINOGENICITY	Flux-calcined diatomaceous earth (Kieselguhr) is composed of amorphous and crystalline silica. Respirable crystalline silica (cristobalite) is classified by IARC and NTP as a known human carcinogen. Crystalline silica is only known to cause cancer when inhaled in a respirable form. It is not known to cause cancer by any other route of exposure.
NTP	Respirable crystalline silica (cristobalite) is classified as a known human carcinogen.
IARC	Respirable crystalline silica (cristobalite) is classified as a known human carcinogen.
NUMERICAL MEASURES OF TOXICITY	No data available
CORROSIVENESS, SENSITIZATION, IRRITANCY	Not applicable

MATERIAL NAME	Diatomaceous Earth, DE125, DE125SYS, 11022951, 415403-1			Page 4 of 4
REPRODUCTIVE TOXICITY	Not available			
TERATOGENICITY, MUTAGENICITY	Not available			
SECTION 12: ECOLOGICAL INFORMATION				
ECOTOXICITY:	Diatomaceous earth products have shown some efficacy as a natural insecticide, but otherwise have no demonstrated toxicity in regards to aquatic or terrestrial life.			
PERSISTENCE AND DEGRADABILITY	Non-biodegradable, inert.			
BIOACCUMULATIVE POTENTIAL	Little potential for bioaccumulation			
MOBILITY IN SOIL	No mobility			
OTHER ADVERSE EFFECTS	None known			
SECTION 13: DISPOSAL CONSIDERATIONS				
WASTE DISPOSAL	If this material as supplied becomes a waste, use solid waste disposal common to landfill type operations or in slurry to sumps. Not considered a hazardous waste under RCRA (40CFR Part 261).			
PACKAGING DISPOSAL	Dispose of in accordance with applicable laws and regulations, typically solid waste disposal common to landfill type operations.			
SECTION 14: TRANSPORT INFORMATION				
BASIC SHIPPING INFORMATION	DOT shipping classification 55 (no restrictions). Technical name is "Diatomaceous Earth".			
ADDITIONAL INFORMATION	No special requirements or placarding necessary.			
SECTION 15: REGULATORY INFORMATION				
U.S. FEDERAL:				
TSCA	Diatomaceous Earth and Cristobalite appear on the EPA TSCA inventory list.			
CERCLA	Diatomaceous Earth is not classified as a hazardous substance under regulations of the Comprehensive Environmental Response Compensation and Liability Act (CERCLA), 40 CFR 302.			
SARA TITLE III	Not listed.			
California Proposition 65:	This product contains crystalline silica, a chemical known to the State of California to cause cancer.			
INTERNATIONAL:				
WHMIS Classification	Class D-2-A			
WHMIS Ingredient Disclosure List	Silica, crystalline, cristobalite			
SECTION 16: OTHER INFORMATION				
			0* Health 0 Flammability 0 Reactivity E Protective Equipment	
ORIGINAL ISSUE DATE	November 18, 1985			
REVISION DATE	August, 2016			
REVISION NO.	12			

Disclaimer: As of the date of the preparation of this document, the foregoing information is believed to be accurate and is provided in good faith to comply with applicable federal and state laws. No warranty, representation or guaranty of any kind, express or implied, is hereby provided or intended with respect to the completeness of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by the purchase, resale, use or exposure to our product. Customer users of silica must comply with all applicable health and safety laws, regulations and orders, including OSHA Hazardous Communication Standard.