



SAFETY DATA SHEET

SECTION 1

Product and Company

1.1 Product identifier

Product Name: Jealous Devil Hex

1.2 Relevant Identified Uses and Uses Advised Against

Use: Barbeque fuel

1.3 Details of the supplier of the Safety Data Sheet

Jealous Devil LLC 300 E 2nd St 15th Floor Reno, NV 89501

1.4 Emergency telephone number

6615328767

1.5 HS Code

4402900100

SECTION 2

Hazard Identification

Hazard Description : NON HAZARDOUS

Appearance : SOLID

Emergency Overview : Hardwood sawdust can cause irritation of trachea and eyes, workers should use appropriate precaution when dealing with this material.

SECTION 3

Composition / information on ingredients

CAS#s and/or concentration percentages are proprietary/trade secret

SECTION 4

Description of first aid measures

Inhalation : Remove to fresh air. If persistent irritation, severe coughing, breathing difficulties occur, get medical advice before returning to work where wood dust is present.

Skin contact : If a rash or persistent or dermatitis occurs, get medical advice before returning to work where wood dust is present.

Eye contact : Flush with water to remove dust particles. If irritation persists, get medical attention.

Ingestion : First aid is not required; however, if ingested and symptoms develop, seek medical attention.

SECTION 5

Fire Fighting Measures

5.1 Extinguishing media

Water, foam, CO2, sand or dirt.

5.2 Specific hazards arising from the substance or mixture.



This material may burn but will not ignite easily.

5.3 Recommendations for firefighting personnel.

5.3.1 Instructions for firefighting:

Spray with water until the fire is smothered.

5.3.2 Protection during firefighting:

Wear self-contained breathing apparatus on sustained fire.

5.3.3 Decomposition products:

In case of fire, it can release irritating and / or toxic fumes and gases such as carbon monoxide.

SECTION 6

Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures.

6.1.1 Personal precautions, protective equipment and emergency procedure: Avoid sources of ignition.

6.1.2 For emergency personnel: Avoid sources of ignition

6.2 Environmental precautions.

Contain the solid to prevent it from scattering.

6.3 Methods and material for containment and cleaning up.

Sweep or vacuum spills for recovery or disposal, avoiding creating dust conditions. Provide good ventilation where dust conditions may occur. Place recovered wood dust in a container for disposal.

Wood saw dust debris on the floor present a slip and fall hazard.

SECTION 7

Handling and Storage

7.1 Precautions for safe handling.

Without particular indications.

7.2 Conditions for safe storage, including any incompatibilities. Carton was strapped parallel with two plastic band and keep in tight closed carton, store in dry and ventilated area. Protect against physical damage. Keep away from strong oxidizer such as ozone, liquid oxygen and gasoline etc.

SECTION 8

Exposure Controls/ Personal Protection

8.1 Exposure controls.

Keep the workplace ventilated, in addition to keeping the work area clean of dust and fiber through the use of vacuuming and / or sweeping equipment.

8.2 Personal protective equipment.

Eye protection: Safety glasses.

Skin care: Wear a long-sleeved shirt that covers the base of the neck, long pants and gloves (heat resistant and waterproof). Skin irritation occurs mainly at pressure points such as the neck, wrists, waist, and between the fingers.

Respiratory protection: Respiratory protection is not required when working with the solid material, you can use a mask if necessary.



SECTION 9

Physical and Chemical Properties

Appearance and Color: Black, Solid, hexagonal

Odour : N.A

P.H : N.A

Explosive Properties : N.A

Oxidizing Properties : N.A

SECTION 10

Stability and reactivity

Avoid heat and ignition sources Stability: Stable under normal use Incompatibility: Strong oxidizers

SECTION 11

Toxicological Information

Acute Symptoms / Signs of exposure: Eye pain, watery eyes, swollen eyelids, itchy skin and conjunctivitis.

Insensitivity to pain, feeling cold or clammy skin looks white and feels hard and cold.

Ingestion: mental confusion, drowsiness, nausea, vomiting and headache. Irregular breathing. Rapid breathing, headache, fatigue, mental confusion, nausea and vomiting.

Chronic effects: Prolonged skin contact may cause skin dryness or rash.

Sensitization: None expected

Coal: LD50 (oral, rat) N/A, LC50 (rat) N/A; dermal LD50 (rabbit) N/A

The material has not been found to be carcinogen or produce reproductive, developmental or genetic effects.

SECTION 12

Ecological Information

Eco-toxicity (aquatic and terrestrial): environmental impact has not been determinate.

SECTION 13

Disposal considerations

Check with all local, regional and national laws and regulations. Regulations may be stricter than national regulations in the region. Small amounts of this material may be suitable for sanitary sewer or waste disposal.



SECTION 14

Transport information

Proper Shipping Name: Not applicable.

Hazard Class: Not applicable. This product has been tested according to the Nations Transport of Dangerous Goods test protocol for spontaneously combustible materials. It has been specifically determinate that this product does not meet the definition of self-heating substance or any hazard class, and therefore is nor hazardous material and not regulated.

Identification number: Not applicable

Packing Group: Not applicable

Name: Not applicable.

SECTION 15

Regulatory Information

The product has been classified in accordance with the hazard criteria of Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

SECTION 16

Other Information

Issued Date: July, 06th 2023