



PHD 200

Compact, versatile dehumidifier. Ideal for crawlspace and other temporary use or installation in moisture-prone areas that need ongoing humidity control. Install in basements, crawlspaces, equipment rooms or other areas. Features the new [Command Hub](#), compatible with the new Command Center App. Available now in the [Apple Store](#) and [Google Play Store](#).



FEATURES

- **Command Center App Users!** For dehu firmware update instructions, visit [Mastering your Dri-Eaz Command Center](#) and scroll down to "Update Your Dri-Eaz Dehumidifier's Command Hub Firmware."
- NEW! Command Hub touchscreen controller displays real-time temp, RH, grain depression and drying progress trends at a glance. Controller integration product for existing i-Series dehumidifiers also available. [Learn more.](#)
- Humidistat keeps moisture under control—set for 40%–90% RH in 5% increments.
- Fast and convenient access to humidistat, job hours, maintenance reminders and more. Display in 3 languages.
- Automatic pumpout allows continuous operation—pumps out up to 3 ft. (1 m) above unit.
- Auto-restart after outage when power is restored.

SIZES - OPTIONS

- **103806 (F515):** One unit
- **116689 (F527):** Filters for PHD 200 - Pack of 3

SPECIFICATIONS

- **Water removal:** 74 pts/day | 35 L/day at 80°F/60%RH (AHAM)
120 pts/day | 57 L/day at 90°F/90%RH
- **Air movement:** 180 CFM | 305 CMH
- **Dimensions (W × H × D):** 12.5 × 17.6 × 21.5 in.
31.8 × 44.7 × 130.8 cm
- **Housing:** Rotomolded polyethylene
- **Weight (w/cord & hose):** 65 lbs. | 29.5 kg
- **Amps:** 6.2A (at 80°F/60%RH)
- **Volts:** 115V
- **Frequency:** 60Hz
- **Sound level (ave.):** 55 dB
- **Operating range:** 45°F–100°F | 7°C–38°C
- **Safety:** ETL listed to CSA standards