SPRING DRIVEN

SPRING DRIVEN REELS ACCESSORIES

HOMENO	_			_	_	RF	FI 9	SER	IFS	_	_	
MOUNTING &						.112		JEM!				
ROLLER B.	RACKETS	PART NO.	Ь	SH, MP & HP	_	S	EN	PC	P-W & SHW	P-WC	Alumi-Pro®	Nitro-Pro®
•	Swing Bracket For vertical surface mounting (only stationary installations),						•	•	•	•	•	•
- 1-	allows reel to swing 180°. Powder coated crinkle black 1/4" steel. Weight: 5 lbs.	15725			•	•						
	Swivel Bracket For horizontal surface mounting (only stationary installations), ball bearing rotation, allows reel to swivel 345°. Powder coated crinkle black heavy gauge steel. Weight: 6 lbs. NOT FOR USE IN CEILING APPLICATIONS.				•	•	•	•	•	•	•	•
	EZ-Up Bracket Reel easily slides in & out for easy overhead mounting. Use as an alternative to the #MR- 1. Must be ordered with #15724 for "I" or "H" beam installations. Weight: 6.5 lbs.	15723	•	•			•	•	•	•	•	•
	EZ-Up "I" or "H" Beam Adapter Must be ordered with #15723. Powder coated crinkle black, all steel construction. Weight: 5 lbs.	15724	•	•			•	•	•	•	•	•
For overhead mounting	Mounting Bracket For overhead mounting, fits 3" to 8 ½" flange on "I" or "H" beam.	MR-1	•	•			•	•	•	•	•	•
1	Powder coated crinkle black 3/16" bent steel. Weight: 13 lbs.				•	•						
	4-Way Roller Bracket Heavy gauge steel, powder	4RB 1/4"-3/4"	•	•	•	•	•	•	•	•	•	•
	coated Coxreels blue (4RB) Available in stainless steel (4RB-SS).	4RB-SS	•	•	•	•	•	•	•	•	•	•
	Available with solid delring rollers (4SR & 4SR-SS)	4SR 1/4"-3/4" 4SR-SS	•	•	•	•	•	•	•	•	•	•
0	Weight: 1 lbs.	45R-35 1/4"-3/4" 4SRB-4	•	•	•	•	•	•	•	•	•	•
	4-Way Roller Bracket Heavy gauge steel, powder coated Coxreels blue with	1/2"	•	•	•	•	•				•	
	stainless steel rollers (4SRB) Available in stainless steel	4\$RB-5		•	•							
B.	(4SRB-SS). Weight: 1 lbs.	4SRB-6			•							

S SERIES MOUNTING & ROLLER BRACKETS PART NO.			S SERIES MODELS					
			SR13 & SL13	SR15 & SL15	SR17 & SL17	SR19 & SL19		
TT .	Dual Side Mount Bracket	15726-13	•					
	Heavy gauge steel, powder coated crinkle black. Weight: 5 lbs.							
	A LA	15726-17	•					
		15726-19				•		
	Single Side	SMB1	•	•				
	Mount Bracket Heavy gauge steel, powder coated crinkle	SMB2			•			
	blackWeight: 2 lbs.	SMB 3				•		

INLET HOSE ASSEMBLIES	PART NO.	FITTINGS	I.D.	LENGTH	PSI
	5150-1.5	1/4" Male x Female NPT	1/4"	18"	300
	5153-1.5	3/8" Male x Female NPT	3/8"	18"	300
	5154-1.5	¹ /2" Male x Female NPT	1/2"	18"	300
	5155-1.5	3/4" Male x Male NPT	3/4"	18"	300
	5224-1.5	3/8" Male x Male NPT	3/8"	18"	3,000
	5256-1.5	1/2" Male x Male NPT	1/2"	18"	2,500
	5290-1.5	3/4" Male x Male NPT	3/4"	18"	1,500
	5304-1.5	¹ /4" Male x Male NPT	1/4"	18"	5,000
Miles .	5336-1.5	3/8" Male x Male NPT	3/8"	18"	4,000
	15717	Garden 3/4"(w/Part #10781) x 3/4" NPT w/adaptor #10782	1/2"	48"	300
	5423-1.5	Twin Grade R ¹ /8" NPTM x BB 9-16 UNF	1/4" Twin	18"	200
	5424-1.5	"T" Grade Twin Grade R 1/4" Twin NPTM x BB 9-16 UNF Twin		18"	200
_					

90° ELBOWS	PART NO.	FITTING THREAD	I.D.	PSI
	6088	Brass LP Male x Female NPT	1/4"	300
	208	Brass LP Male x Female NPT	3/8"	300
	222	Brass LP Male x Female NPT	1/2"	300
	385	Brass LP Male x Female NPT	3/4"	300
	500	Steel MP Male x Female NPT	3/8"	3,000
A THE THE PARTY OF	1671	Steel MP Male x Female NPT	1/2"	3,000
The same of the sa	15014	Steel MP Male x Female NPT	3/4"	1,250
	616	Steel HP Male x Female NPT	1/4"	5,000
	617	Steel HP Male x Female NPT	3/8"	5,000

HUSE STUPS	HOSE STOPS	HOSE GUARD	Н	JSE	CORD	OVERALL	
& GUARDS	PART NO.	PART NO.	I.D.	0.D.	COND		
	131	237-1	1/4"	1/2"	12/3 SJO	21/2"	
	131-1	237-1	-	-	16/3 SJO	21/2"	
	633	237-1	1/4" Twin Line		-	31/2"	
	131-3	237-1	3/8"	21/32"	10/3 SO	21/2"	
	131-4	398-1	1/2"	3/4"	-	21/2"	
	254	-	1/2"	3/4"	-	31/2"	
	430	398-1	3/4"	1"	-	31/2"	
	20214	-	1"	19/16"	-	5"	
	20215	-	11/4"	13/16"	-	5"	
	20216	-	11/2"	2 ¹ /16"	-	5"	
	00047		0"	0940"		E11	

BEND RESTRICTORS	ADD SUFFIX	I.D.	DESCRIPTION	PSI
	-BXB	1/4"	Black PVC Bend Restrictor	300
	-ВХВ	3/8"	Black PVC Bend Restrictor	300
	-вхв	1/2"	Black PVC Bend Restrictor	300

Designed to limit the degree of bending without compromising the integrity of the hose assembly while also preventing the hose-end from kinking, excessive wearing, & tearing.

QUICK Disconnects	PART NO.	I.D.	DESCRIPTION	CONNECTION	PSI
	10759-1	1/4"	Quick" Disconnect	NPT (F)	300
The same of the sa	10759-2	3/8"	Quick Disconnect	NPT (F)	300

Quick disconnect couplings thread onto end of hose fitting to provide fast, leak-proof connections for low pressure hose lines. Conveniently connect, interchange, & secure pneumatic tools or other spraying devices to any air, water, chemical or other hose lines.



WARNING: Cancer and reproductive Harm - See page 63 for more information – www.P65Warning.ca.gov

