



### **ELECTRICAL**

Technology:	LED
Watts:	16W
Volts:	120V-277V
Lumens:	1850L/2000L/1950L
CRI:	80+
CCT (Kelvins):	30K/40K/65K - Soft White to Daylight
Beam Spread :	180
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	32W
Operating Temperature :	-20C (-4F) to +45C (+113F)
THD:	25%
Light Source:	LED
Voltage Type:	Range Voltage
Warranty:	5 Year Limited - 10 hr per day

### **PACKAGING**

Each UPC:	045923165115
Each Quantity:	1
Each Dimensions:	12.01 x 1.38 x 12.01

# Project/Job Name:

Location:

Fixture Type:

Notes:

**\$16511** - LED Circline; 16 Watt; T9; 3000K/4000K/6500K CCT Selectable; G10q Base; 120-277 Volt

### • CCT Selectable







#### **PHYSICAL**

Base:	G10q (4-Pin)
Shape:	Т9
Finish:	Frost
Dimensions (In.):	MOL: 1.2 - MOD: 1.2
Weight (Lbs.):	0.57
Material:	Polycarbonate (PC)
Housing Color:	Frost

# **COMPLIANCE**

Safety Listing:	cETLus - Classified
Location Rating:	Damp
Indoor/Outoor:	Indoor
Energy Star Qualified:	No
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

### **INFO**

Specification Note:	Only compatible with Electronic ballasts when installed in Type A mode. See ballast compatibility list
	for details. Not for use on magnetic ballasts.; Inner Diameter: 9.45 in.
Installation Note:	Not for use in vapor tight fixtures.
Min Compartment Size:	Length 14.1 in. Width 14.1 in. Height: 3.5 in.