Sentinel HDig

Dehumidifier

Specifications

Features	Sentinel HDi90
cETL	✓
Compressor Type	Rotary
More Thorough, and More Quick	≠
Ducting options	✓
Condensate Pump	✓
Auto Defrosting	✓
Energy Star	✓
Easy handling	✓
Water full protection	✓
Environmental R410A Refrigerant	✓
Automatic humidistat control	✓
Memory Starting	✓
Rare earth alloy Tube Evaporator	✓
Continuous Model	✓
HVAC Remote System	✓
Optional Remote Controller	✓
Low Temperature	✓
Bypass Air sensor	✓

Specifications	Sentinel HDi90
Power	115V/60Hz
Current	5.56A
COP	2.69L/kWh
Size For	Up to 2,600 sq.ft.
Filter	Pre Filter and MERV-1 Filter
Air flow	210 CFM, 350 CMH
Sound Pressure Level	<58 dBA
Feet	Adjustable Feet
Refrigerant	R410A
Draining	Condensate Pump
Defrosting Control System	Auto Defrosting
Functioning Temperature Range	33.8~104°F
Functioning Humidity Range	36-90%
Capacity	90 Pints
DOE (60°F, 60% RH)	47.71 PPD
Weight	70.5 lbs (32kg)
Dim (L X W X H)	23.2 x15.2 x 17.7 in
Loading quantity	20": 144 Sets;40":292 Sets; 40"HQ:365 Sets

Application

The Sentinel HDi90(Duct-able Version) Dehumidifier has cETL and ENERGY STAR approved. Energy Star Certified Dehumidifier-quickly and effectively removes

moisture with less energy than conventional dehumidifiers without racking up your energy bill, saving you money.

The Sentinel HDi90(Duct-able Version) dehumidifier is designed specifically for crawl spaces and basements. Low noise level, great COP 2.69L/kWh(115v/60Hz) and huge capacity 90 PPD at AHAM condition. The Sentinel HDi90(Duct-able Version) supplements the air conditioning system in the summer time and maintains humidity levels balanced of the year.

Installation flexibility makes the unit ideal for almost any application. No conventional dehumidifier can perform as efficiently and effectively in basements and crawl spaces as

Sentinel HDi90(Duct-able Version), It is the best choice for residential work and restoration

jobs, and suitable for household. shops, storage areas, industrial institusions and garage applications etc... The remote control design makes this unit an ideal choice for places where remote sensing and controlling is required. Optional duct mounting flanges reduce the installation time when connecting to an existing/new ducting systems.

Key Design Features

- Supper COP
- 2.69 L/Kwh(115v/60Hz)
- Rugged Condensate Pump(Developed only for Dehumidifier)
- Coated Coils with Stainless Side Plate
- Quick Access to Pump and Main Board
- Smallest Size
- HVAC Remote System



Optional Outlet Duct 5.9"





Wrinkle free tube

Additional Features

- Engineered for low temperature operation and the air flow issues that crawl spaces present
- Ducting options for divided spaces
- Remote Control equiped
- Heavy-Duty Condensate Pump
- Quick connector to Pump (the pump can be taken out freely just full out the quick connector)



Pump





MERV-1 Filter

Clean Air Filter

EFFICIENET · LARGE CAPACITY · POWERFUL INDUSTRY • RESIDENTIAL HOMES • STORES • RESTORATION

Sentinel HDi90 Dehumidifier (Duct-able Version)

Applications	Sentinel HDi90
Crawlspace	*
Shops/Bars	✓
Museums/Sports Halls	✓
Water Damage Restoration	✓
Computer Rooms	✓
Basements	★


Applications	Sentinel HDi90
Hotel/Motel	4
Offices	✓
Laboratories	✓
Museums	✓
Storage Areas	✓
Restaurants	✓

Installation of a Sentinel Hdi90 with a Supply Kit Only



- 1.Passive Return Vent
- 2.Remote Control(mounts on opposite Wall in Finished Area, Energize the senser on Remote Control)
- 3.Supply Grill
- 4.Supply/Discharge Duct Work
- Place the **Sentinel Hdi90 Duct able Version** in unfinished area of the basement near a drain access (condensate will be drained out via Pump).
- Connecting the Duct Tube on Collar, supply the dry air from the dehumidifier to a large and open area in finished section of the basement.
- Place a return grill / passive vent on the other side of the wall that separates the finished and unfinished areas. This will allow circular air flow go through the basement.
- The passive grill will prevent the unfinished room from being placed under a negative pressure and also allow the dehumidifier to focus on keeping the unfinished area dry as well.
- The Remote Control can be used For normal Retome function, to insulate the Noise of Unit, and Also can be used at the Senser Switch, you can choose the humidity senser between Unit and remote Control.
- Be sure to keep all doors open in the basement to help with proper air circulation(Bedrooms, Bathrooms, etc.)

Installation of a Sentinel Hdi90 with a Supply and Return Kit



- 1 Return Grill
- 2.Remote Control(mounts on opposite Wall in Finished Area, Energize the senser on Remote Control)
- 3. Optional Wall Mount Dehumidistat (mounts on opposite wall in finished area)
- 4.Supply Grill
- 5.Supply/Discharge Duct Work
- 6.Return/Intake Duct Work
- •Place the **Sentinel HDi90** (**Duct-able Version**) in unfinished area of the basement near a drain access (condensate will be drained out via Pump).
- •Connecting the Duct Tube on Collar, supply the dry air from the dehumidifier to a large and open area in finished section of the basement.
- •Place a return grill 1 passive vent on the other side of the wall that separates the finished and unfinished areas. This will allow circular air flow go through the basement
- •The passive grill will prevent the unfinished room from being placed under a negative pressure and also allow the dehumidifier to focus on keeping the unfinished area dry as well.
- •The Remote Control can be used For normal Retome function,to insulate the Noise of Unit, and Also can be used at the Senser Switch,you can choose the humidity senser between Unit and remote Control.

Be sure to keep all doors open in the basement to help with proper air.circulation(Bedrooms, Bathrooms, etc.)

PROVEN PERFORMANCE

The are effective solutions to environmental control problems. The Sentinel HDi90 (Duct-able Version) has CE and CETL Approved. With patent for invention protected, the item is in the top range list of energy efficient products. As the unique design compared with others,we have the humidity senser in bypass air design which make the short-cycling go away and have quick access to pump and main board. Customers can do it by themselves and service become easy. Preassembly makes the installation process simple, thereby it reduces the overall installation and project cost.

This Unit is equipped with a **Auto defrosting system**, which ensures a quick and efficient clearing of ice from the coil under a minimum operating temperature of 2°C. Sentinel HDi90 (Duct-able Version) removes maximum 90 pints of water per day (AHAM) while draws only 5.56 amps, Sentinel HDi90 (Duct-able Version) is one of the smallest, lightest and most powerful dehumidifiers on the market. Sentinel HDi90 (Duct-able Version) is leading the industry by introducing rare earth alloy tube evaporator. This new feature will extend the life of the coils , provide protection in corrosive environments and maintain the coil's heat transfer ability over the life of the coil. The additional features of the **Condensate Pump** make **Sentinel HDi90** (**Duct-able Version**) the ideal choice for unmanned installation.

