20:1 PRO





- Digital Time Display lets you know when the coffee will be done.
- Ready Light lets you know that you're ready to brew.
- Brewer Audible Signal alerts user when coffee is ready.
- Brewing Light flashes to indicate that brewing is in process.
- Auto-Arm, our temperature sentry: will only allow brewing to happen at the correct temperature.
- Power Bar signals that brewer is "On".
- Hot Water Faucet can deliver water at any time.
- Dual Voltage optional.
- Under 18"
- Brews into 2.2 liter glass airpots.

Optional Drop Down Tray





20:1 PRO

Set-up on the 20:1 Brewing system is easy. Simply plug in the water supply, plug in the system's built in cord, and turn the machine on. The 20:1 system will sense a dry probe and begin filling the tank automatically. Once the water in the tank has reached the proper level, the tank heater will automatically turn on and begin heating. In minutes, the correct brewing temperature will be reached, and you're ready to brew!










Standard Brew Basket


Optional Gourmet Funnel

Optional Drop Down Tray

Optional Dual Voltage

Dimensions





Additional Information

		US Watts/Amps		Canadian Watts/Amps	
Part Number	Description	120 V	240 V (option)	120 V (option)	240 V (option)

Part Number	Description	120 V	240 V (option)	120 V (option)	240 V (option)
119725	20:1-AP, PRO-COF, PFB, 1750	1750/14.6	3500/14.6	1400/11.7	3500/14.6
119695	20:1-AP,PRO-COF, PFB, DV	1750/14.6	3150/13.1	1400/11.7	3150/13.1

Note: Unless specified, dual voltage units are shipped configured for connection to a 120 V electrical supply in the US market.

DV* = Dual Voltage



