

Data Sheet

XC II 300 Pro

BIZERBA

Modern PC technology in a compact design is what the X-Class II Pro series stands for. This multifunctional device allows convenient, intuitive and fast operation via touchscreen. Enjoy more performance due to a large RAM. All models are provided with a powerful Intel® Quad Core processor. Ideally suitable for new features or individual requirements.



More information
High performance
with a wide range of
solutions and options.

| Specifications | Facts | Details |
|------------------------------------|--|--|
| Color | Anthracite gray | RAL 7016 |
| Operator display | 10.1" touch TFT | Resolution: 1,024 x 600 (WSVGA) LED backlit Resistive 5-wire touch technology Infinitely inclinable: adjustable viewing angle |
| | 15.6" touch TFT | Resolution: 1,366 x 768 (HD/WXGA) LED backlit Resistive 5-wire touch technology Infinitely inclinable: adjustable viewing angle |
| Customer display | No customer display | |
| | 7" TFT | Resolution: 800 x 480 LED backlit |
| | 10.1" TFT | Resolution: 1,024 x 600 (WSVGA) LED backlit |
| Operating system | Windows 10 IoT Enterprise 2016 LTSB | 64 bit Windows |
| | BizLPOS3 OpenSuse® ≥ 42.1 Leap Kernel 4.2 | 64 bit Linux |
| Application software | RetailPowerScale | Bizerba scale software, compatible with Retail-Framework products |
| | RetailIntegratorsKit (RIK) | 3rd-party software |
| Processor | Intel® Celeron® Processor N3160 Quad Core | Clock rate of up to 2.24 GHz |
| | | L2 cache: 2 MB |
| | | Instruction set: 64 bit Integrated graphics card: Intel® HD Graphics 400 |
| Working memory | DDR3 | 4 GB RAM |
| Mass memory | SSD | 60 GB, optionally 120 GB |
| Printer | 3" label printer | print speed up to 150 mm/s, depending on the paper used |
| | 3" receipt / linerless printer | Up to 3"/76 mm paper width, 200 dpi *Not recommended for industrial labeling |
| External additional printer | Usage of the Bizerba power supply unit | KF 3" receipt / linerless printer |
| | RSP 28 allows to use the following printers of the K-Flex series as external additional printer. | KF 3" label printer |
| | | KF 2" L Compact receipt / linerless printer |

| | | |
|-----------------------------|--|---|
| Interfaces | 2 x USB 3.0 | Super speed |
| | 2 x USB 2.0 | High speed |
| | 2 x COM | DSUB, RS232 |
| | LAN | RJ45, GBit LAN |
| | Audio output | 3.5 mm jack |
| | Cash register drawer connection (COM) | RJ12 |
| Weighing ranges | Connection of external load receptors | Weighing ranges up to 15/30 lb |
| Temperature range | -10 °C to +40 °C | |
| Power consumption | In stand-by 2.4 W | Energy saving thanks to use of Wake on LAN |
| | During operation typically 20 W | |
| Net weight of device | XC II 300 Pro (10.1"/no customer display) | Approx. 10.5 kg |
| Software extensions | RetailApps | Extra software function per RetailApps |
| | Software modules: Cash register, scanning, e-cash, inventory, shrink re-weigh, returns, delivery note, return delivery, cash invoice, order, sum QR barcode, Content Flash, proof of origin, time registration, video journal, RetailConnect | Extra software functions per module |
| WLAN modules | BWLC | Bizerba Wireless LAN Client |
| | | 802.11 a/b/g max. 54 MBit/s |
| | USB | USB WLAN stick, no floating sales mode possible |
| | | 802.11 a/b/g/n max. 300 MBit/s |

Info graphics



Symbols



Java
Powered



Linux
64 bit



Windows 10



T +49 7433 12-0
fax: +49 7433 12-2696
marketing@bizerba.com

www.bizerba.com

Tel. Office +1 732 565-6000
Tel. Service +1 732 565-6001
Fax +1 732 819-0429
us.info@bizerba.com