

## Internet Office 120V 550VA 300W Standby UPS, Ultra-Compact Desktop, USB

MODEL NUMBER: **INTERNET550U**



### Description

Tripp Lite's INTERNET550U standby UPS offers complete protection for PCs, workstations and other sensitive electronics in an attractive ultra-compact, mountable housing. Prevents data loss and system downtime by providing battery supported AC output during brownouts and blackout conditions. 8 output receptacles, two of which are widely-spaced to accommodate large transformer plugs without blocking outlets. 4 outlets with full battery support and surge suppression protect computers, monitors and other vital system components from loss of power. 4 additional outlets with surge suppression-only are ideal for printers and other accessories not requiring battery support. Single line telephone suppression jacks protect modem, fax machine, cordless phone or other peripherals with a standard dialup or DSL phone line connection. USB with PowerAlert monitoring software (available via web download) and cabling enables safe unattended system shutdown in the case of extended power failure. HID-compliant USB enables integration with built-in power management and auto-shutdown features of Windows and Mac OS X. Audible alarm and front panel LEDs offer status information regarding line and battery power operation. 550VA/300 watt power handling ability supports an entry level PC with small monitor consuming 100 watts for up to 10 minutes during power failures. \$100,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

### Features

- INTERNET550U standby UPS offers complete protection from blackouts, brownouts and surges on both AC and Tel/DSL line connections
- 8 outlets, two of which are widely spaced to accommodate large transformer plugs without blocking outlets
- 4 battery supported outlets protect computer, monitor and vital system peripherals, plus 4 additional surge suppression-only outlets for printers and other system accessories not requiring battery support
- Provides battery derived AC output during blackouts and brownouts

### Highlights

- 550VA ultra-compact 120V standby UPS
- Maintains AC output during power failures
- 4 UPS battery supported outlets, 4 surge-only outlets
- USB, TEL/DSL protection, Wall mountable, 99% efficient
- NEMA 5-15P input plug and 8 NEMA 5-15R outlets
- **This product is ENERGY STAR qualified for its ability to save customers money while helping to protect the environment**

### Package Includes

- INTERNET550U UPS System
- USB cable
- Instruction manual



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

- 550VA/300 watt power handling ability supports a variety of PCs, workstations and other sensitive electronics
- Supports an entry level PC with small monitor consuming 100 watts for up to 10 minutes during power failures
- Single line Tel/DSL line surge suppression protects modem, fax machine or cordless phone
- Built-in USB port enables data-saving unattended shutdown when used with Tripp Lite's PowerAlert software, available via FREE download from [www.tripplite.com/poweralert](http://www.tripplite.com/poweralert)
- HID-compliant USB interface enables integration with built-in power management and auto-shutdown features of Windows and Mac OS X.
- Supports Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application/OS or hard power off/on reboot of connected equipment - ideal for unattended kiosk applications
- Space saving, ultra-compact housing fits almost anywhere
- Optional PDUB15 bypass PDU enables hot-swappable UPS replacement with no disruption to connected equipment
- Keyhole mounting flanges enable secure wallmount installation

## Specifications

| OVERVIEW                                        |                                     |
|-------------------------------------------------|-------------------------------------|
| UPC Code                                        | 037332123459                        |
| OUTPUT                                          |                                     |
| Output Volt Amp Capacity (VA)                   | 550                                 |
| Output Watt Capacity (Watts)                    | 300                                 |
| Nominal Output Voltage(s) Supported             | 110V; 115V; 120V                    |
| Nominal Voltage Details                         | 115v nominal output in battery mode |
| Frequency Compatibility                         | 60 Hz                               |
| Output Voltage Regulation (Battery Mode)        | +/- 5%                              |
| Output Receptacles                              | (8) 5-15R                           |
| UPS Output Receptacles (Surge Suppression Only) | 4 UPS outlets, 4 surge-only outlets |
| Hot-Swap PDU options                            | PDUB15 (2U / 8 5-15R outlets)       |
| Output AC Waveform (AC Mode)                    | Sine wave                           |
| Output AC Waveform (Battery Mode)               | PWM sine wave                       |
| Individually Controllable Load Banks            | No                                  |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

| INPUT                                                         |                                                                         |
|---------------------------------------------------------------|-------------------------------------------------------------------------|
| Rated input current (Maximum Load)                            | 10A                                                                     |
| Nominal Input Voltage(s) Supported                            | 120V AC                                                                 |
| UPS Input Connection Type                                     | 5-15P; Right-Angled                                                     |
| Input Circuit Breakers                                        | 10A                                                                     |
| UPS Input Cord Length (ft.)                                   | 6                                                                       |
| UPS Input Cord Length (m)                                     | 1.8                                                                     |
| Recommended Electrical Service                                | 15A 120V                                                                |
| Input Phase                                                   | Single-Phase                                                            |
| BATTERY                                                       |                                                                         |
| Half Load Runtime (min.)                                      | 5.6 minutes (150w)                                                      |
| DC System Voltage (VDC)                                       | 12                                                                      |
| Expandable Runtime                                            | No                                                                      |
| USER INTERFACE, ALERTS & CONTROLS                             |                                                                         |
| Switches                                                      | Combination switch controls on/off power status and self-test operation |
| Audible Alarm                                                 | Audible alarm indicates power-failure and overload status               |
| LED Indicators                                                | 2 LEDs indicate power status and overload/check battery status          |
| SURGE / NOISE SUPPRESSION                                     |                                                                         |
| UPS AC Suppression Joule Rating                               | 420                                                                     |
| UPS AC Suppression Response Time                              | Instantaneous                                                           |
| UPS Dataline Suppression                                      | 1 line TEL/DSL (1 in / 1 out)                                           |
| EMI / RFI AC Noise Suppression                                | Yes                                                                     |
| PHYSICAL                                                      |                                                                         |
| Installation Form Factors Supported with Included Accessories | Tower; Ultra-compact desktop; Wallmount                                 |
| Primary Form Factor                                           | Desktop                                                                 |
| UPS Power Module Dimensions (hwd, in.)                        | 3.1 x 5.7 x 10.8                                                        |
| UPS Power Module Dimensions (hwd, cm)                         | 7.87 x 14.48 x 27.43                                                    |
| UPS Power Module Weight (lbs.)                                | 5                                                                       |
| UPS Power Module Weight (kg)                                  | 2.27                                                                    |
| Shipping Dimensions (hwd / in.)                               | 4.10 x 8.00 x 13.00                                                     |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|                                                             |                                                                                                                                                                                                                                           |
|-------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Shipping Dimensions (hwd / cm)                              | 10.41 x 20.32 x 33.02                                                                                                                                                                                                                     |
| Shipping Weight (lbs.)                                      | 5.50                                                                                                                                                                                                                                      |
| Shipping Weight (kg)                                        | 2.49                                                                                                                                                                                                                                      |
| UPS Housing Material                                        | ABS                                                                                                                                                                                                                                       |
| Primary UPS Height (mm)                                     | 79                                                                                                                                                                                                                                        |
| Primary UPS Width (mm)                                      | 145                                                                                                                                                                                                                                       |
| Primary UPS Depth (mm)                                      | 274                                                                                                                                                                                                                                       |
| <b>ENVIRONMENTAL</b>                                        |                                                                                                                                                                                                                                           |
| Operating Temperature Range                                 | +32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius                                                                                                                                                                                 |
| Storage Temperature Range                                   | +5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius                                                                                                                                                                                |
| Relative Humidity                                           | 0 to 95%, non-condensing                                                                                                                                                                                                                  |
| AC Mode BTU / Hr. (Full Load)                               | 14                                                                                                                                                                                                                                        |
| AC Mode Efficiency Rating (100% Load)                       | 99%                                                                                                                                                                                                                                       |
| <b>COMMUNICATIONS</b>                                       |                                                                                                                                                                                                                                           |
| Communications Interface                                    | USB (HID enabled)                                                                                                                                                                                                                         |
| PowerAlert Software                                         | For local monitoring via the UPS's built-in USB port, download PowerAlert Local software at <a href="http://www.tripplite.com/poweralert">http://www.tripplite.com/poweralert</a>                                                         |
| Communications Cable                                        | RJ to USB interface cable included                                                                                                                                                                                                        |
| WatchDog Compatibility                                      | Supports Watchdog application, OS and hard-reboot restart options for remote applications                                                                                                                                                 |
| Network UPS Tools Compatibility                             | NUT compatible. See the full list of Tripp Lite NUT compatible UPS systems at <a href="http://www.networkupstools.org/stable-hcl.html?manufacturer=Tripp+Lite">http://www.networkupstools.org/stable-hcl.html?manufacturer=Tripp Lite</a> |
| <b>LINE / BATTERY TRANSFER</b>                              |                                                                                                                                                                                                                                           |
| Transfer Time                                               | 4 milliseconds (AC to battery mode) / 2 milliseconds (battery mode to AC)                                                                                                                                                                 |
| Low Voltage Transfer to Battery Power (Setpoint)            | 99                                                                                                                                                                                                                                        |
| High Voltage Transfer to Battery Power (Setpoint)           | 139                                                                                                                                                                                                                                       |
| <b>SPECIAL FEATURES</b>                                     |                                                                                                                                                                                                                                           |
| Cold Start (Startup in Battery Mode During a Power Failure) | Cold-start operation supported                                                                                                                                                                                                            |
| Green Energy-Saving Features                                | Greater than 95% efficiency - GREEN UPS                                                                                                                                                                                                   |
| <b>CERTIFICATIONS</b>                                       |                                                                                                                                                                                                                                           |
| UPS Certifications                                          | Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico); Meets FCC Part 15 Category B (EMI); ENERGY STAR Qualified                                                                                                         |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

| WARRANTY                                                   |                                                                                                                        |
|------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Product Warranty Period (U.S. & Canada)                    | 3-year limited warranty                                                                                                |
| Product Warranty Period (Latin America)                    | 3-year limited warranty                                                                                                |
| Product Warranty Period (International)                    | 2-year limited warranty                                                                                                |
| Product Warranty Period (Mexico)                           | 3-year limited warranty                                                                                                |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$100,000 <a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a> |

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>