APPLICATION:	
JOB NAME:	
QUANTITY:	ITEM NO.:

12" STAINLESS STEEL BRAIDED SUPPLY LINES & MOUNTING KIT	
38" [965.2mm]	<b>A</b>
1/2"F NPT INLETS	
"B"   12"   [304.8mm]   12"   [304.8mm]   12"   [304.8mm]	1]
"A" [177.8mm] 2" [50.8mm]	
FOOTPRINT: 1-3/4" [42.9mm] 2-5/8" [65.5mm]	

ROUGH-IN	MODEL	DIM "A"	DIM "B"	DIM "C"
	34169	8-3/4" [221.3mm]	12-3/8" [313.3mm]	6" [152.4mm]
1-1/4"	34177	9" [227.6mm]	12-7/8" [326.0mm]	8" [203.2mm]
\[31.8mm]	34185	9-5/8" [243.5mm]	13-3/8"' [340.3mm]	10" [254.0mm]
	34193	10-1/4" [259.4mm]	13-7/8" [351.4mm]	12" [304.8mm]
Ψ	34207	10-7/8" [275.2mm]	14-3/4" [373.7mm]	14" [355.6mm]
	34215	11-5/8" [294.3mm]	15-3/8" [389.5mm]	16" [406.4mm]

### PRODUCT NAME:

# PRE-RINSE SPRG SINGLE DECK DUAL CTL WITH WALL BRACKET & ADD-ON FAUCET

		SPECIAL CONFIGURATION		
	MODEL:			
	□ 34169	WITH 6" SWING SPOUT		
	□ 34177	WITH 8" SWING SPOUT		
	□ 34185	WITH 10" SWING SPOUT		
	□ 34193	WITH 12" SWING SPOUT		
	□ 34207	WITH 14" SWING SPOUT		
	□ 34215	WITH 16" SWING SPOUT		

## **OPTIONS OR MODIFICATIONS:**

- □ SUPPLY LINES (24" OR 36") CIRCLE LENGTH
- □ BACKFLOW PREVENTER
- □ BRUSH
- □ VANDAL RESISTANT KIT
- ☐ HANDLES (CROSS OR WRIST) CIRCLE STYLE
- □ OTHER \_

#### **FEATURES:**

#### MAIN CONTROL VALVE

- \* SINGLE DECK, DUAL CONTROL
- \* INTERNAL SPRING LOADED CHECK VALVES
- \* SWIVELING SEAT DISKS
- \* HOT SIDE STEM RIGHT HAND CHECK
- \* COLD SIDE STEM LEFT HAND CHECK
- \* STAINLESS STEEL SEATS, SEAT SCREWS AND HANDLE SCREWS

## ADD-ON CONTROL VALVE

- \* STEM RIGHT HAND SWIVEL
- \* HOT INDEX BUTTON
- \* SWIVELING SEAT DISKS
- \* STAINLESS STEEL SEATS, SEAT SCREWS AND HANDLE SCREWS.

## HOSE

- \* 36" LENGTH
- \* STAINLESS STEEL END FITTINGS
- \* STAINLESS STEEL EXTERNAL JACKET
- \* 3-PLY FIBER REINFORCED INTERNAL RUBBER HOSE
- \* REPAIRABLE IN FIELD WITH SIMPLE TOOLS

## **ULTRA SPRAY VALVE**

- \* LOWEST ENERGY USER 1.15 GPM @ 60 PSI
- \* CLEANS FASTER TEST PROVEN
- \* ENGINEERED TO LAST NO 'O' RINGS TO LEAK
- \* INTERCHANGEABLE FITS ALL BRANDS

## WALL BRACKET

\* ADJUSTS FROM 2" TO 12"

### SYSTEM LIMITS

- \* TEMP: 40 F MIN. TO 140 F MAX. STATIC
- \* PRESSURE 200 PSI MAX. STATIC
- \* SHIPPING WEIGHT: 15.0 LBS



TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com