
APPLICATION:		PRODUCT NAME:		
		SWIVEL GOOSENECK SPOUT ASSEMBLY		
JOB NAME:			SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS	
QUANTITY:	ITEM NO.	MODEL:		
·		□ 3965	12" SWIVEL GOOSENECK SPOUT	

SHIPPING WEIGHT * 0.75 LBS



		2.2 GPM AERATOR
"C"		
		— "A" ————
		"B"
		<u> </u>

MODEL	DIM "A"	DIM "B"	DIM "C"
3965	5-1/2" [140mm]	7-3/8" [187mm]	12" [304mm]
2060	3-1/2"	3-3/8"	7"

PRODUCT NAME:					
SWIVEL GOOSENECK SPOUT ASSEMBLY					
	SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS		3965 REV		
MODEL:					
□ 3965	12" SWIVEL GOOSENECK SPOUT				
□ 3968	6" SWIVEL GOOSENECK SPOUT				
OPTIONS OR MODIFICATIONS:					
☐ OTHER _					
FEATURES					
* 2.2 GPM AERATOR					
SYSTEM LIMITS					
* TEMP: 40°F MIN. TO 140°F MAX. * PRESSURE: 200 PSI MAX. STATIC					
PKESSUR	KE: 200 PSI MAX. STATIC				

3968 [89mm] [86mm] [180mm]



TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com-www.fisher-mfg.com