

Model RR5-48.5LT (dump left shown)

The Marshall **Models RR5-48.5 and RR5-42** Fry Dump Stations feature our ThermoGlo™ heating technology. Heat radiates from every square inch of the upper flat plate heating surface. This eliminates the need to clean intricate cal-rod, wire and reflector assemblies. There is also auxiliary bottom heat. This dump station includes four organizers and a fry dump pan with a bagged fry holder.

All Marshall products are supported by a nationwide service organization and in-house, full-time Customer Support Department. To place an order call:

1-800-627-8368

Marshall's Fry Dump Station incorporates ThermoGlo<sup>TM</sup> technology designed to solve demanding warming and holding temperature requirements.

### **FEATURES**


- Flat surface allows for easy wipe-clean maintenance
- Food stays "presentation ready" longer because exact internal temperatures can be reached faster and maintained longer
- Illumination provided by four food-grade incandescent bulbs
- Can be oriented for either dump-left or dumpright
- Includes Marshall's ten-channel timer, which is field convertible for dump-left or dumpright


### CONSTRUCTION

- Heavy gauge stainless steel
- Designed and built to custom specifications with heat radiating from the ThermoGlo<sup>TM</sup> surface
- Designed with a flat unbreakable radiating metal face encased in stainless steel housing

# ETL (US, Canada) & NSF Listed FOR COMMERCIAL USE ONLY

\*Ask about Marshall's companion High Speed Toasters, Conveyor Broilers and Ventilation Systems.





## Overall Dimensions Models RR5-48.5 and RR5-42

<u>Dimensions:</u> RR5-48.5LT* RR5-48.5RT* RR5-42LT* RR5-42RT*	Height: 59" (1499 mm) 59" (1499 mm) 59" (1499 mm) 59" (1499 mm)	Width: 48.625" (1235 mm) 48.625" (1235 mm) 42.000" (1067 mm) 42.000" (1067 mm)	32.750 32.750	: 0" (832 mm) 0" (832 mm) 0" (832 mm) 0" (832 mm)	
Shipping Information:	Weight:	Ship Wt.:	NMFC Freight (USA):	Ship. Cubes:	
RR5-48.5 RR5-42	400 lbs. (182 kilos) 350 lbs. (159 kilos)	475 lbs. (216 kilos) 425 lbs. (195 kilos)	Class 125 Class 125	84.5 cubic ft. (2.4 cubic meters) 74.4 cubic ft. (2.2 cubic meters)	
Electrical: RR5-48.5 RR5-42	208V, 50/60Hz, 1Ph 14.75 amps/3.1 kW (includes 2 amps maximum for timer) 3 wire grounded type plug, NEMA 6-20 7 ft. cord 208V, 50/60Hz, 1Ph 13 amps/2.7 kW (includes 2 amps maximum for timer) 3 wire grounded type plug, NEMA 6-20 7 ft. cord				
Inserts: RR5-42	Dump Pan: 21" Wide	Bag Holder: 1 Row – 3.625" Wide	1 - 4.	Organizers: 1 - 4.000" Wide 3 - 3.500" Wide	
RR5-48.5	22" Wide	2 Rows – 6.875" Wide	1 - 5.0	1 – 5.000" Wide 3 – 4.000" Wide	

<sup>\*</sup>LT = dump to left as shown / RT = dump to right (opposite of shown)

### Marshall Air Systems, Inc.

419 Peachtree Drive South • Charlotte, North Carolina 28217 USA • Phone: (704) 525-6230 Fax: (704) 525-6229 • www.marshallair.com