



DUAL-TEMPERATURE WINE DISPENSER

PRO-LINE™ WINE E-SERIES™ 25" - 4 KEG / 2 FAUCET

- Designed by wine-industry experts for performance and value
- Two dedicated temperature zones for optimal wine dispensing
- Finesse wine font with 2 faucets
- Commercial grade construction - built to last



MDD23W-E-A

Black



Dual-Temperature: Built In Digital Thermostats



Listed by Edison Testing Laboratories.
Conforms to UL & NSF Standards.



Wine Certified

Tap handles not included
Tapping hardware not included

www.micromatic.com • 1 (866) 327-4159

PRO-LINE™ WINE E-SERIES™ 25" - 4 KEG

Job Number: _____ Location: _____

Part No.	Finish	Faucets	Doors	Shipping Weight
 MDD23W-E-A	Black	2	1	78 kg
				172 lbs

Operating Performance

Capacity of 20 Liter Kegs	4 (2 per zone)	Condenser HP	1/6
Color-coded Digital Thermostats	2 (Blue LED-Whites & Red LED-Reds)	Voltage	115/60/1
Temperature Range - Whites	42-48° F (5.5 - 8.8C)	Plug Type	NEMA-5-15P
Temperature Tange - Reds	55-65° F (12.7 - 18.3C)	Cord Length	8'
Approval	ETL Listed	Refrigerant	R-134a
Running Amps	2.5	Charge oz	5.64
Exterior	18 gauge stainless steel top, 22 gauge solid doors, 24 gauge steel front, sides and back.		
Interior	20 gauge stainless steel floor, reinforced frame, 24 gauge galvanized walls.		
Ventilation	Back ventilated.		
Plumbing	Automatic condensate evaporator, no drain connection required. Evaporator condensate has been plumbed to a condensate pan located in the compressor housing.		
Insulation	Foamed-in-place using high density, CFC-free polyurethane; 1-1/2" top, walls and floor.		
Mobility	Castors are standard and not removable.		

Dimensions

