



DUAL-TEMPERATURE WINE DISPENSER

PRO-LINE™ WINE E-SERIES™ 36" - 4 KEG

- Designed by wine-industry experts for performance and value
- Two dedicated temperature zones for optimal wine dispensing
- Pre-drilled for customer tower choice
- Commercial grade construction - built to last



MDD36SW-E

Stainless Steel



MDD36W-E

Black

Shown: Wine Font MTM-4PSS-W and
Drip Tray DP-1020. Order Separately.



Dual-Temperature: Built In Digital Thermostats



Listed by Edison Testing Laboratories.
Conforms to UL & NSF Standards.



Wine Certified

www.micromatic.com • 1 (866) 327-4159

PRO-LINE™ WINE E-SERIES™ 36" - 4 KEG

Job Number: _____ Location: _____

Part No.	Exterior	Doors	Shipping Weight
☐ MDD36W-E	Black	1	78 kg 172 lb
☐ MDD36SW-E	Stainless Steel	1	78 kg 172 lb

Operating Performance

Capacity of 20 Liter Kegs	4 (2 per zone)	Running Amps	3.6
Cubic Feet (liters)	TBD	Condenser HP	1/6
Hole for Wine Font	1	Voltage	115/60/1
Hole Diameter	3"	Plug Type	NEMA-5-15P
Color-coded Digital Thermostats	2 (Blue LED-Whites & Red LED-Reds)	Cord Length	8'
Temperature Range - Whites	42-48° F (5.5 - 8.8C)	Refrigerant	R-134a
Temperature Tange - Reds	55-65° F (12.7 - 18.3C)	Charge oz	6.35
Approval	ETL Listed, Energy Star		

Exterior	18 gauge stainless steel top, 22 gauge solid doors, 24 gauge steel front, sides and back
Interior	20 gauge stainless steel floor and walls
Ventilation	Front ventilated
Plumbing	Automatic condensate evaporator, no drain connection required. Evaporator condensate has been plumbed to a condensate pan located in the compressor housing
Insulation	Foamed-in-place using high density, CFC-free polyurethane; 2" top, walls and floor
Accessories	Castors or 6" fixed legs

Dimensions

