April 2014

Technical Data

3M[™] Heavy Duty Degreaser Concentrate

Description

The 3M[™] Heavy Duty Degreaser is a powerful degreaser concentrate developed for extremely tough jobs. Ideal for cleaning machinery, engines, factory floors, tools, trucks, and metal parts.

Heavy Duty Degreaser quickly penetrates grease, oil and a variety of soils.

Special Features

- Quickly penetrates oily and greasy soils
- Versatile product can be used in automatic scrubbers, mop buckets, pressure washers, or for manual cleaning
- Economical strong concentration can be diluted with up to 100 parts water

Applications

- Tools, machinery and equipment
- Factory floors
- Auto plants
- Tire and rubber manufacturing
- Garages

Packaging

4 one-gallon bottles per case

General Use Directions

Dilute concentrate based on the soil level.

Soil Level	Dilution
Light	1.25 oz/gal (1:100)
Medium	2.5 oz/gal (1:50)
Heavy	5 oz/gal (1:25)
Very Heavy	26 oz/gal (1:5)

General degreasing

- 1. Apply diluted product with a trigger spray bottle, sponge, mop or brush.
- 2. Allow the degreaser to penetrate the soil.
- 3. Scrub as required to clean the surface.
- 4. Wipe surface dry.

Dip Tank

Use product concentrate or dilute up to 1:15 (8 ounces/gallon)

Auto Scrubber

Dilute 1:40 to 1:60 (2-3 ounces/gallon)

Steam or Pressure Washer

Dilute 1:40 to 1:60 (2-3 ounces/gallon)

Note:

This product should not be used on glass.

S

NOTE:

Refer to product Safety Data Sheet for specific physical properties, health hazard, first aid and precautionary information.

3M™ Heavy Duty Degreaser Concentrate SDS:

22-4251-9



3M Branch Sales Offices

ANCHORAGE

11151 Calaska Circle Anchorage, AK 99515

Telephone: 907/522-5200 Facsimile 907/522-1645

HONOLULU

4443 Malaai Street Honolulu, HI 96818 Mail to: P.O. Box 30048 Honolulu, HI 96820

Telephone: 808/422-2721 Facsimile 808/422-9557

CONTINENTAL UNITED STATES

Customer Service Department 3M Commercial Solutions Division 3M Center Building 224-2S-04 St. Paul, MN 55144-1000

Order Entry 1-800-852-9722 Facsimile 1-800-447-0408 ccd-bst@mmm.com

CANADA

N6A 4T1

1840 Oxford Street East London, Ontario, Canada N5V 3G2 Mail to: P.O. Box 5757 London, Ontario, Canada

Telephone: 800/364-3577 Facsimile: 800/479-4453

Important Notice to User

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application

Warranty and Limited Remedy: 3M warrants that each 3M product will be free from defects in material and manufacture for 90 days from the date of purchase from 3M's authorized distributor. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.

