

Flav-R-Savor® PORTABLE HOLDING CABINET Models FSHC-5W1-EE, -7W1-EE, -7W2-EE

Hatco's NEW energy efficient Flav-R-Savor® Portable Holding Cabinet will keep prepared foods at optimum serving temperatures for hours. The electronic thermostatically controlled heat and humidity allows food to be prepared

FLEXIBILITY

Available with one-door or pass-through. These units come standard with 4" (120 mm) diameter casters, seven sets of adjustable rack slides, and a 1 gallon (3.8-liter) capacity water chamber.

in advance of peak serving periods.

QUALITY

The following features assure the finest performance for years to come:

- Allows you to hold product longer while saving you money through increased energy efficiencies
- Electronic control with digital read out, temperature range of 80° - 200°F (27° - 93°C), and high efficiency humidity control
- Using the lower temperature range of 80°-100°F (27°-38°C), allows for proofing all types of breads
- All stainless steel interior, and no element contact with water makes the unit easier to clean
- Accommodates Gastronorm pans
- Electrical components, controls, and digital temperature readout are located at the top for easy access
- Comes in standard *Designer* Black, or optional stainless steel
- Stacking kit available
- Doors are easily field convertable from left-hand door hinge to right-hand door hinge



FSHC-7W1-EE and FSHC-7W2-EE units only






ONE YEAR ON-SITE PARTS AND LABOR WARRANTY, PLUS ONE ADDITIONAL YEAR PARTS-ONLY WARRANTY ON ALL FLAV-R-SAVOR METAL SHEATHED AIR HEATING FI FMFNTS.




HATCO CORPORATION P.O. Box 340500 Milwaukee, WI 53234-0500 U.S.A. (800) 558-0607 • (414) 671-6350 • Fax (800) 543-7521 • Int'l. Fax: (414) 671-3976 www.hatcocorp.com • E-mail: equipsales@hatcocorp.com



Flav-R-Savor® PORTABLE HOLDING CABINET





FRONT VIEW

FRONT VIEW

SPECIFICATIONS

Model	Description	Watts	Amps	Hz
FSHC-5W1-EE	Single Door	1118	9.3	60
FSHC-7W1-EE	Single Door	1118	9.3	60
FSHC-7W2-EE	Pass-Through	1118	9.3	60

DIMENSIONS

SIDE VIEW

FSHC-xW1-EE:

26.02"W x 31.25"D x 35.96"H w/casters (661 x 794 x 913 mm).

26.02"W x 34.54"D x 38.9"H w/casters (661 x 877 x 988 mm). Water Capacity: 1 gallon (3.8 liters).

VOLTAGE

120V, single phase, 9.3 Amps, 60Hz, NEMA 5-15P

CORD LOCATION

Back of unit, top right side

PLUG CONFIGURATIONS



OPTIONS (Available at time of purchase only)

- ☐ Designer Black (standard) or stainless steel
- Glass Door(s) (in lieu of stainless steel door) (not Energy Star qualified)
- ☐ Low profile casters (FSHC-5W1-EE model only) (deduct 2.3" [57 mm])
- ☐ Platform for mounting directly on a counter (deduct 4.1" [104 mm])
- ☐ Stacking Hardware (*Designer* Black powdercoated or stainless steel)
- ☐ Bumper Hardware (for use with standard casters only) (add .1" [3 mm])
- ☐ 4" legs (in lieu of casters) (deduct .4" [10 mm])
- ☐ 6" legs (in lieu of casters) (add 1.7" [43 mm])

ACCESSORIES

- ☐ Pan slides
- ☐ Food pans

PRODUCT SPECS Portable Holding Cabinet

The humidity and heat-controlled Portable Holding Cabinet shall be a Flav-R-Savor® Model ... , rated at ... volts, and ... watts, as manufactured by the Hatco Corporation, Milwaukee, WI 53234 U.S.A.

The cabinet shall have ... door(s), rack slides, insulated side walls, 4" (102 mm) diameter casters with wheel locks, and a 6' (1829 mm) cord

and plug. It shall include a water reservoir, electronic control with digital read out, temperature and humidity controlled, pan slides.

Accessories shall include extra pan slides, and food pans.

One year on-site parts and labor warranty plus one additional year parts-only warranty on all Flav-R-Savor metal sheathed air heating elements with 24/7 service (U.S. and Canada only).

HATCO CORPORATION P.O. Box 340500 Milwaukee, WI 53234-0500 U.S.A. • (800) 558-0607 • (414) 671-6350 Fax (800) 543-7521 • Int'l. Fax (414) 671-3976 • www.hatcocorp.com • E-mail: equipsales@hatcocorp.com