

RM-7-HC 10/16/19 Item # 13408

WxDxH 21.25" x 25" x 37.75"













Dimensions / Capacity

Dillicitations / Gapacity	RM-7-HC
Interior Storage Capacity (CF)	5.97 ft ³
Overall Width x Depth	21.25" x 25"
Depth with door open	44.88"
Height	37.75"
Adjustable Shelves	2 adjustable, 1 floor shelf
Shelf Dimensions (W x D)	17.75" x 20.75"
Floor Shelf Dimensions (W x D)	18" x 9.25"
Crated Shipping Weight	155 lbs.
Crated Width x Depth x Height	30" x 30" x 42"
Electrical / Refrigeration	One Section RM-7-HC
Voltage	115/60/1
HACR Breaker	15.0 Amps
Electrical Connection (NEMA)	5-15P 🕦
Voltage Range	104-126
Ambient Temp. Range	60° to 86°F
Control Setpoint Range	28° to 40°F
Amperage	3.2
Energy Consumption (kWh/day) @ASHRAE	1.38
Approx. Nominal Compres. BTU/HR (HP)	582 (1/8HP)
Refrigerant	R290

Options

☐ Floor Epoxy Shelf (HS-5344) ☐ Epoxy Shelf (HS-5343)

One Section

5.97 IL
21.25" x 25"
44.88"
37.75"
2 adjustable, 1 floor shelf
17.75" x 20.75"
18" x 9.25"
155 lbs.
30" x 30" x 42"
One Section RM-7-HC
115/60/1
15.0 Amps
5-15P 🕦
104-126
60° to 86°F
28° to 40°F
3.2
1.38
582 (1/8HP)
R290

Warranty

3 Year - parts and Labor on entire machine. 5 Year - Parts on Compressor Valid in United States, Canada, Puerto Rico and U.S. Territories. Contact factory for warranty in other countries.

Item #:	
Project:	
Qty:	
AIA#:	

Features


- Curved vertical corners with silver aluminum exterior provide enhanced product display
- Energy efficient vertical LED interior lights illuminate products on display
- ► Forced-air evaporator for quick temperature pull-down
- Large glass door are energy efficient low E multi pane
- Spring assisted self-closing door with stay open feature
- (3) epoxy coated wire shelves are standard
- Stackable (three units high) to conserve warehouse floor space
- · Refrigerant flow is controlled with a capillary tube
- 2 inch leveling legs standard
- · Three years parts and labor warranty
- · Five year compressor warranty
- 8 ft. cord and plug


Capacity:

20 oz. bottles: 102 12 oz. bottles: 217




FRONT VIEW SIDE VIEW






PLAN VIEW



HEADER DIMS



Graphic Requirements:

- 360 dpi resolution. Scale 1=1
- Colors for CMYK process
- Image with 1/4" of excess by side
- Graphics must be saved in photoshop (with layers)
 (or your sign company file type requirements)
- Include a full color print out

Material Requirements:

• 3M exterior grade UV resistant vinyl adhesive

Note: Texts and important parts of the image should be within the visible area. The visible area is illustrated by dotted lines when it applies.