

WET CHEMICAL STORED PRESSURE FIRE EXTINGUISHER

Wet Chemical Fire Extinguishers contain a blend of Potassium Acetate and Potassium Citrate that is extremely effective in combating fires fueled by the unsaturated cooking oils and greases used in today's commercial cooking appliances. This agent excels at effectively fighting and cooling these very hot and difficult fires.

The misting nozzle delivers the agent in a fine spray that prevents the splashing of the burning grease and confines it to the cooking surface.

The extinguisher is manufactured to ANSI/UL 8 and ANSI/UL 711 Standards.

The extinguisher is designed to work in conjunction With pre-engineered kitchen fire suppression systems. It has been tested to extinguish one 18" x 24" fryer.



**6 LITER
WET CHEMICAL
FIRE EXTINGUISHER**

SPECIFICATIONS	
Model	WC- 6 Liter
Part Number	50006
UL Rating	1A:K
Capacity (gal/Liter)	1.59 / 6
Operating Pressure	100 psi (690 kPa)
Discharge time (Seconds)	54
Temperature Range	+40°F to +120°F
Cylinder Construction	Stainless Steel
Shipping Weight (lbs/kg)	22 / 10
Extinguisher Height (in/cm)	19.25 / 48.9
Height w/ Hose Installed (in/cm)	25.5 / 64.8
Width w/ Hose Installed (in/cm)	11 / 27.9
Cylinder Diameter 9in/cm)	7 / 17.8
Standard Mounting Hardware	Wall Hook