


HDR4845-25









The heavy-duty BulkPak 4845 HDR Series is used extensively by the automotive industry, as it meets the specifications of the Automotive Industry Action Group (AIAG). Unitized loads can be delivered directly to the assembly line for immediate part presentation, with no unwrapping or unbanding. Bulk containers collapse when empty for reduced return transportation costs and warehouse space savings. During storage and shipping these bulk bins stack securely atop each other. Palletized container loads can be stacked with the BulkPak, for greater shipping efficiency. Based on the standard AIAG footprint, these bulk containers are designed and constructed to efficiently move, store and ship components. Pallet boxes offer the strength and rugged durability demanded in today's material handling and distribution systems. Custom protective dunnage is available for all ORBIS BulkPak containers. These plastic containers are fully recyclable at the end of their service life. (All dimensions and specifications are approximate. Performance characteristics are based on uniform static loads and may be affected by the distribution of load, handling methods, number, type of access doors, and temperatures beyond the range of 0 to 120 degrees Fahrenheit.)

- 45 x 48 x 25 footprint
- Structural-foam molded in high-density polyethylene
- Container capacity: 2,000 lbs
- 0 or 2 access doors on 48" side only
- NOTE: 45 doors and/or wing walls are not available on the HDR4845-25 or HDR4845-39
- Base: All-plastic picture frame bottom
- Deck: Vented
- Sidewalls: Solid
- Popular applications: Automotive, appliance, and transportation equipment

| Outside Length In | 48 |
|------------------------------|-------|
| Outside Width In | 45 |
| Outside Height In | 25 |
| Inside Length In | 44.5 |
| Inside Width In | 41.5 |
| Prod Clearance In | 18.4 |
| Collapsed Height In | 13.0 |
| Container Capacity Lb | 2000 |
| Weight Lb | 118.4 |
| Maximum Loaded Stack Static | 6 |
| Maximum Loaded Stack Dynamic | 4 |
| Return Ratio | 1.9:1 |
| Door Openings Long H In | 11.6 |
| Door Openings Long W In | 32.1 |
| Internal Volume Cu Ft | 19.7 |
| 53ft Trailer Qty Assembled | 104 |
| 53ft Trailer Qty Collapsed | 208 |