		T
APPLICATION:		PRODUCT NAME:
		STAINLESS STEEL DOUBLE PEDAL CONTROL VALVE WALL MOUNT
JOB NAME:		SPECIAL CONFIGURATION
	F	☐ CHECK BASE MODEL AND OPTIONS
QUANTITY:	ITEM NO.	MODEL:
14" [355.6mm] 8-7/8" [225.4mm]		□ 48070
		OPTIONS OR MODIFICATIONS:
		☐ SUPPLY LINES (24" OR 36") CIRCLE LENGTH☐ NIPPLES
		□ ELBOWS
		☐ HANDLES (CROSS OR WRIST) CIRCLE STYLE
		☐ VANDAL RESISTANT KIT
		□ OTHER
		FEATURES
		+ DEDA. AMODIZED AMMANA
		* PEDAL ANODIZED ALUMINUM * CYLINDER CLOSES WITH WATER FLOW
		* POLISHED CHROME
ADJUSTABLE BOLT		RECOMMENDED SETTINGS
		* 110°F AT 80 PSI
		SYSTEM LIMITS
		* TEMP: 40°F MIN. TO 140°F MAX.
		* PRESSURE 200 PSI MAX. STATIC
		SHIPPING WEIGHT
		* 4.0 LBS
		* NSF 61-9 APPROVED & LISTED
		www.truesdail.com
	8" 9" (MIN) [203.2mm] [228.6mm]	
5-3/4" [146.1mm]		
7 ^M Y 7 ^M Y		
FLOOR		
ROUGH-IN:		
CLEARANCE ^{_/} HOLE FOR 1/4-20		
FH SCREW 5" [127.0mm]		H/SHER
[127.0mm]		FISHER MANUFACTURING COMPANY
ANSI/A112.18.1M		TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com