

2-Person Hands-Free Wall Mount Stainless Steel Wash Station

| Model | Sensor Type | Flow-Rate |
|-----------|-----------------|------------------|
| 54WAL | AC Powered | Standard 2.0 GPM |
| 54WAL-0.5 | AC Powered | Low-Flow 0.5 GPM |
| 54WBL | Battery Powered | Standard 2.0 GPM |
| 54WBL-0.5 | Battery Powered | Low-Flow 0.5 GPM |

Product Specifications

Constructed from welded #16 gauge type 304 stainless steel. The front, bottom and back are formed from a single sheet with a rolled rim on front and sides. Exposed surfaces have a blended uniform satin finish.

| | |
|-----------------------|-------------------------------------|
| Outside Dimensions | 40" x 20" x 18" High |
| Inside Bowl Size | 37" x 16-1/2" x 8" Deep |
| Back Splash Height | 10" |
| Water Activation | AC or Battery Powered Sensor Faucet |
| Flow Rate | 2 GPM |
| Inlet Connections | 3/8" Male Compression |
| Drain Opening | 2" |
| Finish | Satin |
| Strainer | 1-1/2" Dia. Duo Basket Strainer |
| Wall Mounting Bracket | 1/4" Dia. Mounting Holes |

Includes

- (1) Wall mount wash station
- (2) AC or Battery powered sensor faucet assembly
- (2) Wall-mounting brackets
- (2) Support brackets
- (2) Mixing check valve
- (1) Strainer assembly with basket

Product Compliance

NSF/ANSI 2 Food Equipment

NSF/ANSI 372 Lead-Free Compliant

ASME A112.18.1



WARNING: Equipment that include faucets on this page may contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.



Part: _____ Quantity: _____

Project: _____

Contact: _____

Date: _____

Approval: _____

Notes:




COLUMBIA SPECIFICATIONS


2-Person Hands-Free Wall Mount Stainless Steel Wash Station

Models 54WAL, 54WAL-0.5, 54WBL and 54WBL-0.5


■ Top




■ Front




■ Side



■ Hole Configurations



■ Wall Mounting Detail



SANI-LAV Sensor Faucets

Wall Mounted AC and Battery Powered
Meets ANSI/ASME A112.18.1 M-1989



Operation

1. A continuous, invisible beam is emitted from the sensor.
2. The faucet is activated by placing hands under the spout within the effective range of the beam. Water starts to flow immediately for as long as the user's hands remain in the sensor range.
3. When hands are removed, the water flow stops. The sensor will automatically reset and be ready for the next user.
4. In the battery powered version, a flashing red light will indicate a low battery condition.

Specifications

Faucet Construction

Solid brass, chrome plated
Solid state, AC or battery, switchable
Preset at 20 seconds and adjustable to 10, 30, or 60 seconds
2 minute run every 12 hours or 24 hours
60, 120, 180 seconds
Preset and adjustable
Presets and adjustable from 1-8 seconds
Armored, vandal resistant
6V DC, normally closed

Control Circuit

- Auto. Time-out
- Line Purge (request only)
- Scrub Mode Delay (request only)
- Sensor Range
- Shut-off Delay

2.0 or 0.5 GPM, Laminar Flow Control

Control Cable

Solenoid Valve

- Wattage: 0.4W (idle), 5W (in use)
- Operating Pressure: 5 psi to 125 psi

2.0 or 0.5 GPM, Laminar Flow Control

Flow Control

AC Mode

Power Adapter

- Standard Plug-in
- (UL/CSA)
- Power Cable
- Optional Multi-Unit Adapter
- (UL/CSA)

Input AC 120V 60 Hz or 220V
Output DC 12V, 0.8A/Class 2
Armored, vandal resistant
Serves up to 8 faucets
Input AC 120V, Output DC 12V, 3A

Battery Mode

Battery Powered Models

(4) AA Alkaline Batteries
400,000 on/off cycles, up to 4 years

Battery Service Life

Package Includes

(1) Faucet with electronic sensor
(1) Control box w/6V DC solenoid
(1) 12V DC plug-in power adapter (H-6700C, -DC, -LR and -LRDC only)
(1) In-line filter with clean-out trap
(1) 18" Flex, S.S. supply tube, 3/8"(1) 6" Gooseneck Spout
(1) Mounting hardware
(1) 2.0 GPM Flow Control(4) AA Alkaline batteries (HB-6700C, -DC, -LR, -LRDC only)
(1) Battery holder (HB-6700C, -DC, -LR, -LRDC only)


Dimensions

| | |
|--|-------------------|
| - Base Width (Outside Measurement) | 2-1/4" |
| - Base Depth | 2-1/2" |
| - Faucet Height (Aerator to Base) | 8-3/4" |
| - Faucet Height Overall | 12-3/4" |
| - Depth (Center of Aerator to Center of Faucet Base) | 5-3/8" |
| - Mounting Bolt Length | 1-7/16" |
| - Mounting Bolt Pattern | Single-hole mount |

Optional Variations and Accessories

- 0.35, 0.5, 1.5, 2.2 GPM Laminar Flow
- HC-010 Multi-Unit Voltage Adapter (AC Powered Only) - 8 units
- HC-0104 Multi-Unit Voltage Adapter (AC Powered Only) - 4 units
- HC-001 Mixing/Check Valve (Mechanical)
- HBL-04-LR Thermostatic Mixing Valve with Checks (Low Lead)
- 8" deep Gooseneck and 6" or 8" Swing Spout Model

| Model | Sensor Type | Flow-Rate |
|-----------|-------------|------------------|
| ES2RL | AC Powered | Standard 2.0 GPM |
| ES2RL-0.5 | AC Powered | Low-Flow 0.5 GPM |



| Model | Sensor Type | Flow-Rate |
|------------|-----------------|------------------|
| ESB2RL | Battery Powered | Standard 2.0 GPM |
| ESB2RL-0.5 | Battery Powered | Low-Flow 0.5 GPM |

