

30 Gallon - Cast Iron Oil Lubricated Belt Drive Compressor

FEATURES AND BENEFITS

- Cast iron, V-twin cylinder, oil lubricated pump features
 - One-piece cast iron crankcase
 - Thermally stable cast iron cylinder body
 - Aluminum head and machined cast iron valve plate
 - Automotive style ball bearings
 - Durable stainless steel reed valves
 - Oil level sight glass
 - Easily accessible oil fill
 - 10" cast iron balanced flywheel
- Heavy duty induction motor for maximum performance and efficiency
- 30 gallon ASME* portable tank equipped with pneumatic tires for maximum portability
- Dual voltage motor is wired for standard 120 volt outlet, and may also be converted for 240 volt application
- Shipped with 100% full synthetic air compressor oil for optimum performance and long life
- Fully assembled and equipped with quick-set regulator, tank and tool pressure gauges, quick connect air outlet and on/off switch for ease of use
- Supported by our Toll Free Customer Help Line



MODEL SPECIFICATIONS

Tank Size:	30 Gallon ASME*
Maximum Pressure:	135 PSI
CFM @ 40 PSI:	6.2
CFM @ 90 PSI:	5.3
Voltage:	120/240 Volt
Running HP:	1.6
Certifications:	CSA – C US*
Warranty:	2 Year Pump 1 Year All Other Parts
Model:	PXCMLC16830A66
UPC:	8 46212 08350 5

Dimensions: 25" x 24.5" x 49.5" • Weight: 165 lbs. • Pallet Qty: 4 • Truckload Qty: 192 (53' trailer)

*ASME – American Society of Mechanical Engineers, CSA Certified to UL1450 and CSA 22.2 No 68

Product style and configuration may vary.

