



Indigo NXT Series iP0600
ice machine on D570 bin.
Ice machine and bin sold separately.

iP0600

Manitowoc Ice Cube Machine

IDP0600A | IYP0600A | IDP0600A | IYP0600W

ICE SHAPES



- ▶ **Half-Dice:** 3/8" x 1 1/8" x 7/8" (0.95 x 2.86 x 2.22 cm)
- ▶ **Dice:** 7/8" x 7/8" x 7/8" (2.22 x 2.22 x 2.22 cm)

SIZE

- ▶ Up to 440 lbs(200 kgs) of daily ice production
- ▶ 30"(76.20 cm) wide, 34"(86.36 cm) deep, and 71.5"(181.61 cm) high on 6"(15.24 cm) legs
- ▶ 532 lb(241 kgs) ice bin storage capacity*

*Application capacity based on 90% volume x 33 lbs./ft³ average density of ice

SPECIFICATIONS

Refrigerant: R290

- ▶ Air-cooled: 270 g
- ▶ Water-cooled: 190 g

BTU Per Hour

- ▶ 10,330(average)
- ▶ 12,000(peak)

Operating Limits

- ▶ Ambient temperature range: 35° to 110°F (1.7° to 43.3°C)
- ▶ Water temperature range: 40° to 90°F (4.4° to 32.2°C)
- ▶ Water pressure ice maker (water in)
 - Min. 20 psi (137.9 kPa)
 - Max. 80 psi (551.1 kPa)

Power: 115/60/1 and 230/60/1

- ▶ Air-cooled-115V
 - Minimum circuit ampacity: 13.3 amps
 - Maximum fuse size: 20 Amps
- ▶ Air-cooled-230V
 - Minimum circuit ampacity: 6.6 amps
 - Maximum fuse size: 15 Amps
- ▶ Water-cooled-115V
 - Minimum circuit ampacity: 12.9 amps
 - Maximum fuse size: 20 Amps
- ▶ Water-cooled-230V
 - Minimum circuit ampacity: 6.3 amps
 - Maximum fuse size: 15 Amps

FEATURES

- ▶ Sanitation
 - Hinged front door and removable components (water trough, tube, curtain, probe, pump) allow easy interior access and cleaning.
 - Select parts feature AlphaSan® antimicrobial protection.
 - DuraTech™ exterior provides superior corrosion resistance compared to stainless steel. Innovative clear coat resists finger prints and dirt.
 - Optional Luminice® Growth Inhibitor helps control bacteria and yeast, with status indicator on display.
- ▶ Sustainability & Value
 - R290 offers low global warming potential and zero ozone depletion.
 - Energy-efficient models (see EnergyStar.gov)
 - Icon-based easyTouch® display simplifies operation.
 - Acoustical probe and Active Sense help ensure consistent ice production.
 - 24-hour diagnostics support preventative maintenance.
 - Designed with programmable ice production to take advantage of off-peak rates and/or shut off over night to lower lifetime costs.*
 - Connect via Bluetooth for quick setup and instant machine information.

*Based on manufacturer assumptions without independent testing. Results may vary by settings and conditions.

ACCESSORIES

- ▶ Luminice® II virus and bacteria inhibitor helps control viruses and bacteria in the ice machine.
- ▶ iAuCS® schedules and performs routine ice machine descaling or sanitizing automatically.
- ▶ Arctic Pure® Pro water filters reduce sediments and chlorine contaminants down to 0.5 microns.

For optimal performance, use the Arctic Pure prefilter in combination with the Arctic Pure primary filter.



Luminice II



iAuCS



Arctic Pure Water Filters

iP0600

Manitowoc Ice Cube Machine

IDP0600A | IYP0600A | IDP0600A | IYP0600W

INSTALLATION

Ice machine must be installed indoors.

Required clearance for

- top and sides: 8" (20.32 cm)
- back: 5" (12.7 cm)

A Electrical Entrance (2) Options

B 3/8"(0.95 cm) F.P.T.

Water Condenser Inlet
(water-cooled units)

C 1/2"(1.27 cm) F.P.T.

Water Condenser Outlet
(water-cooled units)

D 1/2"(1.27 cm)

Auxiliary Base Drain Socket

E 3/8"(0.95 cm) F.P.T.


Ice Making Water Inlet

F 1/2"(1.27 cm) F.P.T.

Ice Making Water Drain

G 3/4"(1.91 cm)

Bin Drain



SPACE-SAVING DESIGN



iP0600
D400

iP0600
D570

Height	59.50" 151.13 cm	71.5" 181.61 cm
Width	30.0" 76.2 cm	30.0" 76.2 cm
Depth	34.0" 86.36 cm	34.0" 86.36 cm
Bin Storage	365 lbs 165 kgs	532 lbs 241 kgs

Height includes adjustable bin legs
6.00" to 8.00", (15.24 to 20.32 cm)
set at 6.00" (15.24 cm).

Bin capacity is based on 90% of the
volume x 33 lbs/ft³ average density of ice.
Ice machine and bin sold separately.

SPECIFICATIONS

	Model	Ice Shape	Shipping Weight	Ice Production 24 Hours		Power Usage kWh per 100 lbs of ice @ 90° Air/70°F Water (32° Air/21°C Water)	Ice Machine Potable water usage per 100 lbs ice @ 90° Air/70°F Water (32° Air/21°C Water)	Condenser water usage per 100 lbs ice @ 90° Air/70°F Water (32° Air/21°C Water)
				70° Air/50°F Water 21° Air/10°C Water	90° Air/70°F Water 32° Air/21°C Water			
Water Cooled	IDP0600A	Dice	161 lbs (73.1 kgs)	662 lbs (300.2 kgs)	514 lbs (233.1 kgs)	4.77 ★	13.9 gal (52.6 L)	N/A
	IYP0600A	Half-Dice	155 lbs (70.3 kgs)	672 lbs (304.8 kgs)	554 lbs (251.2 kgs)	4.77 ★	13.9 gal (52.6 L)	N/A
Air Cooled	IDP0600W	Dice	153 lbs (69.4 kgs)	605 lbs (274.4 kgs)	509 lbs (230.9 kgs)	4.11	15.3 gal (57.9 L)	135 gal (511 L)
	IYP0600W	Half-Dice	153 lbs (69.4 kgs)	650 lbs (294.8 kgs)	505 lbs (229 kgs)	4.43	15 gal (56.8 L)	135 gal (511 L)

★ Energy Star Model

Limited Commercial Warranty

Ice Maker Three (3) years parts and labor

Evaporator Five (5) years parts and labor

Compressor Five (5) years parts, three (3) years labor



2110 South 26th Street | Manitowoc, WI 54220 | United States
+1.920.682.0161 | 920.683.7589 Fax | manitowocice.com

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners. ©2025 Pentair. All rights reserved.