

DESCRIPTION

Floor-Mounted 1.28 gpf (4.8 Lpf) Pressure-Assisted/Tank Toilet ADA Water Closet.

COMPONENTS

Bowl: Code 2108029Tank: Code 2108010

DETAILS

• Flush Volume: 1.28 gpf (4.8 Lpf)

FEATURES

- White Vitreous China
- Elongated bowl
- Floor mounted, floor outlet
- 12" (305mm) rough-in
- Chrome metal flush handle
- Secure, anti-rocking 3-point tank mounting system
- Powered by Flushmate® brand pressure assisted flushing technology to achieve 1,000g MaP score
- Over 60 ft (18.3 m) drainline carry performance
- Water spot area: 11 \(^1\lambda\) x 9\(^3\lambda\) (286 mm x 248 mm)
- Smooth, quiet cable activated flush handle left hand
- Fully glazed trapway
- Closet bolts and caps included
- · Toilet seat and wax ring not included

PLUMBING SYSTEM REQUIREMENTS

Maximum Static Pressure: 80 PSI (552 kPa)
Minimum Static Pressure: 20 PSI (138 kPa)

DOWNLOADS

- Pressure-Assisted Installation Instructions
- Flushmate Owner's Manual
- Pressure-Assisted Repair and Maintenance Guide
- Additional Downloads



COMPLIANCES & CERTIFICATIONS













(ADA Compliant, CalGreen Compliant, CEC Compliant, cUPC Green Certified, WaterSense Listed, NOM Certified)

NOTE:

All vitreous china dimensions shown in these drawings are nominal and not to scale. Dimensions can vary within the tolerances established in the governing ASME A112.19.2/CSA B45.1 standard. It is important to consider this when planning rough-in and plumbing layouts.

All information contained within this document subject to change without notice.

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com



ROUGH-IN

