## T&S BRASS AND BRONZE WORKS, INC.

2 Saddleback Cove / P.O. Box 1088 Travelers Rest, SC 29690

Model No.

EC-3100-TMV

Item No.

ANSI A117.1 (ADA)

ASSE 1070 (TMV)

1:6


Sheet: 1 of 2

Scale:

UL 1951

12/20/19

Travelers Rest, SC: 800-476-4103 • Simi Valley, CA: 800-423-0150 • Fax: 864-834-3518 • www.tsbrass.com



Flow Control Setting Switches, Thermostatic Temperature Control Mixing Valve

Approved:

JHB

Date:

w/ Check Valves, 18" Hot & Cold Supply Stop Flexible Connector Hoses

GEF

Drawn:

KJG

Checked:



## T&S BRASS AND BRONZE WORKS, INC.

2 Saddleback Cove / P.O. Box 1088 Travelers Rest, SC 29690

Model No.

EC-3100-TMV

Item No.


Travelers Rest, SC: 800-476-4103 • Simi Valley, CA: 800-423-0150 • Fax: 864-834-3518 • www.tsbrass.com

| 3 |  |
|---|--|
| 2 |  |
| 1 |  |

| ITEM<br>NO. | SALES NO. | DESCRIPTION                                   |
|-------------|-----------|---|
| 1           | B-0199-06 | VR Aerator w/ Key                             |
| 2           | 044A      | 3/8" to Aerator Adapter                       |
| 3           | 006575-45 | O-ring  |
| 4           | 017195-45 | Angled Sensor w/ Cable                        |
| 5           | 016297-45 | Inlet Hose, Faucet, 1/2" NPSM-F x 1/4" NPSM-F |
| 6           | EC-FILTER | Replacement Filter                            |
| 7           | 016647-45 | ChekPoint Sensor Faucet Control Module        |
| 8           | 5EF-0002  | A/C Transformer                               |
| 9           | EC-TMV    | ASSE 1070 Thermostatic Mixing Valve           |
| 10          | 5EF-0005  | Supply Hose, 9/16-24 Female x 1/2" NPSM       |
| 11          | 015425-45 | Vandal Resistant Key                          |
|             |           |   |



A Maximum of (8) ChekPoint Faucets can be Hardwire Connected and Powered by EC-HARDWIRE ChekPoint Hardwire AĆ Transformer. (Sold Separately)



Label for Flow Control Switch Settings is Located on Inside of Back Cover.

Flow Control Switches are Located Inside Module Housing in Black Box Next to Battery Compartment.
\*Switches are Set to DEFAULT Position:

- - Auto Time Out = 15 Seconds
  - Shut Off Delay = 1 Second Auto Flush = OFF

Remove (4) Screws and Back Cover to Access Switches.

\*Available Water Flow Control Selections:

- Auto Time Out: 15 sec, 30 sec, 45 sec, 60 sec, 3 min, 20 min Shut Off Delay: 1 sec, 10 sec, 15 sec, 30 sec

Checked:

- Auto Flush (30 Seconds After Every 12 Inactive Hours): ON or OFF

**Product Specifications:** 

KJG

Drawn:

Chrome Plated Brass Electronic Faucet:

Deck Mt. Rigid Gooseneck w/ VR Aerator, AC/DC Control Module w/ Internal Flow Control Setting Switches, Thermostatic Temperature Control Mixing Valve w/ Check Valves, 18" Hot & Cold Supply Stop Flexible Connector Hoses

Approved:

Date:

12/20/19

**GEF** 

Product Compliance:

ASME A112.18.1 / CSA B125.1 NSF 61 - Section 9 NSF 372 (Low Lead Content) ANSI A117.1 (ADA)

UL 1951 ASSE <u>1070</u>

Scale: NTS Sheet: 2 of 2