



TECHNICAL DATA SHEET

CLR PRO MAX[®] INDUSTRIAL DEGREASER

DESCRIPTION:

CLR PRO MAX[®] Industrial Degreaser effectively penetrates and dissolves heavy grease, oil, and grime, saving time and effort on degreasing jobs. The water-based, concentrated formula contains no abrasives or solvents.

FEATURES & BENEFITS:

- Penetrates and effectively cuts through oil, grease, cutting fluids, and residue found on parts, machinery, and heavy equipment.
- Eliminates grease, oil, and food remnants from appliances, vents, traps, grill hoods, and trash containers.
- Concentrated formula allows you to choose the strength you need to get the job done.
- Used for surface preparation before welding, plating, or painting.
- Safe to use in floor scrubbers, parts washers, dip tanks, pressure washers and carpet extractors.
- Water-based formula is non-flammable and has no VOCs.
- Contains no acids, abrasive, or petroleum solvents.
- NSF Registered—approved for use in food processing, food storage, and food service facilities.

SURFACES

CONCRETE	ASPHALT	STAINLESS STEEL	PAINTED SURFACES
BRICK	GRANITE	RUBBER	FLOOR MATS
STONE	FIBERGLASS	CARPET	VINYL
TERRAZZO	METAL	NON-WAX FLOORS	

DIRECTIONS FOR USE

1. Always spot test on an inconspicuous area before applying.
2. Start by removing heavy or loose deposits.
3. Apply product to surface. Use towel or wet sponge to wipe surface clean. Dwell time may vary by soil load.
4. Rinse with clean water after use.

Product	Size	Stock #
CLR PRO MAX [®] Industrial Degreaser	32 oz.	I-DEG32-6PROM
	1 Gal.	I-DEG128-4PROM
	5 Gal.	I-DEG-5PROM
	55 Gal.	I-DEG-55PROM
	275 Gal.	I-DEG-275PROM



Safety: See label and SDS for precautionary instructions before use. Use appropriate safety equipment and job site controls during application, handling, and disposing. SDS is available online at www.clrpro.com.



PHYSICAL & CHEMICAL PROPERTIES

Appearance	Clear liquid
Odor	None
Odor Threshold	N.D.
pH @20°C	13.4
Melting Point	N.D.
Freezing Point	N.D.
Boiling Point	N.D.
Boiling Point Range	N.A.
Flash Point	N.D.
Evaporation Rate	N.D.
Flammability	Not Flammable
Upper/Lower Flammability	N.A.
Vapor Pressure	N.D.
Vapor Density (mm Hg)	N.D.
Relative Density @20°C	N.D.
Solubility in Water	Soluble
Partition Coefficient; n-octanol/water	N.D.
Auto Ignition Temperature	N.A.
Decomposition Temperature	N.A.
Viscosity	N.D.
VOC	0%

TDS-MAX-I-DEG



TECHNICAL DATA SHEET

DILUTION RATIOS

APPLICATION	WATER to CLR PRO MAX® Industrial Degreaser
Industry / Warehouse	
Machinery	1:1
Tools	1:1
Concrete Floors	10:1
Oil Tanks	10:1
Pressure Washers	10:1
Tank Style Parts Washer	3:1
Dip Tank & Ultrasonic Parts Washer	25:1
Spray Cabinet Washer	70:1
Automotive	
Driveways	1:1
Engines	1:1
Parts	3:1
W/W Tires	1:1
Car Wash	1gal:1oz
Utilities	
Motors	4:1
Transformers	5:1
Turbine Blades	5:1
Foodservice Restaurant	
Exhaust Filters	1:1
Stoves	1:1
Wax Remover	1:1
Carpets	3:1
Exhaust Hoods	3:1
Upholstery	4:1
Counter Tops	6:1
No Wax Floors	20:1

Ratio is equal units of measurement unless indicated.