

PS 748 UTILITY GRADE TENSILIZED STRAPPING TAPE

TYPICAL APPLICATIONS

- For light duty strapping, packaging, bundling and palletizing applications

PRODUCT FEATURES

- Utility grade tensilized strapping tape
- Quick and aggressive bond to a variety of surfaces
- Abrasion-, moisture- and solvent-resistant

CONSTRUCTION

Backing: Tensilized, mono-oriented polypropylene film

Adhesive: Emulsion acrylic adhesive

STANDARD WIDTHS

0.35 in; 0.47 in; 0.7 in
9 mm; 12 mm; 18 mm

STANDARD LENGTH

60.1 yd
55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLORS



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	34 oz/in width	3.72 N/10 mm
Elongation	30%	30%
Service Temperature Range	0 F to 250 F	-18 C to 121 C
Tensile	100 lbs/in width	175.1 N/10 mm
Thickness	2.8 mils	0.07 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

