



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S29815 - 15 Watt; A19 LED; Frosted; 2700K; Medium base; 220 deg. Beam Angle; 120 Volt

- Rated for Enclosed Fixture



ELECTRICAL

Technology:	LED
Watts:	15W
Volts:	120V
Lumens:	1600L
CRI:	80
Rg Value :	6
CCT (Kelvins):	2700K
Color Description:	Warm White
Beam Spread :	220
Hours Rated:	25000
Dimmable:	Yes-Dimmable
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable
Incandescent Equivalent :	100W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Power Factor :	0.94
Light Source:	LED
Warranty:	5 Year Limited - 10 hr per day

PACKAGING

Each UPC:	045923298158
Each Quantity:	1
Each Dimensions:	2.44 x 2.44 x 5.12
Inner UPC:	20045923298152
Inner Quantity:	6
Inner Dimensions:	7.80 x 5.20 x 5.43
Case UPC:	10045923298155
Case Quantity:	24
Case Dimensions:	11.22 x 8.46 x 11.93

PHYSICAL

ANSI Base:	E26
Base:	Medium
Shape:	A19
Finish:	Frost
MOD (In.):	2.362
MOL (In.):	4.646
Weight (Lbs.):	0.07
Material:	Metal / Plastic

COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-2307670
Energy Star Lamp Category:	Omnidirectional
DLC Approved:	No
UL/ETL Standard:	ANSI/UL 1993; CSA-C22.2 No. 1993
BAA Compliant:	No
NOM Certificate No.:	NOM-030- ENER-2016!NTEC22EN003813
NOM Expiration Date:	5/29/2024
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	Not For Sale In: CA



S29815 - 15 Watt; A19 LED; Frosted; 2700K; Medium base; 220 deg.
Beam Angle; 120 Volt

DIMMER COMPATIBILITY

Lutron	AYCL-153P
Lutron	CTRP-253P
Lutron	DVCL-153P
Lutron	DVRP-253P
Lutron	LECL-153PH
Lutron	MA-PRO
Lutron	NTRP-250
Lutron	PD-6WCL
Lutron	RRD-PRO
Satco	S11270