

Profit from the Eagle Advantage®

# **Specification Sheet**

## **Short Form Specifications**

Eagle One-Compartment Sink, model\_\_\_\_\_\_\_, with 2"-wide "Euro-Style" edging on front and sides. Sink bowl is heavy gauge type 304 stainless steel, with 13½" water level, deep drawn, seamless and have all corners coved. Top—including backsplash, and drainboards (when required)—is heavy gauge type 430 stainless steel. Drainboards shall be "V" creased for positive drainage. 9½" high backsplash with 1" upturn and tile edge. Legs to be 1½" O.D. galvanized tubing with front-to-back crossbracing, and 1" high impact plastic adjustable bullet feet.



# **Options / Accessories**

- ☐ Stainless steel legs
- ☐ Stainless steel bullet feet
- ☐ Lever drains
- ☐ Twist handle drains
- Twist drain brackets
- ☐ Faucets
- ☐ Sink covers
- Waste outlets
- Sink kits
- Overflow hole

## **EAGLE GROUP**

100 Industrial Boulevard, Clayton, DE 19938-8903 USA Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440 MHC/Retail Display Divisions: Phone 800-637-5100

For custom configuration or fabrication needs, contact our **SpecFAB Division**. Phone: 302-653-3000 • Fax: 302-653-3091 • e-mail: specfab@eaglegrp.com

Item No.:	
Project No.:	
S.I.S. No.:	

# 414 Series Coved Corner One-Compartment Sinks

### MODELS:

<b>414-16-1</b>	<b>□</b> 414-18-1	<b>□</b> 414-22-1	□ 414-24-1
<b>414-16-1-18</b>	<b>□</b> 414-18-1-18	<b>□</b> 414-22-1-18	<b>414-24-1-18</b>
☐ 414-16-1-18L	☐ 414-18-1-18L	☐ 414-22-1-18L	<b>414-24-1-18</b>
☐ 414-16-1-18R	☐ 414-18-1-18R	☐ 414-22-1-18R	<b>414-24-1-18</b>
<b>414-16-1-24</b>	<b>414-18-1-24</b>	□ 414-22-1-24	<b>414-24-1-24</b>
☐ 414-16-1-24L	☐ 414-18-1-24L	☐ 414-22-1-24L	<b>414-24-1-24</b>
☐ 414-16-1-24R	□ 414-18-1-24R	☐ 414-22-1-24R	<b>414-24-1-24</b>

#### **Materials**

- Sink bowl: Heavy gauge type 304 stainless steel.
- Top: Drainboards, backsplash and euro-style edging are heavy gauge type 430 stainless steel.
- Legs: 1%" (41mm)-diameter heavy-gauge galvanized tubing with plated 12-gauge gussets and high-impact corrosion resistant fully adjustable bullet feet - crossbracing is 1" (25mm)-diameter heavy-gauge galvanized tubing.

### **Design and Construction Features**

- Bowl features deep-drawn one-piece seamless construction, using state-of-the-art hydraulic presses.
- Sink bowl has generous radius with a minimum dimension of 3" (76mm) and are rectangular for maximum capacity.
- New 20" x 16" (508 x 406mm) bowl design, with enhanced polishing techniques.
- 13½" (343mm) water level is standard.
- Swirl-away drainage.
- Leg gusset assemblies welded adjacent to sink bowl for maximum weight support and stability.
- 9½" (241mm) standard backsplash includes 1" (25mm) upturn and tile edge for easy installation and feathering to wall/splash surface.
- "V" creased drainboards for positive drainage.

### Mechanical:

- Water supply is  $\frac{1}{2}$ " (13mm) IPS for hot and cold lines.
- Faucet holes are 1½" (29mm) punched on 8" (203mm) centers.
- Basket-type waste drain included fits sink bowl's 3½" (89mm) opening and features 1½" (38mm) outlet.

# Certifications / Approvals AUTOQUOTES







EG20.23 Rev. 10/12



Item No.:	
Project No.:	
S.I.S. No.:	

# 414 Series Coved Corner One-Compartment Sinks






haw	Overall wi		naion A	-	A—————————————————————————————————————
	l size		nsion A	_ 3″	5"
in.	mm	in.	mm	76mm	127 <u>mm √[9</u> 5″
20" x 16"		27½"	699	_ +	↑ 241mm
24" x 18"	610 x 457	31¾"	807	[	
22" x 22"	559 x 559	29¾"	756	<b>1</b>	$H \mid H \mid H \mid$
24" x 24"	610 x 610	31¾″	807	13.5″ 343mm	44" 1118mm
Drain location for rough-in				37.5″	39"   991mm
bow	bowl size Dimension B		953mm		
in.	mm	in.	mm		
20" x 16"	508 x 406	14"	357		
24" x 18"	610 x 457	16″	406	1	1
22" x 22"	559 x 559	15″	381	9.75″	
24" x 24"	610 x 610	16″	406	248mm	









Please note the pair of legs located under the OUTER area of drainboard (only on one-compartment sinks with one drainboard)

	BOWL DIMENSIONS   width length			DRAINBOARD length			OVERALL DIMENSIONS width length				weight		
model #	in.	mm	in.	mm	quantity	in.	mm	in.	mm	in.	mm	lbs.	kg
414-16-1	20″	508	16″	406	0		-	27½″	699	23¼"	591	40	18.1
414-16-1-18R or L	20″	508	16″	406	1	18″	457	27½"	699	38¾"	987	59	26.8
414-16-1-18	20″	508	16″	406	2	18″	457	27½″	699	54½"	1384	78	35.4
414-16-1-24R or L	20″	508	16″	406	1	24"	610	27½"	699	447/8"	1140	65	29.5
414-16-1-24	20″	508	16″	406	2	24"	610	27½″	699	66½"	1689	90	40.8
414-18-1	24"	610	18″	457	0		-	31¾″	807	25½"	648	45	20.4
414-18-1-18R or L	24"	610	18″	457	1	18″	457	31¾″	807	40¾"	1035	64	29.0
414-18-1-18	24"	610	18″	457	2	18″	457	31¾″	807	56"	1422	83	37.6
414-18-1-24R or L	24"	610	18″	457	1	24"	610	31¾″	807	46¾"	1188	70	31.8
414-18-1-24	24"	610	18"	457	2	24"	610	31¾″	807	68"	1727	95	43.1
414-22-1	22"	559	22″	559	0		-	29¾"	756	29½"	749	55	24.9
414-22-1-18R or L	22"	559	22"	559	1	18″	457	29¾"	756	45"	1143	74	33.6
414-22-1-18	22″	559	22"	559	2	18″	457	29¾"	756	60½"	1537	93	42.2
414-22-1-24R or L	22″	559	22"	559	1	24"	610	29¾"	756	51″	1295	80	36.3
414-22-1-24	22″	559	22″	559	2	24"	610	29¾″	756	72½″	1842	105	47.6
414-24-1	24"	610	24"	610	0		-	31¾″	807	31½"	800	60	27.2
414-24-1-18R or L	24"	610	24"	610	1	18″	457	31¾″	807	46¾"	1188	79	35.8
414-24-1-18	24"	610	24"	610	2	18″	457	31¾″	807	62"	1575	98	44.5
414-24-1-24R or L	24″	610	24"	610	1	24"	610	31¾″	807	52¾"	1340	85	38.6
414-24-1-24	24"	610	24"	610	2	24"	610	31¾"	807	74"	1880	110	49.9

## **EAGLE GROUP**

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440 MHC/Retail Display Divisions: Phone 800-637-5100

Printed in U.S.A. ©2012 by Eagle Group

Rev. 10/12