

Specification Sheet

Short Form Specifications

Eagle Hand Sinks with Side Splashes, model _____. Constructed of all-welded type 304 stainless steel, with deep-drawn positive drain sink bowl, inverted "V" edge to prevent spillage, drain, splash-mounted faucet, and factory-installed side splash on both sides. Offered are the following hand sinks:

- Model #HSA-10-F-LRS.
- Model #HSAN-10-F-LRS. 12" side-to-side.
- Model #HSA-10-FDPE-LRS. Includes paper towel dispenser, soap dispenser, and electronic-eye sensor-beam faucet with 12-volt adaptor – 120/60/1.
- Model #HSA-10-FTWS-LRS. Includes tubular wall support.



HSA-10-F-LRS



HSAN-10-F-LRS



HSA-10-FDPE-LRS



HSA-10-FTWS-LRS

model #	includes	bowl size		overall size		weight	
		width	length x depth	width	length x height	lbs.	kg
HSA-10-F-LRS	faucet, basket drain and side splashes	9¾" x 13½" x 6¾"	248 x 343 x 173	14¾" x 18¾" x 12¾"	376 x 480 x 324	14	6.4
HSAN-10-F-LRS	12" side-to-side, faucet, basket drain, side splashes	13½" x 9¾" x 6¾"	343 x 248 x 173	18" x 12" x 14¼"	457 x 305 x 362	13	5.9
HSA-10-FTWS-LRS	faucet, p-trap, tubular wall brackets, basket drain, side splashes	9¾" x 13½" x 6¾"	248 x 343 x 173	14¾" x 18¾" x 12¾"	376 x 480 x 324	21	9.5
HSA-10-FDPE-LRS	electronic-eye faucet, towel/soap dispenser, basket drain, side splashes	9¾" x 13½" x 6¾"	248 x 343 x 173	14¾" x 19¼" x 28¼"	376 x 489 x 718	31	14.1

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440

MHC/Retail Display Divisions: Phone 800-637-5100

For custom configuration or fabrication needs, contact our SpecFAB® Division.

Phone: 302-653-3000 • Fax: 302-653-3091 • e-mail: quotes@eaglegrp.com

Item No.: _____
Project No.: _____
S.I.S. No.: _____

Hand Sinks with Side Splashes

MODELS:

- ☐ HSA-10-F-LRS
- ☐ HSAN-10-F-LRS
- ☐ HSA-10-FTWS-LRS
- ☐ HSA-10-FDPE-LRS

Hand Sinks

- Heavy gauge type 304 stainless steel all-welded construction.
- Inverted "V" edge rim retards spillage.
- Unique deep-drawn positive-drain bowl assures complete drainage to meet the most stringent health code requirements.
- Water inlet: ½" (13mm) NPS.
- Drain outlet: 1½" (38mm) NPS.

Side Splashes

- Side splashes are factory-installed on both sides of sink.
- 16 gauge type 304 stainless steel.
- Tapered and rounded for safety.

Certifications / Approvals



AUTOQUOTES

