

## SELF-CONTAINED PASS-THRU BACK BAR REFRIGERATOR 2-, 4- AND 6-DOOR









JOB	
AREA	
ITEM NO.	
MODEL NO.	
PTS36	2-Door Model
PTS60	4-Door Model
PTS84	6-Door Model

PTS36 shown

econ friendly R290 Refrigerant NSF/ANSI Standard 7 Listed for open food storage. Note: Models furnished with wine temperature are listed for the storage and display of bottled and canned products only.


MODEL NUMBERS		PTS36	PTS60	PTS84
NUMBER OF DOORS		2	4	6
EXTERIOR CABINET DIMENSIONS	Length - in. (mm)	36 (914)	60 (1524)	84 (2134)
	Depth - in. (mm)	2611/16 (678)	2611/16 (678)	2611/16 (678)
	Height - in. (mm)	34% (878)	34% (878)	34% (878)
INTERIOR CABINET DIMENSIONS	Length - in. (mm)	20 (508)	44 (1118)	68 (1727)
	Depth - in. (mm)	18¾ (476)	18¾ (476)	18¾ (476)
	Height - in. (mm)	31 (787)	31 (787)	31 (787)
INTERNAL VOLUME Net. Cu. Ft. (Litres)		8.0 (227)	17.4 (493)	26.7 (756)
PRODUCT CAPACITY	CASE PACKED - 12 OZ. BOTTLE/CAN	182/273	371/553	581/868
PRODUCT CAPACITY	STAGGERED - 12 OZ. BOTTLE/CAN	196/292	400/592	628/932
SHIPPING WEIGHT Lbs. (kg.)		264 (120)	354 (161)	496 (225)
ELECTRICAL SPECIFICATIONS	Electrical Supply	120 VAC/60 Hz/1 Ph	120 VAC/60 Hz/1 Ph	120 VAC/60 Hz/1 Ph
	Running Load Amps	1.8	2.5	4.2
	Electrical Connection	Cord connected	Cord connected	Cord connected
	Cord Plug Type	NEMA 5-15	NEMA 5-15	NEMA 5-15
	Cord Length	8'	8'	8'
	Defrost Initiation	Automatic	Automatic	Automatic
	Defrost Type	Off cycle	Off cycle	Off cycle
	Thermostat	Digital control	Digital control	Digital control
	Lighting Type	LED	LED	LED
REFRIGERATION SPECIFICATIONS	Horsepower	1/6	1/5	1/4
	Refrigerant	R290	R290	R290
	Refrigerant Charge gm.	90	100	90
	Factory Temperature Setting-Refrigerator F (C)	38° (3.3°)	38° (3.3°)	38° (3.3°)
	Temperature Range-Refrigerator F (C)	33°-40° (0.5°-4.5°)	33°-40° (0.5°-4.5°)	33°-40° (0.5°-4.5°)
	Factory Temperature Setting-White Wine F (C)	50°-55° (10.0°-13.0°)	50°-55° (10.0°-13.0°)	50°-55° (10.0°-13.0°)
	Factory Temperature Setting-Red Wine F (C)	60°-65° (15.5°-18.0°)	60°-65° (15.5°-18.0°)	60°-65° (15.5°-18.0°)
	Temperature Range-Wine F (C)	50°-65° (10.0°-18.0°)	50°-65° (10.0°-18.0°)	50°-65° (10.0°-18.0°)
	Condensing Unit Location	Left or Right	Left or Right	Left or Right
	Expansion Device	Capillary tube	Capillary tube	Capillary tube
	Pull Out Condensing Unit	Yes	Yes	Yes
	Format Vanta d	Yes	Yes	Yes
DILIMPING	Front Vented			
PLUMBING	Floor Drain Included	Yes	Yes	Yes

Form No. Z2381 Rev. 05.07.2019



## SELF-CONTAINED PASS-THRU BACK BAR REFRIGERATOR 2-, 4- AND 6-DOOR

Note: Open floor drain not provided on models intended for non-packaged food.



## California Prop 65 Notice:



**WARNING:** The materials used in this product may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm, For more information go to www.P65Warnings.ca.gov.