Model 380ADP









Double Door, Slant Front, Outdoor Ice Merchandiser

Mode	Dimensions D x W x H	Volts / Hertz / Phase	Amps	Unit H.P.	Refrigerant	Capacity (Cu. Ft.)	Approx. Shipping Weight (lbs.)
380 AI	P Ext. 35" x 48" x 72" Int. 31" x 44" x 53"	115V / 60HZ / 1PH	4.13 amps / 15-amp circuit	1/3	R-290	38	340

Agency Listings

> ETL Listed in accordance to UL 60335-1-89 and UL 60335-2-89 Standard - 2nd Edition

Connections

- Electrical connection: Heavy Duty 12-Gauge 10-Foot. Cord with plug
- > Condensation Plumbing Connection: 1/2" I.D. Plastic

Optional Features

- > Bright Aluminum Diamond Plate Kick Plate
- > Door Opening Ice Breaker Bar
- > 4" Casters with 1/4 " Aluminum Angle Perimeter Frame
- > TX Valve Metering Device
- > ETL Listed in accordance to NSF7 Standard

Standard Features

- Merchandiser designed to hold product between 10°F to 20°F
- 26-gauge Ceram-A-Star pre-painted steel exterior/26-gauge galvanized steel interior
- > Solid Insulated Door with TPE Magnetic, Positive Seal, Self-Closing Gasket
- > Top Mounted Refrigeration System with Low Global Warming Potential
- > Copper Tube Evaporator with Capillary Tube
- > Environmentally-friendly, nonflammable, foamed-inplace insulation that provides exceptional energy efficiency.
- > Electronic Control System Gives Service Friendly Fault Codes
- > Electric Automatic Defrost (AD) System
- > Floor Racks
- > Solid Injection Molded Feet