# **Model 630ADP**









## Single Door, Upright, Outdoor Ice Merchandiser

Model	Dimensions D x W x H	Volts / Hertz / Phase	Amps	Unit H.P.	Refrigerant	Capacity (Cu. Ft.)	Approx. Shipping Weight (lbs.)
630ADP	Ext. 35" x 62" x 79" Int. 31" x 58" x 59"	115V / 60HZ / 1PH	6.8 amps / 15- amp circuit	1/3	R-290	61	420

#### **Agency Listings**

> ETL Listed in accordance to to UL 60335-1-89 and UL 60335-2-89 Standard - 2nd Edition

#### Connections

- ➤ Electrical connection: Heavy Duty 12-Gauge 10-Foot. Cord with plug
- > Condensation Plumbing Connection: 1/2" I.D. Plastic

### **Optional Features**

- > 24" LED Light
- > Bright Aluminum Diamond Plate Kick Plate
- > Door Opening Ice Breaker Bar
- > Electric Condensation Pan
- > 4" Casters with 1/4 " Aluminum Angle Perimeter Frame
- > TX Valve Metering Device
- > ETL Listed in accordance to NSF7 Standard
- > Shelves

#### **Standard Features**

- Merchandiser designed to hold product between 10°F to 20°F
- > 26-gauge Ceram-A-Star pre-painted steel exterior/26-gauge galvanized steel interior
- Solid Insulated Door with TPE Magnetic, Positive Seal, Self-Closing Gasket
- Top Mounted Refrigeration System with Low Global Warming Potential
- Aluminum Fin/Copper Tube Evaporator with Capillary Tube
- > Environmentally-friendly, nonflammable, foamed-inplace insulation that provides exceptional energy efficiency.
- Electronic Control System Gives Service Friendly Fault Codes
- > Electric Automatic Defrost (AD) System
- > Floor Racks
- > Solid Injection Molded Feet