

3M™ Water Filtration Products

SPEC# _____

QUANTITY _____

application: **DROP-IN REPLACEMENTS**

models:

9 3/4" Cartridges

The 3M™ Water Filtration Products line of drop-in cartridges are an economical way to help reduce constituents in water that can cause equipment damage and unappealing product. Media choices of graded density, charge modified, activated carbon and pleated polypropylene provide a wide range of sediment holding capacities, chlorine reduction capabilities and micron ratings. These cartridges can be used in the 3M Water Filtration Products premium line of drop-in housings or as retrofits to upgrade current filtration.

PRODUCT SPECIFICATIONS

Model Number	Part Number	Micron Rating	Claims	Type	Flow Rate gpm (lpm)	CUNO Housings
CFS8504-A	55847-03	10	Sediment Reduction	Uniform Density	6 (22.7)	CFS11 CFS01 CFSBCI-1
CFS110	56121-11	5	Sediment Reduction	Progressive Porosity	8 (30.3)	
CFS124	56212-05	25	Course Sediment Reduction	Progressive Porosity	6 (22.7)	
CFS2501	55603-13	0.6	Cyst Reduction	Pleated Membrane	3 (11.4)	
CFS2506	55757-03	5	5 Micron Absolute Particulate Reduction	Pleated Membrane	3 (11.4)	
CFS420IMF	55609-04	5	Sediment, Scale Inhibition	Graded Density Polyphosphate	8 (30.3)	
CFS117	55593-04	5	Chlorine Taste and Odor Reduction	Granular Activated Carbon	3 (11.4)	
CFS117-S	55594-12	5	Chlorine Taste and Odor Reduction, Scale Inhibition	Granular Activated Carbon Polyphosphate	3 (11.4)	
CFSCB10	56126-04	10	Chlorine Taste and Odor Reduction For equipment applications up to 200°F (93.3°C)	Carbon Block	1 (3.8)	
CFS185-A	5594605	1	Sediment, Chlorine Taste and Odor Reduction	Carbon Block	1.7 (6.4)	
CFS186-A	FSCT0B10N	5	Chlorine Taste and Odor Reduction	Carbon Block	1.67 (6.3)	



9 3/4" Cartridges

3M™ Water Filtration Products

SPEC# _____

QUANTITY _____

MODEL NUMBER _____

PART NUMBER _____

IMPORTANT: INSTALLATION TIPS

These installation tips are for informational purposes only and are not intended to be used as actual installation instructions. **CAUTION:** To reduce the risk associated with property damage due to water leakage:

- **Read and follow** Use Instructions before installation and use of this system.
- Installation and use **MUST** comply with all state and local plumbing codes.
- **Protect from freezing**, remove filter cartridge when temperatures are expected to drop below 40°F (4.4°C).
- **Do not install on hot water supply lines.** The maximum operating water temperature of this filter system is 100°F (37.8°C).
- **Do not install** where water hammer conditions may occur. If water hammer conditions exist you must install a water hammer arrester. Contact a plumbing professional if you are uncertain how to check for this condition.
- The disposable filter cartridge **MUST** be replaced every 12 months, at the rated capacity or if a noticeable reduction in flow rate occurs.

⚠ WARNING: To reduce the risk associated with the ingestion of contaminants:

- **Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.**
Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts. EPA Establishment #070595-CT-001

CUNO Incorporated recommends regularly scheduled maintenance and replacement of the filter cartridge(s) in order for the product to perform as advertised/sold. CUNO shall not be liable for system failures due to improper maintenance.



CUNO Incorporated
400 Research Parkway
Meriden, CT 06450 U.S.A.
Toll Free: 1.800.222.7880
Worldwide: 203.237.5541
Fax: 203.238.8701
www.cuno.com