



Conditioned air stays in, energy bills go down

The All-New **SchwankAir 2000 Series** easily mounts on any door up to 10 feet high in order to create an air seal to keep conditioned air in the building and keep dust, dirt, and insects out. Multiple units can be stacked together for larger door widths.



Keep Conditioned Air In



Save Energy



Deter Insects



No Cold Drafts

Features

- Available in ambient, electric, and water models for any type of application
- Available in 208V, 230V, 480V, and 600V models
- All units are available in optional heated models
- All units are available in optional recessed air curtain models
- Wall brackets and ceiling mounting points supplied for surface mount units
- SchwankAir Wired Controller included



Door Heights: Up to 10 feet

Perfect for:



RESTAURANTS



HOTELS



RETAIL



FOOD PROCESSING



WAREHOUSES



MANUFACTURING



AUTOMOTIVE



SchwankAir 2000 Series - Technical Specifications

Information below is intended only as a reference and should not be used when installing equipment. Please ensure you locate the most recent instruction manual for accurate and up to date information.

2000 Series Specifications

Model	Length		Height		Depth		Supply				Heat Output		Max. Air Volume		Noise	Max. Door Height		Net Weight	
	[mm]	[in]	[mm]	[in]	[mm]	[in]	Volts	Phase	Hz	Amps	[kw]	[btuh]	[m3/h]	[cfm]	[dB]	[m]	[ft]	[kg]	[lbs]
2045	1137	45	198	8	275	11	240	1	60	0.5	N/A	N/A	1250	740	55	3	9' 10"	15	33
2066	1669	66	198	8	275	11	240	1	60	0.7	N/A	N/A	1800	1060	55	3	9' 10'	21	46
2087	2200	87	198	8	275	11	240	1	60	1	N/A	N/A	2500	1470	56	3	9' 10'	31	68
2045EH	1137	45	198	8	275	11	208	3	60	24.5	4.5 / 9	15,370 / 30,735	1250	740	55	3	9' 10"	16	35
2045EH	1137	45	198	8	275	11	480	3	60	10.9	4.5 / 9	15,370 / 30,735	1250	740	55	3	9' 10'	16	35
2045EH	1137	45	198	8	275	11	600	3	60	9.3	4.5 / 9	15,370 / 30,735	1250	740	56	3	9' 10'	16	35
2066EH	1669	66	198	8	275	11	208	3	60	32.7	6 / 12	20,490 / 40,980	1800	1060	55	3	9' 10"	23	51
2066EH	1669	66	198	8	275	11	480	3	60	14.5	6 / 12	20,490 / 40,980	1800	1060	55	3	9' 10'	23	51
2066EH	1669	66	198	8	275	11	600	3	60	12.8	6 / 12	20,490 / 40,980	1800	1060	56	3	9' 10'	23	51
2087EH	2200	87	198	8	275	11	208	3	60	49	9 / 18	30,735 / 61,470	2500	1470	55	3	9' 10"	33	73
2087EH	2200	87	198	8	275	11	480	3	60	21.7	9 / 18	30,735 / 61,470	2500	1470	55	3	9' 10'	33	73
2087EH	2200	87	198	8	275	11	600	3	60	18.6	9 / 18	30,735 / 61,470	2500	1470	56	3	9' 10'	33	73
2045WH	1137	45	198	8	275	11	240	1	60	0.5	3 / 6	10,245 / 20,490	1180	700	55	3	9' 10"	18	40
2066WH	1669	66	198	8	275	11	240	1	60	0.7	4.5 / 9	15,370 / 30,735	1700	1000	55	3	9' 10'	26	57
2087WH	2200	87	198	8	275	11	240	1	60	1	6 / 12	20,490 / 40,980	2360	1400	56	3	9' 10'	37	81
2047R	1200	47	205	8	347	14	240	1	60	0.5	N/A	N/A	1250	740	55	2.75	9'	19	42
2063R	1600	63	205	8	347	14	240	1	60	0.7	N/A	N/A	1800	1060	55	2.75	9'	25	55
2083R	2100	83	205	8	347	14	240	1	60	1	N/A	N/A	2500	1470	56	2.75	9'	35	77
2047EHR	1200	47	205	8	347	14	208	3	60	24.5	4.5 / 9	15,370 / 30,735	1250	740	55	2.75	9'	20	44
2047EHR	1200	47	205	8	347	14	480	3	60	10.9	4.5 / 9	15,370 / 30,735	1250	740	55	2.75	9'	20	44
2047EHR	1200	47	205	8	347	14	600	3	60	9.3	4.5 / 9	15,370 / 30,735	1250	740	56	2.75	9'	20	44
2063EHR	1600	63	205	8	347	14	208	3	60	32.7	6 / 12	20,490 / 40,980	1800	1060	55	2.75	9'	27	60
2063EHR	1600	63	205	8	347	14	480	3	60	14.5	6 / 12	20,490 / 40,980	1800	1060	55	2.75	9'	27	60
2063EHR	1600	63	205	8	347	14	600	3	60	12.8	6 / 12	20,490 / 40,980	1800	1060	56	2.75	9'	27	60
2083EHR	2100	83	205	8	347	14	208	3	60	49	9 / 18	30,735 / 61,470	2500	1470	55	2.75	9'	37	82
2083EHR	2100	83	205	8	347	14	480	3	60	21.7	9 / 18	30,735 / 61,470	2500	1470	55	2.75	9'	37	82
2083EHR	2100	83	205	8	347	14	600	3	60	18.6	9 / 18	30,735 / 61,470	2500	1470	56	2.75	9'	37	82
2047WHR	1200	47	205	8	347	14	240	1	60	0.5	3 / 6	10,245 / 20,490	1180	700	55	2.75	9'	22	49
2063WHR	1600	63	205	8	347	14	240	1	60	0.7	4.5 / 9	15,370 / 30,735	1700	1000	55	2.75	9'	30	66
2083WHR	2100	83	205	8	347	14	240	1	60	1	6 / 12	20,490 / 40,980	2360	1400	56	2.75	9'	41	90

USA: 2 Schwank Way, Waynesboro, GA 30830 | Canada: 5285 Bradco Blvd. Mississauga, ON L4W 2A6
Tel: 1-877-446-3727 | Fax: 1-866-361-0523 | www.schwankgroup.com | csr@schwankgroup.com



M120815 RL: v1.1 RD: Sept-2016